

उपहार सम्बन्धी सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	टोपी	क्याप टोपी (मल्टिकर)	प्रति थान
२	खादा	ढाकाको विभिन्न कलरको	प्रति थान
३	सल	पस्मिना / दोसल्ला	प्रति थान
४	टोपी	भादगाउँले	प्रति थान
५	टोपी	ढाका	प्रति थान
६	पर्स	ढाका	प्रति थान
७	थैली	कपडाको	प्रति थान
८	खुकुरी दाप सहित	६ ईञ्च	प्रति थान
९	खुकुरी दाप सहित	८ ईञ्च	प्रति थान
१०	खुकुरी दाप सहित	१० ईञ्च	प्रति थान
११	करुवा	०.५ लिटर कलामक ढलौट	प्रति थान
१२	करुवा	७" height and Plane design	प्रति थान
१३	मुर्ति	बुद्धको का.म.पा.को नाम र लोगो ईचिड गरी सिसाको फ्रेम भित्र ६ ईञ्चको	प्रति थान
१४	मुर्ति	बुद्धको का.म.पा.को नाम र लोगो ईचिड गरी सिसाको फ्रेम भित्र ८ ईञ्चको	प्रति थान
१५	मुर्ति	बुद्धको का.म.पा.को नाम र लोगो ईचिड गरी सिसाको फ्रेम भित्र १२ ईञ्चको	प्रति थान
१६	मुर्ति	बुद्धको का.म.पा.को नाम र लोगो ईचिड गरी बक्स सहित ४ ईञ्चको ढलौटको	प्रति थान
१७	मुर्ति	बुद्धको का.म.पा.को नाम र लोगो ईचिड गरी बक्स सहित ६ ईञ्चको ढलौटको	प्रति थान
१८	मुर्ति	बुद्धको का.म.पा.को नाम र लोगो ईचिड गरी बक्स सहित ८ ईञ्चको ढलौटको कलात्मक	प्रति थान
१९	मन्दिर	पशुपतिनाथको मन्दिर का.म.पा.को नाम र लोगो ईचिड गरी सिसाको फ्रेम सहित ६ ईञ्चको कलात्मक	प्रति थान
२०	मन्दिर	पशुपतिनाथको मन्दिर का.म.पा.को नाम र लोगो ईचिड गरी सिसाको फ्रेम भित्र ८ ईञ्चको कलात्मक	प्रति थान
२१	मन्दिर	पशुपतिनाथको मन्दिर का.म.पा.को नाम र लोगो ईचिड गरी सिसाको फ्रेम भित्र १२ ईञ्चको	प्रति थान
२२	मन्दिर	स्वयम्बुको आकृतिमा का.म.पा.को नाम र लोगो ईचिड सहित सिसा भित्र ६ ईञ्चको	प्रति थान
२३	मन्दिर	स्वयम्बुको आकृतिमा का.म.पा.को नाम र लोगो ईचिड गरी सिसाको फ्रेम भित्र ८ ईञ्चको	प्रति थान
२४	मन्दिर	स्वयम्बुको आकृतिमा का.म.पा.को नाम र लोगो ईचिडगरी सिसाको फ्रेम भित्र १२ ईञ्चको	प्रति थान
२५	मयुर झ्याल	काठको मयुर झ्याल ६ ईञ्चको कलात्मक	प्रति थान
२६	मयुर झ्याल	काठको मयुर झ्याल १० ईञ्चको कलात्मक	प्रति थान
२७	मयुर झ्याल	काठको मयुर झ्याल १२ ईञ्चको कलात्मक	प्रति थान
२८	मञ्जु श्री मुर्ति	का.म.पा.को नाम र लोगो ईचिड सहित ६ ईञ्चको कलात्मक ढलौट	प्रति थान
२९	माला	सयपत्री फुलको	प्रति थान
३०	बुके	टेबुल	प्रति थान
३१	बुके	बास्केट	प्रति थान
३२	गुच्छा	फुलको	प्रति थान
३३	रिवन(Ribbon)	कपडाको	प्रति मिटर
३४	पानस	ढलोट/ पितलको गणेशको मुर्ति भएको २७ इन्च अग्लो	प्रति थान
३५	फुलको रिद		प्रति थान
३६	फुल	विभिन्न दिवसमा हलिकप्टरबाट खसाल्ने	प्रति के जी
३७	बेलुन	विभिन्न दिवसमा उडाउने/सजाउने	प्रति थान

स्टेशनरी सम्बन्धी सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	कार्यालयको छाप	वाक्लो फममा गोलो र चारपाटे सेल्फ ईङ्क	प्रति थान
२	कार्यालयको छाप (रबर स्ट्याम्प)	वाक्लो रबरमा गोलो र चारपाटे	प्रति थान
३	नाम तथा पद लेखेको छाप	चारपाटे सेल्फ ईङ्क	प्रति थान
४	नेम प्लेट	प्लास्टिकको मिडियम साईज (८*१२ ईञ्च)	प्रति थान
५	नेम प्लेट	प्लास्टिकको ठुलो साईज (१८*२४ ईञ्च)	प्रति थान
६	नेम प्लेट	तामा/पितलमा इचिड गरेको मिडियम साईज (८*१२ ईञ्च)	प्रति थान
७	नेम प्लेट	तामा/पितलमा इचिड गरेको ठुलो साईज (१८*२४ ईञ्च)	प्रति थान
८	टेबल नेम प्लेट	आलमुनियमको	प्रति थान
९	टेबल नेम प्लेट	काठको	प्रति थान
१०	स्ट्याम्प प्याड	कालो/निलो ११० ७० एम एम	प्रति थान
११	व्याचहरू रिबन (१) कलर	विभिन्न कलरको रिबन	प्रति थान
१२	व्याचहरू रिबन (२) कलर	विभिन्न कलरको रिबन	प्रति थान
१३	व्याचहरू रिबन (४) कलर	विभिन्न कलरको रिबन	प्रति थान
१४	प्रमाणपत्र	कलर A४ साईज	प्रति थान
१५	प्रमाणपत्रको फ्रेम	गोल्डेन A४ साईजका लागि	प्रति थान
१६	फ्लेक्स ब्यानर विभिन्न साईज तथा डिजाईनको (प्रिन्ट मात्र)	मल्टिकलर	प्रति वर्ग फिट
१७	फ्लेक्स ब्यानर विभिन्न साईज तथा डिजाईनको (प्रिन्ट तथा फलामको फ्रेम सहित)	मल्टिकलर	प्रति वर्ग फिट
१८	भिजिटिङ् कार्ड	मल्टिकलर	प्रति थान
१९	निमन्त्रणा कार्ड	१ कलर	प्रति थान
२०	निमन्त्रणा कार्ड	मल्टिकलर	प्रति थान
२१	कपडाको ब्यानर	विभिन्न साईज (सुती)	प्रति मिटर
२२	महानगर झण्डा	६ फिट	प्रति थान
२३	महानगर झण्डा	४ फिट	प्रति थान
२४	महानगर झण्डा	१ फिट	प्रति थान
२५	महानगर झण्डा	१ फिट काठको स्टेण्ड सहित	प्रति थान
२६	नेपालको राष्ट्रिय झण्डा	६ फिट	प्रति थान
२७	नेपालको राष्ट्रिय झण्डा	४ फिट	प्रति थान
२८	नेपालको राष्ट्रिय झण्डा	१ फिट काठको स्टेण्ड सहित	प्रति थान
२९	नेपालको राष्ट्रिय झण्डा	१ फिट पित्तलको स्टेण्ड सहित	प्रति थान
३०	नेपालको राष्ट्रिय झण्डा	१० मिटर	प्रति थान
३१	नेपालको राष्ट्रिय झण्डा	८ मिटर	प्रति थान
३२	नेपालको राष्ट्रिय झण्डा	६ मिटर	प्रति थान
३३	नेपालको राष्ट्रिय झण्डा	१२ फिट	प्रति थान
३४	भिन्ने घडी	Analog, small size (12inch diameter)	प्रति थान
३५	भिन्ने घडी	Analog, medium size (18 inch diameter)	प्रति थान
३६	भिन्ने घडी	Analog, large size 24 inch diameter	प्रति थान
३७	डायरी	एक्जुकेटिभ	प्रति थान
३८	डायरी	स्पाइरल, Minimum ४० page	प्रति थान
३९	रजिस्टर	५० पाने ८० ग्राम पेपर उड फ्री	प्रति थान
४०	रजिस्टर	१०० पाने ८० ग्राम पेपर उड फ्री	प्रति थान
४१	माईन्युट रजिष्टर	बाहिरी कभरमा कपडाले बाइन्डिङ गरिएको १००पाने	प्रति थान
४२	खाम	भिन्न कपडा भएको फाइल Size नेपाली कागजमा का.म.पा.को नाम र लोगो प्रिन्ट भएको	प्रति थान
४३	खाम	A४ Size नेपाली कागजमा का.म.पा.को नाम र लोगो प्रिन्ट भएको	प्रति थान
४४	खाम	७"×५" इन्चको नेपाली कागजमा का.म.पा.को नाम र लोगो प्रिन्ट भएको	प्रति थान

४५	ट्रान्सपरेन्ट पेपर	A4 Size Binding Plastic paper	प्रति रिम
४६	रबर	१ के जी को	प्रति प्याकेट
४७	Photocopy work	single side (B/W)	प्रति पेज
४८	Photocopy work	both side (B/W)	प्रति पेज
४९	Photocopy Binding	२५० पेज सम्मको टेप बाइन्डिङ	प्रति थान
५०	Photocopy	A3 Size	प्रति थान
५१	Printing	A0 Size (90 GSM), Color Print	प्रति थान
५२	Printing	A1 Size (90 GSM), Color Print	प्रति थान
५३	टोनर रिफिल/cartridge Refill	refilling with original ink for cartridges used in all types of printers	प्रति थान
५४	बाइन्डिङ टेप	१ इन्ची	प्रति थान
५५	बाइन्डिङ टेप	१.५ इन्ची	प्रति थान
५६	बाइन्डिङ टेप	२ इन्ची	प्रति थान
५७	टेप	कार्टुन	प्रति थान
५८	टेप	सेलो सानो	प्रति थान
५९	टेप	सेलो मझौला	प्रति थान
६०	टेप	सेलो ठुलो	प्रति थान
६१	पेपर कटर	paper cutter with blade	प्रति थान
६२	पेन होल्डर/पेन स्ट्याण्ड	काठको	प्रति थान
६३	नेपाली पेपर	A४ Size २० ग्राम, १०० पानाको प्याड	प्याड
६४	नेपाली पेपर	A४ Size ४० ग्राम, १०० पानाको प्याड	प्याड
६५	मेटा कार्ड	Breadth 22.5cm and length 10.1cm Multi Color (Size in Approx.)	प्रति प्याकेट
६६	कार्ड होल्डर	डोरी सहित साधारण	प्रति थान
६७	स्ट्याम्प प्याड	११०*७० वर्ग मि.मि.	प्रति थान
६८	टेबल च्याक्र	प्लाष्टिकको तिन लेयर	प्रति थान
६९	डटपेन	मोनटेक्स वा सो सरह	प्रति थान
७०	जेलपेन	सेलो प्वाइन्टेक्स ०.५ कालो र रातो वा सो सरह	प्रति थान
७१	पाइलट पेन	V5 JF वा सो सरह कालो निलो रातो र हरियो	प्रति थान
७२	पाइलट पेन	V7 JF वा सो सरह कालो निलो रातो र हरियो	प्रति थान
७३	पाइलट पेन	V10 Grip Hi-Techpoint वा सो सरह कालो र रातो	प्रति थान
७४	मार्कर	बोर्ड मार्कर विभिन्न कलरका Snowman वा सो सरह	प्रति थान
७५	परमानेन्ट मार्कर	विभिन्न कलरको Snowman वा सो सरह	प्रति थान
७६	बोर्ड डस्टर		प्रति थान
७७	हाइलाइटर	विभिन्न कलरको स्टुटलर वा सो सरह	प्रति थान
७८	साइन पेन		प्रति थान
७९	पेन्सिल	HB	प्रति थान
८०	इरेजर		प्रति थान
८१	पेन्सिल कटर		प्रति थान
८२	टोनर मसि	Dust, Black	प्रति थान
८३	इन्डेक्स फायल	प्लाष्टिक हाई कभर	प्रति थान
८४	फोल्डर फायल	नमूनानुसार प्लाष्टिकको	प्रति थान
८५	रिंग फायल	ए ४ साइज, २ Ring Binder	प्रति थान
८६	फाइल तुना		प्रति मुठा
८७	रेकर्ड फाइल		प्रति थान
८८	कोब्रा फाईल		प्रति थान
८९	बक्स फाइल		प्रति थान
९०	नेपाली फाईल		प्रति थान
९१	फाइल बाइन्डिङ		प्रति थान
९२	फाइल स्ट्याण्ड		प्रति थान
९३	खाम	चेक साइज, सादा	प्रति थान
९४	कार्बन पेपर	केमेल वा सो सरह	प्रति प्याकेट
९५	फोटोकपी पेपर	A४ size ८० gsm , जे.के Copier वा सो सरह	प्रति रिम
९६	फोटोकपी पेपर	A३ size जे.के Copier वा सो सरह	प्रति रिम

९७	फोटोकपी पेपर	A४ size ८० gsm , जे.के Copier वा सो सरह कलरमा	प्रति रिम
९८	फोटोकपी पेपर	A४ size ७० gsm , जे.के Copier वा सो सरह कलरमा	प्रति रिम
९९	पोसिड पेपर	टास्ने, ५० सिट	प्रति थान
१००	Sticky Notes	1 Pack of Self-Stick Notes 0.6 x 3 Inch, 5 colorsx100 sheets	प्रति थान
१०१	थर्मल पेपर	e ticket को लागि प्रयोग हुने, ३ inch, ८० mm	प्रति रोल
१०२	पेपर क्लीप	१०० पिस प्रति प्याकेट	प्रति प्याकेट
१०३	वाईन्डिङ कभर पेपर	१०० पिस प्रति प्याकेट	प्रति प्याकेट
१०४	थम्बपिन		प्रति प्याकेट
१०५	प्लास्टिक स्केल	१५ cm	प्रति थान
१०६	प्लास्टिक स्केल	३० cm	प्रति थान
१०७	My Clear bag	प्लाष्टिकको बटन भएको,	प्रति थान
१०८	पन्चिड मेशिन ठूलो	कंगारो ८०० वा सो सरह	प्रति थान
१०९	पन्चिड मेशिन मझौला	८ सि.एम कंगारो ६०० वा सो सरह	प्रति थान
११०	स्टाप्पर मेशिन	सानो (No1-1m) कंगारो वा सो सरह	प्रति थान
१११	स्टाप्पर मेशिन	मझौतला ६०० HD-45 कंगारो वा सो सरह	प्रति थान
११२	स्टाप्पर मेशिन	ठूलो HD-23S 25 कंगारो वा सो सरह	प्रति थान
११३	स्टाप्पर पिन	मझौला २४/६ कंगारो वा सो सरहको १ बट्टा २० प्याकेट भएको	प्रति प्याकेट
११४	स्टाप्पर पिन ठूलो	ठूलो कंगारो वा सो सरहको १ बट्टा २० प्याकेट भएको	प्रति प्याकेट
११५	स्टाप्पर पिन	सानो कंगारो वा सो सरहको १ बट्टा, २० प्याकेट भएको	प्रति प्याकेट
११६	ग्लु स्टिक	Amos Korean वा सो सरह ३५ ग्राम	प्रति थान
११७	स्केल	स्टिल १८ इन्चको	प्रति थान
११८	टिप्पणी फाइल		प्रति थान
११९	सवारी लगबुक	६० ग्राम पेपरमा १०० पानाको प्याड	प्रति प्याड
१२०	आगन्तुक परिचय पत्र	Design and Print	प्रति थान
१२१	आगन्तुक परिचय पत्र	साधारण प्लास्टिक कभर भएको	प्रति थान
१२२	कर्मचारी अस्थायी परिचय पत्र		प्रति थान
१२३	बारकोड स्टीकर	१००० पिसको रोल	प्रति रोल
१२४	पिन रिमुभर		प्रति थान
१२५	पुस पिन		प्रति प्याकेट
१२६	हार्डकभर बाइन्डिङ	Minimum 100 page	प्रति थान
१२७	भिनाइल स्टिकर		प्रति ब फि
१२८	स्टिकर		प्रति ब फि
१२९	टेबुल घन्टी	Set	प्रति थान
१३०	आगन्तुक परिचय पत्र डोरी	नाइलन विभिन्न कलरको	प्रति के.जी.

कार्यालय मालसामान सम्बन्धी सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	Automatic Room Spray	liquid with Machine	प्रति थान
२	Automatic Room Spray	liquid only	प्रति थान
३	Abdominal Towel		प्रति थान
४	Plastic Dust Bin	१० लिटर क्षमता	प्रति थान
५	Plastic Dust Bin	१५ लिटर क्षमता	प्रति थान
६	Plastic Dust Bin	२० लिटर क्षमता	प्रति थान
७	Plastic Dust Bin	२५ लिटर क्षमता	प्रति थान
८	Plastic Dust Bin (सडकमा राख्ने)	८० लिटर क्षमताको पाङ्गा भएको	प्रति थान
९	Insect Killer Bat	rechargeable	प्रति थान
१०	Mosquito Repellent Machine	device with 45 ml liquid	प्रति थान
११	mosquito repellent liquid	४५ एम एल	प्रति थान
१२	Paper Cup	Minimum 150 ml	प्रति थान
१३	अविर	५० ग्राम	प्रति प्याकेट
१४	Floor Cleaner	एरोम्याक्स Equivalent	थान
१५	एसिड	dilulte HCl	प्रति लिटर

१६	कास्टिक सोडा		प्रति के जी
१७	कुचो	अमिसो	प्रति थान
१८	खरेटो	नरिवल वा सो सरह	प्रति थान
१९	कुशन	Minimum 1.5 x 1.5 sq ft	प्रति थान
२०	क्याल्कुलेटर(Calculator)		प्रति थान
२१	क्याल्कुलेटर(Calculator)	scientific calculator fx 991 es plus or equivalent	प्रति थान
२२	रिवल्विङ चियरको चक्रा	फिटिङ सहित	प्रति थान
२३	छाता	XXL Size, radius 30"	प्रति थान
२४	छाता	सानो फोल्डिङ गर्न मिल्ने	प्रति थान
२५	छाता	७ फिट अग्लो, गार्डेनिङ छाता	प्रति थान
२६	झोल साबुन		प्रति लिटर
२७	टेन्ट भाडामा		प्रति वर्ग फिट
२८	टेबुल घर्मी लक		प्रति थान
२९	टर्षाका	२ फिटको	प्रति थान
३०	टर्षाका	४ फिटको	प्रति थान
३१	ट्याकसुट(Tracksuit)	सेटमा कामपाको नाम र लोगो प्रिन्ट भएको	प्रति थान
३२	बर्षादी (Rain coat)	single piece / two piece	प्रति थान
३३	ट्वाईलेट ब्रस		प्रति थान
३४	डोर क्लोजर	हाइड्रोलिक	प्रति थान
३५	तकिया (सिरानी)	खोल सहित	प्रति थान
३६	तन्ना	Single Bed	प्रति थान
३७	तन्ना	Double bed	प्रति थान
३८	ताल्चा	Key Normal SS Link Lock, Padlock Size: 40 mm,	प्रति थान
३९	ताल्चा	padlock size 75 mm	प्रति थान
४०	दराज लक		प्रति थान
४१	धुप (अगरबत्ती)		प्रति प्याकेट
४२	पछाडी बोक्ने व्याग		प्रति थान
४३	पितलको गमला	7.5 inch hight and 8 in diameter	प्रति थान
४४	पुनिङ स	320 mm long, Permanently filed teeth , triple edge with plastic/wood handle	प्रति थान
४५	पेपर बेट		प्रति थान
४६	प्रमाण पत्रको काठको मैयुर फ्रेम		प्रति थान
४७	प्रोजेक्टर पोइन्टर	rechargeable, laser	प्रति थान
४८	फिनेल	सेतो झोल	प्रति लिटर
४९	फिनेल	दाना १/२ के.जी.	प्रति प्याकेट
५०	फिनेल	कालो झोल	प्रति लिटर
५१	प्लाष्टिक बाटा	२० लिटर	प्रति थान
५२	प्लाष्टिक बाटा	१० लिटर	प्रति थान
५३	प्लाष्टिक बाल्टिन	२० लिटर	प्रति थान
५४	प्लाष्टिक बाल्टिन	१० लिटर	प्रति थान
५५	Insect killer spray	बेगन Equivalent	प्रति थान
५६	बेतको लाठि		प्रति थान
५७	सुटकेश	१८ inch	प्रति थान
५८	सुटकेश	२२ inch	प्रति थान
५९	सुटकेश	२४ Inch	प्रति थान
६०	Hand carry Bag		प्रति थान
६१	भाडा धुने साबुन	६५ gm	प्रति थान
६२	भाडा माइने पाउडर	भिम वा सो सरह १/२ के जी	प्रति प्याकेट
६३	भुईँ पुछ्ने कपडा		प्रति थान
६४	मस्कूईटो क्याइल(Mosquito Coil)		प्रति थान
६५	मेजरिङ टेप	१०० मिटर कोमेलन वा सो सरह	प्रति थान
६६	मेजरिङ टेप	५० मिटर कोमेलन वा सो सरह	प्रति थान
६७	मेजरिङ टेप	३० मिटर कोमेलन वा सो सरह	प्रति थान

६८	मेजरिङ टेप	२५ मिटर कोमेलन वा सो सरह	प्रति थान
६९	मेजरिङ टेप	५ मिटर, komelon(ECO) or equivalent	प्रति थान
७०	रुम स्प्रे		प्रति थान
७१	रुम स्प्रे	एरोविक	प्रति थान
७२	ग्यास लाइट		प्रति थान
७३	लिक्विड हेण्ड वास	२०० एम.एल.	प्रति थान
७४	कपडा धुने साबुन	१०० ग्राम	प्रति थान
७५	लेदर अफिस व्याग	W15"*H11"*B5"	प्रति थान
७६	वाईपर	डण्डी सहित	प्रति थान
७७	डिटरजेन्ट पाउडर	१/२ के जी	प्रति प्याकेट
७८	डिटरजेन्ट पाउडर	१ के जी	प्रति प्याकेट
७९	सिङ्गी		प्रति थान
८०	सिरक	White Cotton, Single Bed खोल सहित	प्रति थान
८१	सिरक	White Cotton,Double bed खोल सहित	प्रति थान
८२	Blankets	Single Bed	प्रति थान
८३	Blankets	Double bed	प्रति थान
८४	डसना	Single Bed खोल सहित	प्रति थान
८५	डसना	Double Bed खोल सहित	प्रति थान
८६	सुतली		प्रति के जी
८७	टबाइलेट पेपर	१० रोलको	प्याकेट
८८	स्टिलको गमला		प्रति थान
८९	स्प्रे प्रिन्ट	४०० एम एल	प्रति थान
९०	दराजमा राखे हेडगार		प्रति थान
९१	Rat Poison/Rat Cake		थान
९२	Air Freshner	प्रति प्याकेट ४ पिस भएको ओडोनिल वा सो सरहको	प्याकेट
९३	कोरा कपडा		प्रति मिटर
९४	फलाटिन कपडा		प्रति मिटर
९५	ग्लास क्लिनर	कोलिन वा सो सरह ५०० ml	थान
९६	युरिन प्याड		थान
९७	झुल	डबल बेड	थान
९८	पि फर्म	8mm	मिटर
९९	पि फर्म	10mm	मिटर
१००	पि फर्म	12mm	मिटर
१०१	बेट टिस्यु	Packet	थान
१०२	सिल टेप(Seal Tape)		थान
१०३	सेनिटाइजर	100ml	थान
१०४	प्लास्टिकको गिलास	Minimum 200 ml	थान
१०५	सिक्रि	5*9 mm	प्रति मिटर
१०६	झुल	डबल बेड	प्रति थान
१०७	सिलिङ फ्यान		प्रति थान
१०८	बाल फ्यान		प्रति थान
१०९	स्ट्याण्ड फ्यान		प्रति थान
११०	दराज भित्र राखिने ह्याङ्गर	प्लाष्टिको	प्रति थान
१११	एयर पकेट		प्रति थान
११२	टीस्यु बक्स	सिल्भर कोटेड	प्रति थान
११३	भ्याकुम इन्सुलेटेड कप		प्रति थान
११४	डमी चेक		प्रति वर्ग फिट

किचनमा प्रयोग हुने सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	क्लोरीन पाउडर		के जी
२	Hotcase	5 litre	थान

३	Rice cooker	5 litre	थान
४	Rice cooker	10 litre	थान
५	Rice cooker	3 litre	थान
६	Tray/ किस्ती	plastic	थान
७	Tray/ किस्ती	स्टिलको	थान
८	अम्बोरा	तामाको	थान
९	ईलेक्ट्रिक थर्मस	५ लिटर	थान
१०	ईलेक्ट्रिक थर्मस	३.८ लिटर	थान
११	थर्मस	१ लिटर	थान
१२	एप्रोन	कपडाको भाँडा माइन्दा प्रयोग गर्ने	थान
१३	कचौरा	मेलामाइनको	थान
१४	कचौरा	ठुलो स्टिलको	थान
१५	कचौरा	सेरामिक्स	थान
१६	कचौरा	सानो स्टिलको	थान
१७	कप	सिसाको ६ पिसको १ सेट	सेट
१८	कप	सेरामिक्स ६ पिसको १ सेट	सेट
१९	प्लेट	मेलामाइन, Min १० inch dia	थान
२०	प्लेट	सेरामिक्स, Min १० inch dia	थान
२१	प्लेट	स्टिलको ठुलो, Minimum १५ inch dia	थान
२२	प्लेट	स्टिलको सानो, min ८ inch dia	थान
२३	कपसेट	स्टिलको ६ पिसको १ सेट	सेट
२४	कफि	१ केजी प्याकेट	के.जी
२५	कफि बिनस	१ केजी प्याकेट	के.जी
२६	कोरेशा		थान
२७	कितली	२ लिटर	थान
२८	खलो	मिडियम साइजको	थान
२९	चक्रे	काठको बिँड भएको	थान
३०	गाभ्री	तामाको २ केजीको १८ इन्च उचाई भएको	थान
३१	ग्यास चुलो	Single burner stainless steel	थान
३२	ग्यास चुलो	Double burner stainless steel	थान
३३	ग्यास चुलो	Double burner, Automatic, stainless steel	थान
३४	ग्यास पाइप	ISO certified	प्रति मिटर
३५	ग्यास रेगुलेटर	Iso certified	थान
३६	ग्रेन टी	प्रति के.जी.	थान
३७	ग्रेन टी पट	१.०० एम एल	थान
३८	चपिड बोर्ड		थान
३९	चप्पल		जोर
४०	चम्चा	Steel Material	थान
४१	चिम्टा	Steel Material	थान
४२	चिया छान्ने जाली	Steel material	थान
४३	चिया पत्ति		प्रति के.जी.
४४	चुलो	ईण्डक्सन १ बर्नर	प्रति थान
४५	चुलो	ईन्फ्रारेड १ बर्नर	प्रति थान
४६	जर्किन	१० लिटर, Plastic	थान
४७	जर्किन	२० लिटर, Plastic	थान
४८	झाझर	Steel	थान
४९	टि म्याट	६ थानको सेट	सेट
५०	टिस्यू पेपर	१०० pulls premium वा सो सरह	थान
५१	ट्वाइलेट पम्प		थान
५२	डस्ट पिकर(Dust Picker)	प्लास्टिकको	थान
५३	डस्ट पिकर(Dust Picker)	स्टिलको/टिनको	थान
५४	डाडु	स्टिलको	थान

५५	पन्थु	स्टिलको	थान
५६	डिब्बा	मसला राख्ने प्लास्टिकको	थान
५७	डेक्ची	१० लिटर, आल्मोनियम/सिल्भर	थान
५८	डेक्ची	५ लिटर आल्मोनियम/सिल्भर	थान
५९	डेक्ची	३ लिटर आल्मोनियम/सिल्भर	थान
६०	ड्रम	प्लास्टिकको १०० लिटर	थान
६१	ताप्ले	स्टिलको २ लिटर	थान
६२	ताप्ले	स्टिलको ३ लिटर	थान
६३	ताप्ले	ननस्टिकी २ लिटर	थान
६४	तावा	फलामको	थान
६५	थाल	स्टिलको	थान
६६	पानी खाने गिलास	स्टिलको, Min २०० ml	थान
६७	पानी खाने गिलास	सिसाको, Min २०० ml	थान
६८	पानी खाने बोटल	भिन्न बाहिर तामा भएको १ लिटर minimum क्षमताको	थान
६९	पानी खाने बोटल	प्लास्टिकको, १ Liter minimum	थान
७०	पानी खाने सिसाको जग	१ लिटर, Borosil or equivalent	थान
७१	पानी खाने स्टिलको जग	१ लिटर	थान
७२	मग	प्लास्टिकको	थान
७३	प्रेसर कुकर	५ लिटर	थान
७४	प्रेसर कुकर	१० लिटर	थान
७५	प्रेसर कुकर	३ लिटर	थान
७६	प्रेसर कुकर ननस्टिकी	५ लिटर नन स्टिक	थान
७७	प्रेसर कुकर ननस्टिकी	१० लिटर	थान
७८	प्रेसर कुकर ननस्टिकी	३ लिटर	थान
७९	कराइ	३ लिटर नन स्टिक	थान
८०	कराइ	५ लिटर नन स्टिक	थान
८१	पिताम्बरी	१०० ग्राम	प्याकेट
८२	प्लाष्टिक मिनी स्टुल		थान
८३	फ्राइप्यान	ननस्टिक	थान
८४	बेलना चौकी		थान
८५	भिन्न तामा भएको जग	१ लिटर	थान
८६	भुइ पुच्छने रुमाल		थान
८७	फ्लोवर क्लिनर	लाइजोल वा सो सरह ५०० एम एल	थान
८८	लाईटर	साधारण	थान
८९	वाटर डिस्पेन्सर	तातो चिसो आउने ईलेक्ट्रोनिक	थान
९०	स्टील उल(भाडा माइने झाली)		थान
९१	इलेक्ट्रिक जग	minimum १.५ लिटर	थान
९२	gaskate	प्रेसर कुकरको	थान
९३	टेबुल वा भाडौँ पुछ्ने टाबेल	१.२ वर्ग फिटको	थान

फर्निचर अन्य सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	हवाईट बोर्ड	४X २ वर्ग फिट	थान
२	कुर्सी	हात भएको काठको	थान
३	कुर्सी	हात नभएको काठको	थान
४	कुर्सी	फोल्डिङ गर्न मिल्ने स्टिलको	थान
५	Revolving Chair	साधारण	थान
६	Revolving Chair	Heavy	थान
७	Revolving Chair	Executive	थान
८	Tea Table	काठको २x४ वर्ग फिट	थान
९	Table	Executive	थान

१०	Office Table	काठको २.५x४ वर्ग फिट	थान
११	Office Table	काठको ३x५ वर्ग फिट	थान
१२	Computer Table	काठको २x३ वर्ग फिटको	थान
१३	Table	काठको चार खुट्टा भएको २.५x३ वर्ग फिटको	थान
१४	दराज	Metal २० Guage, ५ फिट उचाई भएको	थान
१५	दराज	Supplying and Fixing of approved good quality lockable steel Glassdoor Cupbord of size (5'6"x2'.8"or morex1'x8") iron used in 20 guage and shutter	थान
१६	दराज	metal २० Guage, ४.५ फिट उचाई भएको	थान
१७	दराज	Supplying and Fixing of approved good quality lockable steel Cupbord of size (5'6"x2'.8"or morex1'x8") iron used in 20 guage and shutter	थान
१८	दराज	Glass Door २० Guage, ६ फिट उचाई भएको	थान
१९	File Cabinet	Supplying and Fixing of central locking mild steel file cabinet containing 4 layer of size (4'Hx2'wx1'6")	थान
२०	Open Rack	Supplyong and fixing of approved good Quality open rack of size (6'x3'x1'8") iron used in 20 guage	थान
२१	Rack	open wood फरमाइका जडान गरेको फिटिङ्ग समेत १८ एम एम को बोर्ड भएको	प्रति वर्ग फिट
२२	डोर म्याट	जुटको	थान
२३	डोर म्याट	Fancy	थान
२४	अल्टिमेट डोर म्याट		वर्ग फिट
२५	कार्पेट	फिटिङ सहित साधारण	वर्ग फिट
२६	कार्पेट	फिटिङ सहित बुट्टेदार	वर्ग फिट
२७	कार्पेट	फिटिङ सहित डिलक्स	वर्ग फिट
२८	टाट/प्लास्टिक कार्पेट	फिटिङ सहित	वर्ग फिट
२९	कार्पेट	क्यालियो	वर्ग फिट
३०	पर्दा	फिटिङ सहित साधारण	मिटर
३१	पर्दा	फिटिङ सहित कटन	मिटर
३२	पर्दा	फिटिङ सहित डिलक्स	मिटर
३३	पर्दा	फिटिङ सहित भर्टिकल	वर्ग फिट
३४	सोफा सेट	५ सिटर क्षमता रेक्जिन जडान गरीएको फिटिङ सहित	सेट
३५	चकटी कुसन	१.५x१.५ वर्ग फिटको	थान
३६	पर्दाको डण्डी	इनामेल कोटेड	मिटर
३७	Flag Stand	5 feet wood's stand	थान
३८	Plastic Chair on rent		थान
३९	साइन बोर्ड		प्रति वर्ग फिट
४०	उजुरी पेटिका	काठको	थान
४१	सूचना पाटी notice board		प्रति वर्ग फिट
४२	भन्याड	आलुमिनिको नन फोल्डिङ १८ फिट	थान
४३	भन्याड	आलुमिनिको नन फोल्डिङ २४ फिट	थान
४४	भन्याड	आलुमिनिको नन फोल्डिङ ६ फिट	थान
४५	भन्याड	आलुमिनिको फोल्डिङ १२ फिट	थान
४६	भन्याड	आलुमिनिको फोल्डिङ १८ फिट	थान
४७	भन्याड	आलुमिनिको फोल्डिङ २४ फिट	थान
४८	भन्याड	काठको १२ फिट	थान
४९	भन्याड	आलुमिनिक डबल साईड ६ फिट	थान
५०	भन्याड	आलुमिनियम डबल साईड ८ फिट	थान
५१	कोट हेंगर	काठको	थान
५२	कोट हेंगर	स्टिलको	थान
५३	इस्टुल	स्टिलको	थान
५४	भाडा राख्ने न्याक	स्टिलको	थान
५५	Visitor bench	3 seater, metallic	सेट
५६	फुट स्टेप(Foot Step)	फलामको double step	थान
५७	पर्दा सपोर्ट		थान
५८	ग्लिप पेच		थान

५९	फलामको बेड	सिंगल बेड	थान
६०	Mattress	Single bed	थान
६१	Mattress	Double bed	थान
६२	काठको पलङ	सिंगल बेड	थान
६३	काठको पलङ	डबल बेड	थान
६४	लो बेड	सिंगल बेड	थान
६५	लो बेड	डबल बेड	थान
६६	टेबुल सिसा	8 mm	प्रति वर्ग फिट
६७	Convex Mirror (traffic)	18 Inch diameter	प्रति थान
६८	Convex Mirror (traffic)	24 Inch diameter	प्रति थान
६९	Convex Mirror (traffic)	30 inch diameter	प्रति थान
७०	Convex Mirror (traffic)	32 inch diameter	प्रति थान
७१	Embossed (raised) Metal	silver or Golden colour lettering (Measured inch-word horizontally)	प्रति इन्च
७२	Embossed (raised)	2mm thick vinyl acrylic (Measured circular diameter inch)	प्रति इन्च
७३	प्लाष्टिकको कुर्चि		थान
७४	कण्डम बक्स	काठको	थान
७५	सुझाव पेटिका	काठको	थान
७६	फाइबर सिट	८ एम एम	वर्ग फिट
७७	फाइबर सिट	६ एम एम	वर्ग फिट

विद्युतीय सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	AC/DC Digital Clamp Meter	Data Hold Display :6000 counts LCD with double color backlight AC Current:4A/40A/400A/600A AC Voltage:4V/40V/400V/600V DC Voltage:400mV/4V/40V/400V/600V Resistance: 400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ Capacitance:4nf/40nf/400nf/4μF/40μF/400μF/4mf Non-contact voltage detection, Diode test Data Hold Auto power off With backlight function With flash light function With lower battery indication function	प्रति थान
२	Battery	AA	प्रति जोर
३	Battery	AAA	प्रति जोर
४	Tester	Voltage: AC 100-500V; approx Size: 131 x 15mm /5.16 x 0.6 Inch(L*D)	प्रति थान
५	पावर सकेट	बक्स सहित १६ एम्पियर	प्रति थान
६	पेचकस	सेट, 31 in 1 magnetic multifunction standard screw driver set	प्रति सेट
७	होल्डर	Bulb Holder B22 to E27 pin to Screw	प्रति थान
८	फ्रिजको रयाँस फेरको		प्रति थान
९	ए सी को रयाँस फेरको	up to 1.5 ton	प्रति थान
१०	ए सी को रयाँस फेरको	2 ton	प्रति थान
११	Tea Electric Kettle	stainless steel Electric kettle	प्रति थान
१२	केबल टाई	100 pcs/packet 2.5mm*150mm self-Locking Nylon wire Cable Zip Ties Cable Ties	थान
१३	क्ल्याम्पर	3 in 1 Heavy duty crimping tool and stripper	थान
१४	Flash/Touch Light	Rechargeable Led Flash/touch Light	थान
१५	Plier	High Leverage Plier	थान
१६	Multimeter	Multimeter Voltage, Current, Resistance Tester Buzzer Led Backlight With Non Contact Buzzer	थान
१७	Lux Meter	Measure in lux or foot-candles, with one button to switch between display options Measuring range up to 200,000 Lux or 20,000 foot candles Data hold to freeze reading on the digital display Min/max ability to show high and low readings Auto power off to save battery life Includes protective sensor cap	थान

१८	Contactor	Heavy duty power contactor with silver alloy contacts - Volts 220 AC - 3 Pole - Copper coil heavy duty Contactor with silver alloy Wire Connector (32 Amps 3pole) 32 Amps 3pole	थान
१९	ProgramableTimer Switch for Street Light Parking lights Glow Sign Boards	Digital ProgramableTimer switch provides user to set single ON - OFF time between 24 Hrs User friendly Keypad & LED display helps user to set ON OFF & Real timings from 00.00 to 23.59 Hrs. Timer works on single phase supply voltage 190VAc to 250VAc Timer is suitable for Output load capacity upto 32 Amps Auto/Manual mode operations available mainly usefull for street lights,parking lights,led glow sign boards,water motors & many more	थान
२०	Street Light Timer Astronomical	Big LCD Display with backlight shows Date, Time, On Time, Off Time Simple and Easy To Understand Intutive Keys on the font panel Basement Mode enables user to advance On Time and prolong Off Time by 15 Min. This mode is specifically designed to address challenges of Low Light Areas like Starcases, Basement Parking etc Most Suuitable for Street Lights, Staircase/ Parking Lights On- Off, Hoarding Lights On-Off, Water Pump/ Sprinkler On-Off, load capacity upto 32 Ams	थान
२१	25 sq mm 3 core ABC Cable	3 core, 25 sq mm	र.मि.
२२	Street light arms/stand, minimum 0.7 mtr long		set
२३	Installation of street light		set
२४	Day night sensor for auto on-off for street light and other light		Nos
२५	Bed switch		Nos
२६	Bulb cover umbrella		Pcs
२७	16 amp contractor 3/4p		Nos
२८	Safety gloves		pair
२९	Pendent holder screw type		nos
३०	Pendent holder pin type		nos
३१	Metal body street light bulb cover		nos
३२	Plastic body street light bulb cover		nos
३३	Light number plate		nos
३४	22-30 watt printed circuit board (PCB) Osram, Philips or equivalent		set
३५	40-50 watt printed circuit board (PCB) Osram, Philips or equivalent		set
३६	100-120 watt printed circuit board (PCB) Osram, Philips or equivalent		set
३७	20-30 watt high quality LED powered driver		set
३८	40-50 watt high quality LED powered driver		set
३९	100-120 watt high quality LED powered driver		set
४०	Installation of street light (with minimal maintenance)		set

हार्डवेयर सम्बन्धी मालसामानहरु

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	अन्तराप	६ ईञ्च	प्रति थान
२	अन्तराप	८ ईञ्च	प्रति थान
३	अन्तराप	१२ ईञ्च	प्रति थान
४	हतौडा	बिड सहित ५०० ग्रामको	प्रति थान
५	हतौडा	हेमि बिड सहित एक केजीको	प्रति थान
६	पेच कस (Screw Driver)	मार्डनस प्लस भएको ८ ईञ्चको	प्रति थान
७	पेन्चिस /पिलास(Pliers)	६ ईञ्च	प्रति थान
८	पेन्चिस /पिलास(Pliers)	८ ईञ्च	प्रति थान
९	ड्रिल मेसिन	१० एम एम	प्रति थान
१०	ड्रिल मेसिन	१३ एम एम	प्रति थान

११	पाईप	नाइलन १ इन्चको	प्रति रोल
१२	एडजस्टेबल रेन्च (Wrench)	सानो ८" / २०० एम एम	प्रति थान
१३	ब्लेड	ढलान काट्ने	प्रति थान
१४	ब्लेड	घाँस काट्ने (१ सेट बराबर २ पिस)	प्रति थान
१५	पञ्जा	छालाको बाक्लो	प्रति जोडी
१६	डोरी	पिड	प्रति रोल
१७	डोरी	नाइलन	प्रति के.जी.
१८	डोरी	जुटको	प्रति के.जी.
१९	डोरी	प्लास्टिकको	प्रति मुठा
२०	पानी टयाङ्गी	हिलटेक वा सो सरह	प्रति लिटर
२१	तारपिन तेल		प्रति लिटर
२२	एक पाङ्ग्रे गाढा	Material: Steel, Enamel Coated, Single Wheel, Dimension : 1370mm * 470mm * 590mm, Pneumatic Wheel Diameter 360mm	थान
२३	चोयाको थुन्से	Height 18", top diameter 18" and base diagonal dimensions 10", and weight at least 900gm	थान
२४	खुर्पा	Full metal body, Weight at least 750 gm, Handle length 5" and height 10"	थान
२५	हसिया	Full metal body, Weight at least 300 gm, Handle length 6" and height 9"	थान
२६	कुटो पाटे चुच्चे	GI pipe handle of 1" diameter and length of 12", चुच्चे side length 4.5" र फटे length 4" and width 2"	थान
२७	साबेल चारपाटे	Full metal body(Grip Handle, Shaft, Collar, Blade), Blade size 12"*9", Shaft Length 21", Shaft Diameter 1.5" and Handle Grip of Length 7" and Width 4.5"	थान
२८	साबेल चुच्चे	Full metal body, Blade size from step to tip 12", width of blade 9", Shaft Length 21", Shaft Diameter 1.5" and Handle Grip of Length 7" and Width 4.5"	थान
२९	गल	5' in length, full solid metal body, 6.8 kg in weight	थान
३०	पिक बिड सहित	Weight of pickaxe only 2.1kg, weight with handle 2.7 kg, wooden handle length of 29", Pickaxe should have chisel end, pick end and eye for inserting the wooden handle	थान
३१	त्रिपाल बुडेदार (सानो १२'x१५')	12'*15' in size, checked pattern, edges are rope reinforced, eyelets at every corner	थान
३२	त्रिपाल बुडेदार (ठूलो १५'x२१')	15'*21' in size, checked pattern, edges are rope reinforced, eyelets at every corner	थान
३३	बोल्ड कटर	Size 18", Rubber handle, adjustable jaws, Cr-V or Cr-Mo material (INGCO brand or equivalent)	थान
३४	बोरा	Made up of plastic and should handle 100 kg of filling weight	थान
३५	कोदालो बिड सहित	Weight of spade only 0.9kg, weight with handle 1.4 kg, wooden handle length of 29", Spade should have chisel end and eye for inserting the wooden handle	थान
३६	हाते करैति	Pruning saw, 320 mm length, permanently filed teeth, triple edge with plastic/wooden handle (Ingeo Brand or Equivalent)	थान
३७	नरिवलको झाडु	3' in length and minimum weight should be 300 gm	थान
३८	सेफ्टि बेल्ट	Single attachment, D- type	थान
३९	फुल गमबूट(छाती सम्मको)	Lightweight, waterproof, Color: Nepal Army, Material : Nylon reinforced PVC, Style : Hip Waders, Cleated Sole and Elastic Waist Band trousers, size 37-44 range	थान
४०	भर्याङ्ग	Aluminum, 12' length, width of step 15" and 12" between two steps	थान
४१	रिफ्लिक्टभ ज्याकेट	2 side pockets with zippers, two lines of high reflective tape of 1.5" width along the waist and chest lines, one zipper vertically in the middle, black color collar, inner layer of net cloth(black) and protection around the sleeves opening, KMC logo and name print	थान
४२	रबरको पन्जा	(finger and palm rubber coated)	जोडी
४३	रबरको पन्जा	long upto fore arm	जोडी
४४	सेफ्टि हेलमेट	Hard helmet, With chin strap, adjustable head buckle, color should be as specified by office	थान
४५	लाईफ ज्याकेट	adjustable elasticity, equipped with safety buckles, reflective strips, suitable for adults upto 100kg weight, with head support	थान
४६	पोखरीको पानी फाल्ने पम्प	submersible pump, 1 HP Italian brand	थान
४७	मास्क	Disposal Mask (Per Piece specifications : 3 layers, size 17.5cm* 9.5cm, with elastic ear loop and nose pin, melt blown filter), 50 PCs Box	प्याकेट
४८	तौल गर्ने मेसिन ३०० केजी क्षमता	Maximum 300 kg, approved by Nepal Bureau of Standards and Metrology Department, Digital measurement, Chargable	थान
४९	कौटा (Rake) 1.5 meter length	9 teeth, 5" tooth length and 15" total length of garden rake 15", with light steel pipe ½" handle of 5' length	थान

५०	काँटा (Rake) 3 meter length	9 teeth, 5" tooth length and 15" total length of garden rake 15", with light steel pipe ½" handle of 9' length	थान
५१	डस्ट प्यान (जस्ता पाता)	handle 4", length of pan 9", top width 7.5", bottom width 9", material tin	थान
५२	लामो बिड र ब्रस भएको मफ	5' handle	थान
५३	बिड सहितको नेट	metal/wooden handle of at least 3' length, net gap 1cm*1 cm, nylon net	थान
५४	डोरी १" साईजको	Nylon	केजी
५५	तार ब्रस	wired brush	थान
५६	च्वाफी लौरो सहितको	5' firm and solid wooden stick	थान
५७	प्लाष्टिकको ब्रस (लट्टी सहितको)	at least 5' handle	थान
५८	बन्चरो	800 gm forged metal, wooden handle of at least 32 "	थान
५९	फोहोर उठाउने २ चक्रे गाडा	made up of 40kg (minimum) (except wheels) of mild steel, hollow pipe handles, tapering at bottom sides, 2 leg stands, 2 wheels of appropriate dia and type	थान
६०	गारवेज प्लाष्टिक	100 litre capacity	थान
६१	छाता ठुलो	xxl size radius 30"	थान
६२	गाडेन पाईप १/२"	Flexible pipe, 0.5" dia	रोल
६३	तार कटर १०"	10" size , max opening 40mm	थान
६४	तार कटर १८"	450mm size, cutting capacity upto 10mm	थान
६५	ब्याट्रीबाट चल्ने करौती, २ थान ब्याट्री र चार्जर सहित	cordless chain saw, 40v , bar length 16", chain speed 14.5m/s, auto lubrication (Ingeo brand or equivalent)	थान
६६	ग्राइन्डर (ब्याट्रीबाट चल्ने), २ थान ब्याट्री र ६ थान चक्का, चार्जर सहित	cordless grinder machine, 4" inch disc, 20v battrey (Ingeo brand or equivalent)	थान
६७	गारवेज प्लाष्टिक	100 litre capacity	थान
६८	स्प्रे पम्प (चार्जवाला) १६ लिटर	16 litres capacity, automatic, chargable	थान
६९	स्प्रे पम्प २ लिटर (हाते)	2 ltr capacity, adustable nozzle, at least 2.5BAR pressure	थान
७०	गाडाको पाङ्ग्रा, ट्युब सहित	Wheel Diameter 360mm, tolerance : ±50mm	थान
७१	डस्टबिन १४० लिटर(पाङ्ग्रावाला)	LLDPE Plastic Dustbin with wheels, capacity 140 litres, base 21"*18", Top lid 29"*28", Height 42", product weight of 16 kg, handle and wheel installed	थान
७२	पन्जा डिसपोजेबल	Latex Disposable Gloves Box ,single wall thickness 0.12mm (100 Pcs in 1 Box)	प्याकेट
७३	गम बुट	waterproof, rubber sole, approx height 11", black in color	जोडी
७४	साबुन	bathing soap, weight 75 gm, Dettol or equivalent	थान
७५	क्याप टोपी	with KMC name and logo, department name in nepali	थान
७६	तैलिया	at least 1.5m*0.5m in dimension	थान
७७	फिनेल	White liquid	लिटर
७८	मालाथिन	Malathion 50% EC	लिटर
७९	सेन्ट्रानोल	equivalent to citronella oil produced by HPPCL	लिटर
८०	Beneficial Microbes	Yeast & mold 2.4X10 ^{^3} cfu/ml, Total plate count 2.8X10 ^{^7} cfu/ml, Bacillus sps 9.9X10 ^{^4} cfu/ml, Pseudomonas sps 2.1X10 ^{^3} cfu/ml, Lactobacter sps 3.21X10 ^{^3} cfu/ml, Trichoderma sps 2.3X10 ^{^3} cfu/ml, E. Coli - Nil, Salmonella sps - Nil, Shigella sps - Nil, pH : 3.0-6.0, base: Liquid based	लिटर
८१	झिँगा मार्ने औषधी	20g packet, acetamiprid 20% SP	प्याकेट
८२	फाल्कोन कैंची	Stainless steel, total length 570mm(±50mm), blade length 250 mm (±30mm)	थान
८३	होज पाईप २"	Hose pipe of dia 2", minimum pressure 8 BAR	मिटर
८४	सेफ्टी चश्मा	anti fog, anti scratch, UV protection	थान
८५	Bleaching Powder		केजी
८६	Bleaching liquid		लिटर
८७	Bleaching powder	ड्रम वाला	के.जी.
८८	फिटकिरी		के.जी.
८९	Water pack System		के.जी.
९०	टि.टि.सी.ए.	९० प्रतिशत	के.जी.
९१	पोलि एल्मुनियम क्लाराईड		लिटर
९२	पि.एन. १० पाइप		प्रति मिटर
९३	चुना	२० के जी को बोरा	प्रति बोरा

९४	डस्टबिन	70 ltr capacity, Base 12.5"*12.5", Top lid 17.5"*17.5", Total Height 29.5", Height without lid 22.5",4.5 kg product weight, with opening on both sides of top lid	थान
९५	डस्टबिन	Stainless Steel, swing type, size (14*28)"	थान
९६	डस्टबिन	Stainless Steel, swing type, size (12*28)"	थान

खेलकुद सम्बन्धी सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	भलिबल नेट	Standard Size	प्रति थान
२	भलिबल	५ नं.	प्रति थान
३	भलिबल पोल		प्रति थान
४	भलिबल म्याट		प्रति थान
५	फुटबल	५ नं.	प्रति थान
६	ब्याटमिन्टन च्याकेट	भेनस वा सरह	प्रति थान
७	ब्याटमिन्टन जाली	भेनस वा सो सरह	प्रति थान
८	ब्याटमिन्टन कक	भेनस वा सो सरह	प्रति थान
९	ब्याटमिन्टन पोल		प्रति थान
१०	T-Shirt Print सहितको	साधारण	प्रति थान
११	T-Shirt Print सहितको	collar	प्रति थान
१२	चेस	गोटी सहित	प्रति थान
१३	चेस	गोटी मात्र	प्रति थान
१४	क्रिकेट बल		प्रति थान
१५	लुडो		प्रति थान
१६	क्यारमबोर्ड गोटी		प्रति थान
१७	Skiping Rope(स्किपिङ रोप)		प्रति थान
१८	क्रिकेट ब्याट		प्रति थान
१९	क्रिकेट स्टम्प		प्रति थान
२०	क्रिकेट हेलमेट		प्रति थान
२१	क्रिकेट ग्लोव्स		प्रति थान
२२	क्रिकेट प्याड		प्रति थान
२३	क्रिकेट गाई		प्रति थान
२४	ब्राम प्याड		प्रति थान
२५	क्यारम बोर्ड	४*४ वर्ग फिटको	प्रति थान
२६	क्यारमबोर्ड पाउडर		के जी
२७	टेबल टेनिस बल		प्रति थान
२८	टेबल टेनिस ब्याट		प्रति थान
२९	टेबल टेनिस बोर्ड	९*५ वर्ग फिट	प्रति थान
३०	टेबल टेनिस नेट		प्रति थान
३१	कराते म्याट		प्रति थान
३२	फुटबल बुट		प्रति थान
३३	जर्सी	का.म.पा.को नाम र लोगो प्रिन्ट सहित	प्रति थान
३४	फुटबल मोजा		प्रति थान
३५	खेलकुद क्याप	का.म.पा.को नाम र लोगो प्रिन्ट सहित	प्रति थान
३६	सिटी	डोरी सहित	प्रति थान
३७	फुटबल गोल पोष्ट		थान
३८	फुटबल कोन		थान
३९	फुटबल नेट		थान
४०	बास्केट बल		थान
४१	बास्केट बल नेट		थान
४२	किप्पर ग्लोभ्स		जोर
४३	फस्ट एड बक्स		थान
४४	बक्सिङ ग्लोभ्स		जोर
४५	योगा म्याट	२*६ वर्ग फिटको	थान

४६	योगा म्याट	४*६ वर्ग फिटको	थान
----	------------	----------------	-----

सूचना प्रविधि सम्बन्धि सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकाई
१	5 Port Network Gigabyte Switch	Port: Min. 5x10/100/1000Mbps Rj 45 Interface or better; metal chasis, Warranty: 1 year warranty or more.	प्रति थान
२	4 port PoE switch with SFP Uplink	Port: Min. 4x10/100/1000Mbps PoE Rj 45 Interface and 2x Gig SFP Interface; Budget Power: 60 w min; Warranty: 1 year warranty or more.	प्रति थान
३	4 port PoE switch with SFP/Rj45 Uplink	Port: Min. 4x10/100/1000Mbps PoE Rj 45 Interface and 2 x RJ45 Uplink or 1 x SFP, 1x Rj45 Uplink Interface; Budget Power: 60 w min; Warranty: 1 year warranty or more.	प्रति थान
४	8 Port PoE Switch with Gigabit Uplink	Port: Min 8x 10/100/1000Mbps PoE Rj45 Interface and 2-port Gig RJ45 Interface, Budget Power: 90W min; Warranty: 1 year or more	प्रति थान
५	8 Port PoE Switch with SFP & Ethernet	Port: Min 8x 10/100/1000Mbps PoE Rj45 Interface and 2-port Gig RJ45 + 2-port Gig SFP Interface, Budget Power: 110W min; Warranty: 1 year or more	प्रति थान
६	16 Port PoE Switch with SFP & Ethernet Uplink	Port: Min 16x 10/100/1000Mbps PoE Rj45 Interface and 2-port Gig RJ45 + 2-port Gig SFP Interface, Budget Power: 185W min; Warranty: 1 year or more	प्रति थान
७	24 Port PoE Switch with SFP & Ethernet Uplink	Port: Min 24x 10/100/1000Mbps PoE Rj45 Interface and 2-port Gig RJ45 + 2-port Gig SFP Interface, Budget Power: 285W min; Warranty: 1 year or more	प्रति थान
८	8 port gigabyte managed switch with PoE	Ports: At least 8x10/100/1000Mbps PoE RJ 45 Interface; 2x Gig SFP interface and 1x Console port or better, L3 Lite Managed via CLI and GUI(Web), Telnet, SSH, MAC: 8K, PoE power budget: 140W or more ;Warranty: 1 year warranty or more.	प्रति थान
९	24 port gigabyte managed switch with PoE	Ports: At least 24x10/100/1000Mbps PoE RJ 45 Interface; 4x Gig SFP, RJ45 combo interface and 1x Console port or better, L3 Lite Managed via CLI and GUI(Web), Telnet, SSH, MAC: 8K, PoE power budget: 370W or more; Warranty: 1 year warranty or more.	प्रति थान
१०	48 port gigabyte managed switch with PoE	Ports: At least 48x10/100/1000Mbps PoE RJ 45 Interface; 4 x Gig SFP interface and 1x Console port or better, L3 Lite Managed via CLI and GUI(Web), Telnet, SSH, MAC: 8K, PoE power budget: 740W or more; Warranty: 1 year warranty or more.	प्रति थान
११	8 Port Network Gigabyte switch	Ports: At least 8x10/100/1000Mbps Rj 45 Interface or better.; metal chasis, Warranty: 1 year warranty or more.	प्रति थान
१२	16 Port Network Gigabyte Switch	Ports: Min 16x10/1000Mbps Rj 45 Interface or better.; metal chasis, Warranty: 1 year warranty or more.	प्रति थान
१३	24 Port Network Gigabyte Switch	Ports: Min 24x10/1000Mbps Rj 45 Interface or better.; metal chasis, Warranty: 1 year warranty or more.	प्रति थान
१४	8 port gigabyte manageable switch with 2 SFP uplink	Ports: At least 8x10/100/1000Mbps RJ45 Interface and 2x1G SFP Ports; 1x Console port or better, L3 Lite Managed via CLI and GUI(Web), Telnet, SSH, MAC: 8K, or more; Warranty: 1 year warranty or more.	प्रति थान
१५	24 port managable switch	Ports: At least 24x10/100/1000Mbps RJ45 Interface and 2x1G SFP Ports or more; 1x Console port or better, L3 Lite Managed via CLI and GUI(Web), Telnet, SSH, MAC: 8K, or more; Warranty: 1 year warranty or more.	प्रति थान
१६	8 Port 10G SFP+ Switch	Ports: At least 8x10G SFP+ Interface and 2x1G RJ45 Interface or better; 1x Console port or better, L3 Lite Managed via CLI and GUI(Web), Telnet, SSH, MAC: 32K, or more; Warranty: 1 year warranty or more.	प्रति थान
१७	8 Port 1G SFP Unmanaged Switch	Ports: At least 8x 1G SFP Interface and 2x1G Rj45 Interface or better; unmanaged; Mac: 8K, Warranty: 1 year warranty or more.	प्रति थान
१८	8 Port 1G SFP Managed Switch	Ports: At least 4x 1G SFP Interface, 4 x 1G SFP and Rj45 combo port and 4x10G SFP Interface or better; 1x Console port or better, L3 stakable lite Managed via CLI and GUI(Web), Telnet, SSH, MAC: 12K, or more; Warranty: 1 year warranty or more.	प्रति थान
१९	24 port SFP Managed Switch	Ports: At least 16x 1G SFP Interface, 8 x 1G SFP and Rj45 combo port and 4x10G SFP Interface or better; 1x Console port or better, L3 stackable Lite Managed via CLI and GUI(Web), Telnet, SSH, MAC: 12K, or more; dual power supply, Warranty: 1 year warranty or more.	प्रति थान
२०	Wireless Access Point	Radio Bands: Dual band (2.4GHz and 5GHz); Ethernet Interface: 1x1G Ethernet Interface Wireless Throughput: 1 Gbps wireless throughput; Concurrent Wireless Users: Atleast Supports upto 128 concurrent wireless users; PoE Injector: PoE Injector included; Warranty: 1 year warranty or more.	प्रति थान

२१	Highend Wireless Access Point	Radio Bands: Dual band (2.4GHz and 5GHz); Ethernet Interface: 1x1G Ethernet Interface Wireless Throughput: 1.2 Gbps wireless throughput; Concurrent Wireless Users: Atleast supports upto 250 concurrent wireless users; PoE Injector: PoE Injector included; Warranty: 1 year warranty or more.	प्रति थान
२२	Wireless Access Point	Radio Bands: Dual band (2.4GHz and 5GHz); Ethernet Interface: 1x1G Ethernet Interface (PoE) or more, Wireless Throughput: 1700 Gbps wireless throughput; IEEE Standard: 802.11 a/b/g/n/ac/wave2/ax (wifi6) Concurrent Wireless Users: upto 128, PoE or DC power operation, Warranty: 1 year warranty or more.	प्रति थान
२३	Highend Wireless Access Point	Radio Bands: Dual band (2.4GHz and 5GHz); Ethernet Interface: 1x2.5G Ethernet Interface (PoE) or more, Wireless Throughput: 2900 Gbps wireless throughput; IEEE Standard: 802.11 a/b/g/n/ac/wave2/ax (wifi6) Concurrent Wireless Users: upto 250, PoE or DC power operation, Warranty: 1 year warranty or more.	प्रति थान
२४	Router	WAN Interfaces: 2x1G RJ45 WAN Interface and 1x1G SFP WAN Interface or more; LAN Interfaces: 4x1G LAN Interface or more; WAN Bandwidth: Support 750 Mbps WAN bandwidth or more; Load Balancing and Failover: Support load balancing and failover between multiple WAN links; Warranty: 1 year warranty or more.	प्रति थान
२५	Router	Port: 5 × 10/100/1000 Mbps RJ45 Ethernet ports and 1 × 1G SFP port configurable WAN branch router, multiple WAN load balancing, automatic failover, policy-based routing, and link redundancy, dual-core 880 MHz processor with 256 MB RAM,	प्रति थान
२६	Router with AP Controller	Port: 1 × Gigabit RJ45/SFP Combo WAN and 8 × Gigabit RJ45 LAN ports flexible WAN connectivity, Supports up to 32 AP licenses for wireless AP management, load balancing, automatic WAN failover, NAT, VPN, IPv4/IPv6, QoS, ACL firewall, and dynamic routing protocols (OSPF/BGP/RIP), Warranty: 1 year warranty or more.	प्रति थान
२७	2U Network Rack		प्रति थान
२८	4U Network Rack	4U 550x450, Wall Mount Network, IP 20, IK08, Protected against mechanical impact with an energy of 5 Joules, CRCA sheet +powder coated with 60-80 micron thickness, UL 2416 approved, supplied with 4 mounting rails level with U mark, front Loackable Glass door, or better.	प्रति थान
२९	6U Network Rack	6U 600x400, Wall Mount Network, IP 20, IK08, Protected against mechanical impact with an energy of 5 Joules, CRCA sheet +powder coated with 60-80 micron thickness, UL 2416 approved, supplied with 4 mounting rails level with U mark, front Loackable Glass door, or better.	प्रति थान
३०	9U Rack	9U 600x400, Wall Mount Network, IP 20, IK08, Protected against mechanical impact with an energy of 5 Joules, CRCA sheet +powder coated with 60-80 micron thickness, UL 2416 approved, supplied with 4 mounting rails level with U mark, front Loackable Glass door, including single fan or better.	प्रति थान
३१	12U Rack	12U 600x400, Wall Mount Network, IP 20, IK08, Protected against mechanical impact with an energy of 5 Joules, CRCA sheet +powder coated with 60-80 micron thickness, UL 2416 approved, supplied with 4 mounting rails level with U mark, front Loackable Glass door, including single fan or better.	प्रति थान
३२	15U Rack	15U 600x400, Wall Mount Network, IP 20, IK08, Protected against mechanical impact with an energy of 5 Joules, CRCA sheet +powder coated with 60-80 micron thickness, UL 2416 approved, supplied with 4 mounting rails level with U mark, front Loackable Glass door, including single fan or better.	प्रति थान
३३	27U Network Rack	27U 600x800 floor standing netwrok rack, aluminium extruded frameworks, IP 20, IK08, Protected against mechanical impact with an energy of 5 Joules, CRCA sheet +powder coated with 60-80 micron thickness, Permissible load- up to 1200 kg, UL 2416 approved, supplied with 4 mounting rails level with printed U mark, front and back mesh ventilation door, including double fan, castor wheel or better.	प्रति थान
३४	42U Network Rack	42U 600x1000 floor standing server rack, aluminium extruded frameworks, IP 20, IK08, Protected against mechanical impact with an energy of 5 Joules, CRCA sheet +powder coated with 60-80 micron thickness, Permissible load- up to 1200 kg, UL 2416 approved, supplied with 4 mounting rails level with printed U mark, front and back mesh ventilation door, including four fan, castor wheel or better.	प्रति थान
३५	24 port patch panel	1U Cat6 Patch Panel with 24 nos Keysotne jack loaded or better	प्रति थान
३६	Cable Manager	1U Cable manager for cat6 cable management or better	प्रति थान
३७	Single Ethernet Faceplate with keystone jack	Single Faceplate with 1xRj 45 Keystone Jack and 3x3 PVC box or better	प्रति थान

૩૮	Double Faceplate with keystone jack	Double Faceplate with 1xRJ 45 , 1x rj11 Keystone Jack and 3x3 PVC box or better	પ્રતિ થાન
૩૯	RJ-11 jack(100 pcs=1box)	RJ11 Jack for Analog Telephony connection	પ્રતિ થાન
૪૦	RJ-45 jack(100 pcs=1box)	RJ45 Jack for Data connection	પ્રતિ થાન
૪૧	PDU extension	The PDU should have Metal body 2U, 6 way, 13A universal power ports and Rackmountable, Warranty 1 year or better	પ્રતિ થાન
૪૨	PDU extension	The PDU should have Metal body, 8 way, 13A universal power ports and zero U, Warranty 1 year or better	પ્રતિ થાન
૪૩	PDU extension	The PDU should have Metal body, 10 way, 13A universal power ports and zero U, Warranty 1 year or better	પ્રતિ થાન
૪૪	Reverse PDU extension (for Server Rack)	The PDU vertical mounted 12 Shocket C13 type and 4 Shocket C19 type 32A reverse power ports, Warranty 1 year or better	પ્રતિ થાન
૪૫	CAT-6 Cable CCA (Indoor/Outdoor)	Cat6 UTP; solid beared Copper min 20%; HDPE (High-Density Polyethylene) insulation, 0.50±0.01 mm, 24 AWG, 305 meter roll	પ્રતિ રોલ
૪૬	Cat6 copper cable (Indoor)	Type: UTP CAT-6; Conductor: 23 AWG Pure copper (Ø 0.53–0.58 mm); Insulation: PVC or better; 250 Mhz frequency, Compliant with ISO/IEC 11801 and ANSI/TIA 568 standards, Euroclass, UL logo and number in box, minimum 305 meter roll	પ્રતિ રોલ
૪૭	Cat6 copper cable (outdoors)	Pure Copper Cat6 Cable, 24 AWG 0.57 mm ± 0.02 mm, 4 Pair, ANSI/TIA standard, HDPE PVC, 305 Mtr in roll or better	પ્રતિ રોલ
૪૮	2 Core Drop wire (30M)	2 Core Drop wire Pre-terminated with suitable fiber port with support with length of 30 meter	પ્રતિ રોલ
૪૯	2 Core Drop wire (50M)	2 Core Drop wire Pre-terminated with suitable fiber port with support with length of 50 meter	પ્રતિ રોલ
૫૦	2 Core Drop wire (100M)	2 Core Drop wire Pre-terminated with suitable fiber port with support with length of 100 meter	પ્રતિ રોલ
૫૧	2 Core Drop wire (150M)	2 Core Drop wire Pre-terminated with suitable fiber port with support with length of 150 meter	પ્રતિ રોલ
૫૨	2 Core Drop wire (200M)	2 Core Drop wire Pre-terminated with suitable fiber port with support with length of 200 meter	પ્રતિ રોલ
૫૩	2 Core Drop wire (300M)	2 Core Drop wire Pre-terminated with suitable fiber port with support with length of 300 meter	પ્રતિ રોલ
૫૪	6 Core Optical fiber cable	Product Type: 6 Core Optical fiber cable	પ્રતિ મિટર
૫૫	12 Core Optical fiber cable	Product Type: 12 Core Optical fiber cable	પ્રતિ મિટર
૫૬	Optical fiber tiffin box	Optical fiber tiffin box	પ્રતિ થાન
૫૭	Media Converter	Product Type: Gigabit Fiber to Ethernet Convertor	પ્રતિ થાન
૫૮	SFP Module singlemode	Product Type: Gigabit Single mode SFP Module	પ્રતિ થાન
૫૯	SFP Module Multimode	Product Type: Gigabit multimode SFP Module	પ્રતિ થાન
૬૦	SFP to RJ-45 Converter	Product Type: Gigabit SFP for Ethernet Connection	પ્રતિ થાન
૬૧	Optical Distribution Frame (ODF) 2 Core	Product Type: Rackmountable 2 Core loaded ODF	પ્રતિ થાન
૬૨	Optical Distribution Frame (ODF) 12 Core	Product Type: Rackmountable 12 Core loaded ODF	પ્રતિ થાન
૬૩	Optical Distribution Frame (ODF) 24 Core	Product Type: Rackmountable 24 Core loaded ODF	પ્રતિ થાન
૬૪	Fiber Patch Cord (3 Meter)	Product Type: 3 meter fiber Patch with SC-SC or SC-LC or LC-LC connector or betrer	પ્રતિ થાન
૬૫	Fiber Patch Cord (5 Meter)	Product Type: 5 meter fiber Patch with SC-SC or SC-LC or LC-LC connector or betrer	પ્રતિ થાન
૬૬	Fiber Patch Cord (10 Meter)	Product Type: 10 meter fiber Patch with SC-SC or SC-LC or LC-LC connector or betrer	પ્રતિ થાન
૬૭	Cat6 Patch Cord (3 Meter)	3-meter factory-manufactured copper CAT6 patch cord 23AWG with RJ45 connectors.	પ્રતિ થાન
૬૮	Cat6 Patch Cord (1 Meter)	1-meter factory-manufactured copper CAT6 patch cord 23AWG with RJ45 connectors.	પ્રતિ થાન
૬૯	Cat6 Patch Cord (0.5 Meter)	0.5-meter factory-manufactured copper CAT6 patch cord with RJ45 connectors.	પ્રતિ થાન
૭૦	Type C to LAN adapter	Product Type: Type C to Gigabit Ethernet Convertor	પ્રતિ થાન
૭૧	USB to LAN adapter	Product Type: USB to Ethernet Convertor	પ્રતિ થાન
૭૨	6 in1 USB-C To 3*USB 3.0 A+HDMI+RJ45+PD Converter	Product Type: 6 in1 USB-C To 3*USB 3.0 A+HDMI+RJ45+PD Converter	પ્રતિ થાન
૭૩	4-Port USB 3.0 Hub + Powered by Micro USB, Metal Plated Shell, Ultra Slim	Product Type: 4-Port USB 3.0 Hub + Powered by Micro USB, Metal Plated Shell, Ultra Slim	પ્રતિ થાન
૭૪	Wireless HDMI Transmitter and Receiver	5 GHz wireless HDMI extender supporting Full HD resolution up to 1920 × 1080 at 60 Hz, HDMI 1.4 or better, HDCP 1.4, wireless transmission distance up to 50 meters, plug-and-play operation, transmission of high-quality video and audio, HDMI input/output, USB-C power supply, compatible with laptops, PCs, projectors, monitors and TVs, including required cables and accessories, with 1-year warranty or more.	પ્રતિ થાન
૭૫	HDMI Cable 3 mtr		પ્રતિ થાન

७६	HDMI Cable 5 mtr	5 Meters, HDMI Cable 4k high speed for all HDMI Devices, Laptop, computer, UHD TV, Monitor, Projector	प्रति थान
७७	HDMI Cable 10 mtr	10 Meter HDMI Cable 4k high speed for all HDMI Devices, Laptop, computer, UHD TV, Monitor, Projector	प्रति थान
७८	HDMI Cable 15 mtr	15 Meter HDMI Cable 4k high speed for all HDMI Devices, Laptop, computer, UHD TV, Monitor, Projector	प्रति थान
७९	HDMI Cable 20 mtr	20 Meter HDMI Cable 4k high speed for all HDMI Devices, Laptop, computer, UHD TV, Monitor, Projector	प्रति थान
८०	2.5mm FRLS Cable	2.5mm FRLS cable 90Meter Roll	प्रति रोल
८१	4.0 mm FRLS Cable	4.0mm FRLS cable 90Meter Roll	प्रति रोल
८२	Power 0/1 Cable	0/1 Power cable	प्रति मिटर
८३	10 mm power cable (outdoor)	10 mm power cable (outdoor)	प्रति मिटर
८४	6 Sq mm Pure Copper Cable	Conductor Size: 6 sq.mm, Conductor: Pure Copper, Insulation: PVC, Current Capacity: ≥37 A, Rated Voltage: 1100 V, Standard: IS 694 / IS 8130.	प्रति मिटर
८५	Power socket with PVC box(3X3)	10A power socket with 3x3 PVC box or better	प्रति थान
८६	Double power socket with PVC box (3*5)	2x10A power socket with 3x5 PVC box or better	प्रति थान
८७	DB Box (Input & Output)	Input and output Breaker,voltage protection	प्रति थान
८८	3 port Multiplug	3 port Multiplug or better	प्रति थान
८९	5 port Multiplug	5 port Multiplug or better	प्रति थान
९०	Metal Grip 2"	Metal Grip 2"	प्रति के जि
९१	PVC Black pipe(3/4")	PVC Black pipe(3/4")	प्रति मिटर
९२	Flexible Pipe 1 "	Flexible Pipe 1 "	प्रति मिटर
९३	Flexible Pipe 2 "	Flexible Pipe 2 "	प्रति मिटर
९४	Listic 25mm	Listic 25mm	प्रति थान
९५	Listic 30 mm	Listic 30 mm	प्रति थान
९६	Listic 40mm	Listic 40mm	प्रति थान
९७	Listic 70mm	Listic 70mm	प्रति थान
९८	Listic Killa	Listic Killa	प्रति थान
९९	Grip 1.5"	Grip 1.5"	प्रति के जि
१००	Full Threaded Black Screw 0.5"	Full Threaded Black Screw 0.5"	प्रति के जि
१०१	Full Threaded Black Screw 1"	Full Threaded Black Screw 1"	प्रति के जि
१०२	Full Threaded Black Screw 1.5"	Full Threaded Black Screw 1.5"	प्रति के जि
१०३	Black Tape	Black Tape	प्रति थान
१०४	Cable tie 150MM	Cable tie 150MM	प्रति प्याकेट
१०५	Cable tie 300MM	Cable tie 300MM	प्रति प्याकेट
१०६	Binding wire	Binding wire	प्रति के जि
१०७	Fiber Splicing	Fiber Splicing, testing and fiber cable management per splicing (per core)	प्रति थान
१०८	Networking / Wiring (without bit wiring)	Laying of Cat 6 Cable, Power Cable,Optical Fiber; testing and tagging per meter. (without bit wiring)	प्रति मिटर
१०९	Networking /Wiring (with bit wiring)	Network cable -CAT 6/Power Cable/Optical Fiber laying in PVC duct, Pipe, crimping, testing and labeling per meter. (with bit wiring including listic)	प्रति मिटर
११०	Network Cabling per point	Network cable laying through PVC duct/pipeline, routing, termination/crimping, labeling, continuity testing and commissioning. per point	प्रति थान
१११	Wiring Cabling per point	Wiring and Cable Management (Cable laying, routing, dressing, bundling, fixing, labeling and proper management of network/power/other cables, including testing) Per point	प्रति थान
११२	CCTV Camera Installation	Installation of CCTV Camera -Indoor and Outdoor Bullet/Dome/PTZ/Wireless Camera (Camera Mounting, basic bracket installation, Cable termination, POE/Power Connection, IP Configuration, NVR/VMS Connection, Camera angle adjustment, Testing and Commissioning including fiber and cable laying per camera)	प्रति थान
११३	ANPR CCTV Camera Installation	Installation of ANPR CCTV Camera(Site Survey, Camera Mounting, Network and Power Installation, ANPR Configuration, NVR/VMS/Server Integration, Testing and Commissioning fiber and cable laying per camera)	प्रति थान
११४	Projector	DLP, XGA, 1024 x 768 pixels, 3500 Lumens or better	प्रति थान
११५	Projector	DLP, WXGA, 1280 x 800 pixels, 4000 Lumens or better	प्रति थान
११६	Projector Screen	120 " diagonal , 4:3 ratio	प्रति थान
११७	Antivirus	1 User	प्रति थान

११८	Antivirus	3 User	प्रति थान
११९	External Harddisk (HDD)	4 TB	प्रति थान
१२०	External Harddisk (HDD)	2 TB	प्रति थान
१२१	External Harddisk (HDD)	1 TB	प्रति थान
१२२	External Harddisk (SSD)	4 TB	प्रति थान
१२३	External Harddisk (SSD)	2 TB	प्रति थान
१२४	External Harddisk (SSD)	1 TB	प्रति थान
१२५	External Harddisk (SSD)	512 GB	प्रति थान
१२६	Internal hard Disk (SSD)	1 TB	प्रति थान
१२७	Internal hard Disk (SSD)	512 GB	प्रति थान
१२८	SSD M.2 SATA	2 TB	प्रति थान
१२९	SSD M.2 SATA	1 TB	प्रति थान
१३०	SSD M.2 SATA	512 GB	प्रति थान
१३१	SSDM.2 SATA	256 GB	प्रति थान
१३२	ATX Power supply	450W/500W	प्रति थान
१३३	Computer Keyboard	English/Nepali, USB/PS2	प्रति थान
१३४	Laptop Keyboard	USB Wired Keyboard (English International Keyboard)	प्रति थान
१३५	Wireless Keyboard	Wireless Keyboard (English International Keyboard)	प्रति थान
१३६	Wireless Keyboard & Mouse	(Combo Pack)	प्रति थान
१३७	Computer Mouse Pad	Simple	प्रति थान
१३८	Wireless Mouse	Wireless Support	प्रति थान
१३९	Computer Mouse	Optical USB/PS2	प्रति थान
१४०	Desktop RAM	4 GB DDR3	प्रति थान
१४१	Desktop RAM	8 GB DDR3	प्रति थान
१४२	Desktop RAM	4 GB DDR4	प्रति थान
१४३	Desktop RAM	8 GB DDR4	प्रति थान
१४४	Desktop RAM	16 GB DDR4	प्रति थान
१४५	Desktop RAM	4 GB DDR5	प्रति थान
१४६	Desktop RAM	8 GB DDR5	प्रति थान
१४७	Desktop RAM	16 GB DDR5	प्रति थान
१४८	Laptop RAM	4 GB DDR3	प्रति थान
१४९	Laptop RAM	8 GB DDR3	प्रति थान
१५०	Laptop RAM	4 GB DDR4	प्रति थान
१५१	Laptop RAM	8 GB DDR4	प्रति थान
१५२	Laptop RAM	16 GB DDR4	प्रति थान
१५३	Laptop RAM	4 GB DDR5	प्रति थान
१५४	Laptop RAM	8 GB DDR5	प्रति थान
१५५	Laptop RAM	16 GB DDR5	प्रति थान
१५६	Laptop Charger	All Brand	प्रति थान
१५७	laptop battery	All Brand	प्रति थान
१५८	Laptop Cooler Pad	Compatible For 14" and 15.6 "	प्रति थान
१५९	Laptop Stand	Metal laptop stand with 360 degree rotatable and height adjustment	प्रति थान
१६०	Laptop Screen	All Brand	प्रति थान
१६१	Laptop Casing	All Brand	प्रति थान
१६२	Printer Cable	1.5 meter, USB Type	प्रति थान
१६३	Power Cable	1.5 meter, For Computer/ Printer	प्रति थान
१६४	UPS	750 VA, Minimum 1 year warranty	प्रति थान
१६५	UPS	1250 VA, Minimum 1 year warranty	प्रति थान
१६६	Printer	Canon LBP 2900 or Equivalent, Minimum 1 year warranty	प्रति थान
१६७	Printer	Canon LBP 3010 or Equivalent, Minimum 1 year warranty	प्रति थान

୧୬୮	3 in 1 Printer	Print/copy-20 PPM or More ,128 MB Memory, Print copy resolution-600x600 or more, scan resolution-1200x1200DPI, Flatbed scanner or better, cartridge included, support mac, windows 10,11 Os, Duplex Printing, USB and Network printing support, 1 year warranty	प्रति थान
୧୬୯	A4 Size MFP	Function: Copy, Print, Scan, Speed (A4): Minimum 27 PPM or higher, Memory: Minimum 256 MB or more, Display: LCD/Touchscreen, First Page Out Time: 8 seconds or less, Multiple Copies: Up to 99 copies or higher, Print Resolution: Up to 1200 × 1200 dpi, Copy/Scan Resolution: 600 × 600 dpi, Connectivity: Hi-Speed USB 2.0 port, Network and Wireless, Duplex Print: Standard, Paper Input: Minimum 250-sheet input tray, Scan Resolution: Up to 1200 × 1200 dpi, Scan Mode: B&W, Greyscale and Color, Scan Destination: Scan to Email and Network Folder, Inclusive: Original Toner Cartridge, Power Cable and USB Cable, Warranty: Minimum 1-year full product warranty, Certifications: Energy Star Certified.	प्रति थान
୧୭୦	Vacuum Cleaner	Type- double Drum, 2000W, 20 liter (minimum)	प्रति थान
୧୭୧	Smart TV	55" 4K(3840 x 2160 pixels) Smart TV, 2 GB RAM, 16 GB ROM, Android 9 or better,1* Ethernet, 2*USB, 1*HDMI (min), wall mount kit with basic required accessories. 1year warranty .	प्रति थान
୧୭୨	Trolley Speaker 8 "	Speaker Size 8 Inch, Sound Output: 30W Wireless Mic, Mic Input 1 Year Warranty,6 Months on Battery	प्रति थान
୧୭୩	Trolley Speaker 12 "	Speaker Size 12 Inch, Sound Output: 40W Bluetooth, Mic Input, Rechargeable Battery, 2 wireless Mic, USB /TF input function, 1 Year Warranty, 6 Months on Battery	प्रति थान
୧୭୪	65" Smart Interactive Board	4K UHD anti-glare display, DLED Backlight, Panel Size: 65", Resolution: 3840 × 2160, Brightness: 350 (cd/m²), Contract ratio: 1200 : 1, Response Time: 8 (ms), color support: 1.07 B, viewing angle: 178°/178°, Glass type: Anti glare tempered glass, Refresh rate: 60 Hz, Color Gamut: 72% NTSC, Lifespan: 50000 h, Haze value: 25%, Pixel Pitch: 0.37 × 0.37, Display size: 1430.5 × 805.5, Camera: 8000 × 6000 pixel, Touch Control: Up to 40 point multi touch (WIN: 40 point, Android: 32 point), CPU: 8 × Cortex A55, RAM: 8 GB, ROM: 128 GB, CPU Frequency: 1.2 GHz, Operation System: Android 14.0, Speaker: 2 × 20 W, Microphone: 8 microphone array, upto12 Mtr pickup , warranty: 1 year minimum	प्रति थान
୧୭୫	75" Smart interactive board	4K UHD anti-glare display, DLED Backlight, Panel Size: 75", Resolution: 3840 × 2160, Brightness: 350 (cd/m²), Contract ratio: 1200 : 1, Response Time: 8 (ms), color support: 1.07 B, viewing angle: 178°/178°, Glass type: Anti glare tempered glass, Refresh rate: 60 Hz, Color Gamut: 72% NTSC, Lifespan: 50000 h, Haze value: 25%, Pixel Pitch: 0.42 × 0.42, Display size: 1649.7 × 927.9, Camera: 8000 × 6000 pixel, Touch Control: Up to 40 point multi touch (WIN: 40 point, Android: 32 point), CPU: 8 × Cortex A55, RAM: 8 GB, ROM: 128 GB, CPU Frequency: 1.2 GHz, Operation System: Android 14.0, Speaker: 2 × 20 W, Microphone: 8 microphone array, upto12 Mtr pickup , warranty: 1 year minimum	प्रति थान
୧୭୬	Trolley with Stand (for LED SMART Board)	Minimum Holding Capacity - 100 KG; Support to 65", 75" and 86"	प्रति थान
୧୭୭	Branch Firewall Device	Interface- 1*1Gigabit WAN , 3 *1Gigabit LAN RJ45 interface or more,IPV4 Firewall Throughput- 3.9 Gbps or more, Concurrent connections per sec - •400K or more concurrent connections. •34K or more sessions per second, IPsec VPN Throughput- 3.0 Gbps or more, Protocols- •The firewall should support SNMP protocols, static routes and dynamic routing protocols (OSPF, BGP),1-year warranty on product.	प्रति थान
୧୭୮	VGA Cable	1 Meters	प्रति थान
୧୭୯	VGA Cable	5 Meters	प्रति थान
୧୮୦	Portable Speaker	For Computer and Laptop, 6W (minimum) total output with 2.0 channel USB plug. Frequency response of 20Hz-20KHz .	प्रति थान
୧୮୧	Remote	Universal TV remote	प्रति थान
୧୮୨	Remote	Universal AC remote	प्रति थान
୧୮୩	Power Bank	22.5 W, 10000 MAH capacity or better, battery-Li-polymer, Output-USB, Type C, Fast Charging- yes, Warranty-1 Year	प्रति थान
୧୮୪	SD Card 8GB	8 GB	प्रति थान
୧୮୫	SD Card 16 GB	16 GB	प्रति थान
୧୮୬	SD Card 32 GB	32 GB	प्रति थान
୧୮୭	SD Card 64GB	64 GB	प्रति थान

१८८	SD Card 128GB	128GB Read/Write speed-100/90 mb/s, high/low temperature resistant, water proof, anti-magnetic	प्रति थान
१८९	64 GB Pendrive	Interface: USB 3.0, transfer speed of up to 100 MB/s ,USB Connector Type: Standard, Warranty: 1 year	प्रति थान
१९०	32 GB Pendrive	Interface: USB 3.0, transfer speed of up to 100 MB/s ,USB Connector Type: Standard, Warranty: 1 year	प्रति थान
१९१	16 GB Pendrive	Interface: USB 3.0, transfer speed of up to 100 MB/s ,USB Connector Type: Standard, Warranty: 1 year	प्रति थान
१९२	8 GB Pendrive	Interface: USB 3.0, transfer speed of up to 100 MB/s ,USB Connector Type: Standard, Warranty: 1 year	प्रति थान
१९३	4 GB Pendrive		प्रति थान
१९४	Telephone Wire	2 pair, 1 Roll (100m)	प्रति थान
१९५	Telephone Wire	2 Pair , 10 meter	प्रति थान
१९६	Electric Room Heater	Halogen Heater, 3 rod, 1200W	प्रति थान
१९७	Rj45 LAN Cable Tester	Network Cable Tester Rj45 Rj11 Rj12 Cat5 Utp Lan Cable Tester Networking Tool Led indication	प्रति थान
१९८	DSLR Camera Charger	For Canon/Nikon/Sony or similar	प्रति थान
१९९	Headphone	Type: Closed Back Dynamic Overhead Headphones, noise-cancelling with microphone, long cables, volume controller, Warranty: 1 year or more	प्रति थान
२००	Micro Oven	23liter / 24 liter, Type-solo, Touch Key Pad, 1 Year Product Warranty	प्रति थान
२०१	Monitor 24"	Size:23.8" Full HD, IPS Panel, Anti-Glare or Higher; Resolution:1920 × 1080 (Full HD) or Higher; Brightness:≥ 250 nits or ≥ 250 cd/m² or Better; Refresh Rate:100Hz or Better; Response Time:5ms or Better; Color Gamut:99% sRGB; Contrast ratio:1000 : 1 or Better; Color depth:8 bit or Higher; Aspect ratio:16:9 or more;Connectivity:HDMI 1.4 ×1, DP 1.2 ×1, DP Out ×1, USB-C (PD 65 W) ×1, USB-A ×2, 3.5 mm jack or More; Audio:2x 2W Speaker, Built in Noise Cancellation Mic or Better; Adjustment:Tilt, Swivel / Pivot / Height Adjustment; VESA Mount:100 x 100 mm or Better; Eyecare:Low Blue Light Technology, Flicker Free, Light Sensor, Color Weakness or More; Mode:Coding Mode, ePaper Mode, Low Blue Light Mode or More; Warranty:1 year or More	प्रति थान
२०२	Biometric Access Control Device	Biometric Authentication:face recognition (mandatory); support for fingerprint and palm (optional); User Capacity:Minimum 50,000 users or more; Card Support:RFID proximity or smart card (125 KHz / 13.56 MHz); Card Capacity:Minimum 50,000 or more;Event/Log Storage:Minimum 100,000 records; Liveness Detection: Required (IR-based or AI-based);Mask Detection:Required; Temperature Screening:Optional; if present, should have ±0.3°C accuracy or better; Recognition Speed:≤ 0.3 seconds per user; Recognition Distance:0.3 to 3.0 meters or more;Display Screen:Minimum 5-inch touchscreen (IPS/TFT);Network Connectivity:Ethernet (TCP/IP); optional Wi-Fi or RS-485;Communication Interfaces:Wiegand input/output, relay output, USB (if applicable);Access Modes:Face / Card / PIN / Palm / Fingerprint (any combination);Door Control:Yes, with built-in relay;Voice and Visual Prompts:Audio and LED indicators supported;User Management:Role-based access, user groups, time zone and schedule support;Anti-passback:Supported (hardware or software-based);Tamper Alarm:Supported;Installation Type:Wall-mounted or freestanding (optional stand);Operating Temperature:-10°C to +55°C or better;Operating Humidity:10%–90% RH, non-condensing;Ingress Protection:(IP)Minimum IP54; IP65 preferred for outdoor installations;Power Supply:DC 12V / 2A or as per manufacturer's Specification;Software Compatibility:Should support integration with third-party software or cloud platforms;Data Export & Reporting:CSV / Excel / PDF or more;Firmware Upgrades:Via network or USB;SDK/API Support:Must be available for integration;Optional	प्रति थान
२०३	4MP Bullet Camera	1/3" CMOS sensor or better; 4MP (2560×1440) resolution or higher; 2.8mm/4mm fixed lens or better; 0.005 Lux @ F1.6 low-light capability; ≥30m illumination with supplemental light; 120dB WDR or better; H.265/H.264 compression or better; 3D DNR, BLC, HLC; up to 20 fps at max resolution; minimum 2 video streams; intrusion and motion detection; microSD support up to 256GB or better; RJ45 (10/100 Mbps); 12V DC/PoE, ≤20W; built-in mic; -10°C to 60°C; IP67 rated; CE/FCC/ROHS certified. Warranty: Minimum 1 year	प्रति थान

२०४	4MP Dome Camera	1/3" CMOS sensor or better; 4MP (2560×1440) resolution or higher; 2.8mm/4mm fixed lens or better; 0.005 Lux @ F1.6 low-light capability; ≥30m illumination with supplemental light; 120dB WDR or better; H.265/H.264 compression or better; 3D DNR, BLC, HLC; up to 20 fps at max resolution; minimum 2 video streams; intrusion and motion detection; microSD support up to 256GB or better; RJ45 (10/100 Mbps); 12V DC/PoE, ≤20W; built-in mic; -10°C to 60°C; IP67 rated; CE/FCC/ROHS certified; Warranty: Minimum 1 year	प्रति थान
२०५	4 MP Indoor/Outdoor Full Colour Camera	Type: Outdoor/Indoor; Sensor: ≥1/1.8"CMOS sensor and F1.0 aperture lens; Resolution: ≥2688×1520; Lens: Indoor 2.8mm ; Outdoor <4.0mm; Illumination: ≤0.0003lux @F1.0; IR/White/Warm light; ≥30m range; auto light on/off control, WDR: ≥120 dB; Video: H.265/H.265 or higher compression, main stream up to 25fps; Audio: G.711a; Enhancement: HLC, white balance; Interface: RJ45 (10/100) PoE supportable, ONVIF Profile S/G/T, Storage: MicroSD (max 256GB supported or more); built in mic; Protection: IP67; AI: Intrusion, tripwire (vehicle & human); CE or FCC or RoHS; Warranty: Minimum 1 year	प्रति थान
२०६	5 MP Outdoor Full Color Camera	Type: Outdoor/Indoor; Sensor: ≥1/1.8"CMOS sensor and F1.0 aperture lens; Resolution: ≥2880*1620; Lens: 4.0mm or 6mm; Illumination: ≤0.0003lux @F1.0; IR/White/Warm light; ≥50m range; auto light on/off control, WDR: ≥120 dB; Video: H.265/H.265 or higher compression, main stream up to 25fps; two way Audio support: G.711a; Enhancement: HLC, BLC, Defog, white balance; Interface: RJ45 (10/100) PoE supportable, ONVIF Profile S/G/T, Storage: MicroSD (max 256GB supported or more); built in mic; Protection: IP67; AI: Intrusion, tripwire (vehicle & human); CE or FCC or RoHS; Warranty: Minimum 1 year	प्रति थान
२०७	8 MP Outdoor Full Color Camera	Type: Outdoor; Sensor: ≥1/1.8"CMOS sensor and F1.0 aperture lens; Resolution: ≥3840×2160; Lens: 4.0mm or 6mm; Illumination: ≤0.0003lux @F1.0; IR/White/Warm light; ≥30m range; auto light on/off control, WDR: ≥120 dB; Video: H.265/H.265 or higher compression, stream up to 25fps; Audio support: G.711a; Enhancement: HLC, BLC, Defog, white balance; Interface: RJ45 (10/100) PoE supportable, ONVIF Profile S/G/T, Storage: MicroSD (max 256GB supported or more); built in mic; Protection: IP67; AI: Intrusion, tripwire (vehicle & human); CE or FCC or RoHS; Warranty: Minimum 1 year	प्रति थान
२०८	4MP Motorized Vari Focal Bullet Camera	Type- Outdoor, Image Sensor-1/3" Progressive Scan CMOS or better, Resolution- 4MP ((2688 × 1520) or better, Lens: Motorized Vari-focal 2.8mm to 12mm or better range, Minimum Illumination- 0.003 Lux @ F1.6 or better, Illumination Distance- Up to 50 m IR distance, WDR -120 dB, Video Compression- H.265/H.264 or better, Image Enhancement-3D DNR, BLC, HLC, Defog; main Frame Rate- 25 fps or better, Smart Features- Motion, human, face detection, vehicle detection, Tampering, Storage- MicroSD slot up to 256 GB or better, Network Interface- RJ45 (10/100 Mbps), PoE support, Built-in Microphone, Protection: IP67, Certifications-CE or FCC or RoHS, Warranty: Minimum 1 year	प्रति थान
२०९	4MP Motorized Varifocal Color Bullet Camera	Type- Outdoor, Image Sensor-1/1.8" Progressive Scan CMOS or better, Resolution- 4MP ((2688 × 1520) or better, Lens- Motorized Vari-focal 2.8mm to 12mm or better range, Minimum Illumination- 0.0005 lux @ F1.2 or better, Illumination Distance- Up to 80 m IR distance, WDR -120 dB, Video Compression- H.265/H.264 or better, Image Enhancement-3D DNR, BLC, HLC, Defog; main Frame Rate- 30 fps or better, Smart Features- Motion, human, face detection, vehicle detection, Support capturing car license picture, Tampering, Storage- MicroSD slot up to 512 GB or better, Network Interface- RJ45 (10/100 Mbps), PoE support, two way audio, Built-in Microphone, Protection: IP67, IK10, Certifications-CE or FCC or RoHS, Warranty: Minimum 1 year	प्रति थान

२१०	PTZ Camera 4MP	Type: Outdoor, Image Sensor: $\geq 1/2.8''$ CMOS; Resolution: $\geq 2688 \times 1520$ or better; Optical Zoom: $\geq 25\times$, Digital zoom $\geq 16\times$; Focal Length: 4.8 mm to 120 mm, Minimum Illumination- 0.003 Lux @ F1.5 or better; IR: upto 100m, Day/Night: Auto (ICR), WDR: ≥ 120 dB, standard PTZ function; Video compression: H.265/H.264 or better, Enhancement: BLC, HLC, Defog; AI: intrusion, smart tracking; Interoperability: ONVIF Profile S/G/T; Interface: RJ45 10/100M, two way audio; Audio in/out ≥ 1 each; Storage: ≥ 256 GB; Protection: IP67, IK10; certifications: CE or FCC or RoHS; should supply with pole mount bracket and required adaptor if required to operate the camera, Warranty: Minimum 1 year	प्रति थान
२११	4 MP Dual Lens PTZ Camera	Type: Outdoor with fix lens and ptz lens integration for multiple view by supporting dual channel in single IP; For Fix Channel: Image Sensor: $\geq 1/1.8''$ CMOS; Resolution: $\geq 2688 \times 1520$ or better; Focal Length: 4.0 mm, Minimum Illumination- 0.0005 Lux @ F1.0 or better; warm light : upto 30m; For PTZ Channel: Image Sensor: $\geq 1/2.7''$ CMOS; Resolution: $\geq 2688 \times 1520$ or better; Optical Zoom: $\geq 25\times$, Focal Length: 4.8 mm to 120 mm, Minimum Illumination- 0.003 Lux @ F1.5 or better; IR: upto 100m, support standard PTZ function; Day/Night: Auto (ICR), WDR: ≥ 120 dB, Video compression: H.265/H.264 or better, Enhancement: BLC, HLC, Defog; AI: Tampering, intrusion, smart tracking, Scene change; Interoperability: ONVIF Profile S/G/T/M; Interface: RJ45 10/100M, two way audio; Audio in/out ≥ 1 each; Storage: ≥ 256 GB; Protection: IP66, certifications: CE or FCC or RoHS; should supply with pole mount bracket and required adaptor if required to operate the camera, Warranty: Minimum 1 year	प्रति थान
२१२	Automatic Number Plate Recognition(ANPR) CCTV Camera	Sensor: $\geq 1/1.8''$ CMOS, 8MP Resolution: $\geq 3840 \times 2160$, Illumination: ≤ 0.0003 lux @F1.6 WDR ≥ 140 dB; Lens: 8–32mm, covers ≥ 2 lanes, White light ≥ 40 m, Video compression: H.265/H.264 or better, Enhancement: BLC, HLC, Defog; stream up to 60 fps, BLC, HLC, 3D DNR, Defog; Interface: RJ45 (10/100) PoE supportable, built in mic, Detection: Motor vehicles, motorcycles, plate recognition and OCR (Nepali $\geq 90\%$, embossed $\geq 99\%$); capture vehicle number plate for speed from 0 to 120 km/h; Storage support: Up to 512GB; Network: RJ45, ONVIF S/G/T, Built: IP67, IK10, Pole mount & 3D angle adjustable brackets should be included, certifications: CE or FCC or RoHS; Warranty: Minimum 1 year	प्रति थान
२१३	Suppliment Light for ANPR	Warm light LED, Color Temperature: 3000K; luminous flux: 4150 lm, Optimal illumination distance: 12m~25m, should support auto day & night function, Illuminance coverage: Min.2 lanes, Number of LED : 20, Dimming mode should control from S485 control or manual key control, Power supply AC : 90 V ~264V, 50/60Hz, Power consumption 3W~50W Adjustable (active power), Life span >50000 hours or more, protection IP68 or more, Pole mount & 3D angle adjustable brackets should be included. Warranty: Minimum 1 year	प्रति थान
२१४	ANPR Arms in existing Pole	Arms suitable for ANPR Camera and light mounting in existing pole of at least 1 mtr to 3 mtr as per requirement of site, having support and proper mounting to bear the required load made by iron metal structure and recommended by camera to get proper field of view and get proper output of camera.	प्रति थान
२१५	4 Port GPON PoE ONU for Road Project	General Features: Auto-discovery & register, IGMP Snooping, VLAN, loop detection, port speed limit, remote management; Port Interface: Min. 4 $\times$ 10/100/1000 Mbps PoE ports (auto-adapted); 1 $\times$ GPON port (pluggable or fixed); Wavelength (nm): Upstream: 1310 $\pm$ 20 nm; Downstream: 1490 $\pm$ 15 nm; Optical Parameters:Receiving Sensitivity: ≤ -28 dBm; Optical Power: 0.5 to +5 dBm; Transmission Distance: ≥ 20 km; PoE Support: Min. 4 $\times$ IEEE 802.3af/at-compliant ports; Link budget: ≥ 30 W per port; Accessories: Power adapter and required accessories included; Compatibility: Fully compatible with Nepal Telecom's OLT; certifications CE or FCC or RoHS; Warranty: Minimum 1 year.	प्रति थान
२१६	4 Port Industrial Switch	Industrial grade switch chasis aluminum corrugated rapid heat dissipation Casing design for outdoor environment with temperature range adaptability-40°C~75°C; Port: 4x Gigabit PoE ports and 2x Gigabit fiber optic ports; packet forwarding rate 8 Mbps or more; bandwidth capacity up to 12 Gbps; 6KV lightning protection or better; CE/FCC/ROHS certified; power budget 30W per port; DIN-rail, IP40, should supplied with industrial grade 120W power adaptor, Warranty: Minimum 1 year.	प्रति थान

२१७	Out Door Pole Mount Ups	Installation: Pole Mounted; Capacity: 600W; Input: 220VAC, 50/60Hz (auto-sensing); Output: 230VAC ±10%, 50/60Hz, Simulated sine wave; Battery: 2× 12V Lead-Acid, 9Ah; Temp. Range: 0°C to 50°C; Interface: Yes (real-time UPS monitoring); Protection: Lightning protection, IP55 waterproof or higher; Size: Minimum 450x500x150 or customizable to fit power adapters of camera and POE switches; Warranty: Minimum 1 year.	प्रति थान
२१८	32" Surveillance monitor	32" Plastic Case LCD Monitor D-LED Backlight, Resolution: 1920*1080, Refresh rate 75Hz , 24*7 Operation Plastic body with ultra-narrow bezel 1*VGA , 1*HDMI , 1 audio, Warranty: Minimum 1 year.	प्रति थान
२१९	43" Surveillance monitor	42.5-Inch Display Specification: Screen size 42.5 inches; resolution Full HD (1920 × 1080) or better; D-LED backlight; brightness 300 cd/m² or higher; 8-bit color depth with 16.7 million colors; response time 8 ms or less; refresh rate 60 Hz; input ports include minimum 1 × HDMI, 1 × VGA/HDMI, and 1 × 3.5 mm audio-in; built-in speakers 2 × 5W or higher	प्रति थान
२२०	55" Surveillance monitor	55" 4K LED Monitor 4K UHD display, Resolution: 3840*2160, 60Hz, LED Backlight, 24*7 Operation, Industrial-grade panel, Ultra-narrow bezel, 2*HDMI, 2*DP, 2* audio, 2*10W Speaker. Warranty: Minimum 1 year.	प्रति थान
२२१	Surveillance Harddrive 4 TB	Capacity: Minimum 4 Terabytes (4TB); Drive Type: Max. 3.5-inch SATA Hard Disk Drive (HDD); Interface: Support SATA III 6 Gb/s; Spindle Speed (RPM): Minimum 7200 RPM; Cache Memory: Minimum 256 MB Cache; Form Factor: 3.5 Inch; Workload Rating: Minimum 180 TB/year workload rating; MTBF (Mean Time Between Failures) ≥ 1 million hours; Purpose: Designed for 24/7 operation in surveillance environments (CCTV, DVR, NVR); Optimized For Continuous video recording, high write workloads; Supported Cameras: Support for up to 64 or more HD cameras simultaneously or Higher; Reliability Features: Enhanced workload capability, vibration resistance, firmware for video streaming or More; Compatibility: Compatible with DVRs, NVRs, and video surveillance systems; Warranty: 1 year or more; Mandatory Certifications: CE/RoHS/ISO	प्रति थान
२२२	Surveillance Harddrive 6 TB	Capacity: Minimum 6 Terabytes (6TB); Drive Type: Max. 3.5-inch SATA Hard Disk Drive (HDD); Interface: Support SATA III 6 Gb/s; Spindle Speed (RPM): Minimum 7200 RPM; Cache Memory: Minimum 256 MB Cache; Form Factor: 3.5 Inch; Workload Rating: Minimum 180 TB/year workload rating; MTBF (Mean Time Between Failures) ≥ 1 million hours; Purpose: Designed for 24/7 operation in surveillance environments (CCTV, DVR, NVR); Optimized For Continuous video recording, high write workloads; Supported Cameras: Support for up to 64 or more HD cameras simultaneously or Higher; Reliability Features: Enhanced workload capability, vibration resistance, firmware for video streaming or More; Compatibility: Compatible with DVRs, NVRs, and video surveillance systems; Warranty: 1 year or more; Mandatory Certifications: CE/RoHS/ISO	प्रति थान
२२३	Surveillance Harddrive 8 TB	Capacity: Minimum 8 Terabytes (8TB); Drive Type: Max. 3.5-inch SATA Hard Disk Drive (HDD); Interface: Support SATA III 6 Gb/s; Spindle Speed (RPM): Minimum 7200 RPM; Cache Memory: Minimum 256 MB Cache; Form Factor: 3.5 Inch; Workload Rating: Minimum 180 TB/year workload rating; MTBF (Mean Time Between Failures) ≥ 1 million hours; Purpose: Designed for 24/7 operation in surveillance environments (CCTV, DVR, NVR); Optimized For Continuous video recording, high write workloads; Supported Cameras: Support for up to 64 or more HD cameras simultaneously or Higher; Reliability Features: Enhanced workload capability, vibration resistance, firmware for video streaming or More; Compatibility: Compatible with DVRs, NVRs, and video surveillance systems; Warranty: 1 year; Certifications: CE/RoHS/ISO	प्रति थान

२२४	Surveillance Harddrive 10 TB	Capacity:Minimum 10 Terabytes (10TB); Drive Type:Max. 3.5-inch SATA Hard Disk Drive (HDD);Interface: Support SATA III 6 Gb/s; Spindle Speed (RPM):Minimum 7200 RPM;Cache Memory: Minimum 256 MB Cache; Form Factor: 3.5 Inch; Workload Rating:Minimum 180 TB/year workload rating; MTBF (Mean Time Between Failures)≥1 million hours; Purpose:Designed for 24/7 operation in surveillance environments (CCTV, DVR, NVR); Optimized For Continuous video recording, high write workloads; Supported Cameras: Support for up to 64 or more HD cameras simultaneously or Higher; Reliability Features:Enhanced workload capability, vibration resistance, firmware for video streaming or More; Compatibility:Compatible with DVRs, NVRs, and video surveillance systems;Warranty:1 year or more; Certifications:CE/RoHS/ISO	प्रति थान
२२५	Surveillance Harddrive 16 TB	Capacity:Minimum 16 Terabytes (16TB); Drive Type:Max. 3.5-inch SATA Hard Disk Drive (HDD);Interface: Support SATA III 6 Gb/s; Spindle Speed (RPM):Minimum 7200 RPM;Cache Memory: Minimum 256 MB Cache; Form Factor: 3.5 Inch; Workload Rating:Minimum 180 TB/year workload rating; MTBF (Mean Time Between Failures)≥1 million hours; Purpose:Designed for 24/7 operation in surveillance environments (CCTV, DVR, NVR); Optimized For Continuous video recording, high write workloads; Supported Cameras: Support for up to 64 or more HD cameras simultaneously or Higher; Reliability Features:Enhanced workload capability, vibration resistance, firmware for video streaming or More; Compatibility:Compatible with DVRs, NVRs, and video surveillance systems;Warranty:1 year ; Certifications:CE/RoHS/ISO	प्रति थान
२२६	8 Channel NVR		
२२७	16 Channel NVR	16-Channel NVR Specification: Supports up to 16 video inputs; decoding format H.265/H.264 or better; max decoding up to 1-ch @ 8MP / 2-ch @ 4MP / 6-ch @ 1080p or better; supports minimum 128 Mbps bandwidth; playback resolution up to 8MP or better; HDMI output 4K UHD (3840×2160) @ 30Hz; 2 SATA HDD slots supporting 8TB per slot or better; 1 × RJ-45 (10/100/1000 Mbps); minimum 2 × USB 2.0 and 1 × USB 3.0; power supply AC 100–240V, 50/60Hz; ONVIF compliant for third-party cameras; audio compression G.711u / G.711a; smart features include face detection, perimeter protection, and motion detection; operating temperature –10°C to 55°C; CE/FCC/ROHS certified; Warranty: Minimum 1 year.	प्रति थान
२२८	32 Channel NVR	32-Channel NVR Specification: Supports up to 32 video inputs; decoding format H.265/H.264 or better; max decoding up to 2-ch @ 8MP / 4-ch @ 4MP / 12-ch @ 1080p or better; supports 160 Mbps or higher bandwidth; playback resolution up to 8MP or better; HDMI output 4K UHD (3840×2160) @ 30Hz; 4 SATA HDD slots supporting 8TB per slot or better; 2 × RJ-45 (10/100/1000 Mbps); minimum 2 × USB 2.0 and 1 × USB 3.0; power supply AC 100–240V, 50/60Hz; ONVIF compliant for third-party cameras; audio compression G.711u / G.711a; smart features include face detection, perimeter protection, and motion detection; operating temperature –10°C to 55°C; CE/FCC/ROHS certified; Warranty: Minimum 1 year.	प्रति थान
२२९	64 Channel NVR	Supports 64 video inputs; HDD up to 128TB (8 × 16TB); RAID 0,1,5,6,10; 320 Mbps bandwidth (in/out); 1 HDMI (4K), 1 VGA (1080p/60Hz) outputs; 1-channel RCA audio; H.265 compression; max decoding 2-ch @ 32MP (25 fps); recording up to 32MP; 2 USB 2.0, 2 USB 3.0; 2 RJ45 10/100/1000 Mbps; supports IPv4, IPv6, HTTP, TCP/IP, DHCP, DNS; 16 alarm inputs, 8 outputs; 100-240 VAC power; CE, FCC certified; operates -10°C to +55°C; Warranty: Minimum 1 year.	प्रति थान
२३०	64 Channel NVR	Supports 64 video inputs; HDD 8 sata max 24TB in each slot; RAID 1,5; 320 Mbps bandwidth incoming, 160 mbps outgoing; 1 HDMI (4K), 1 VGA (1080p/60Hz) outputs; 1-channel RCA audio; H.265 compression; max decoding 2-ch @ 32MP (25 fps); recording up to 32MP; 2 USB 3.0; 2 RJ45 10/100/1000 Mbps; supports IPv4, IPv6, HTTP, TCP/IP, DHCP, DNS; 16 alarm inputs, 8 outputs; 100-240 VAC power; CE, FCC certified; operates -10°C to +55°C; Warranty: Minimum 1 year.	प्रति थान
२३१	MC Chassis	Media Converter Rack Specification: Supports up to 14 media converter slots; metal enclosure; standard 2U rack height.	प्रति थान
२३२	Metal Pole Box	Type: Outdoor; dimensions approximately 320 × 280 × 255 mm; water and dust proof; equipped with locking mechanism, cable knockouts, and mounting provisions.	प्रति थान

२३३	Waterproof PVC Junction box	Type: Outdoor; suitable for switch and power cables mounting; water and dust proof; equipped with locking mechanism, cable knockouts, and mounting provisions made by PVC.	प्रति थान
२३४	Pole Box Tagging Waterproof Sticker	Outdoor laminated waterproof KMC name and logo printed sticker to be affix in outdoor pole box/junction box, having size at least: 21X11 cm	प्रति थान
२३५	Fiber Cable Tagging Waterproof Sticker	Outdoor laminated waterproof KMC name and logo printed sticker to be affix in all outdoor fiber cable, cat6 cable and power cable, having size at least: 30.5X6.5 cm	प्रति थान
२३६	3 Kva online UPS	Type: online UPS; Capacity: 3kVA/ 48 V minimum; Input Voltage: 220–240V AC, single-phase; Output Voltage: Pure sine wave, 220–240V AC; Battery: Compatible with external battery bank; Protections: Overvoltage, undervoltage, short circuit, overload; Communication: Basic monitoring interface (RS232/USB); Display: Basic status indicators for power and battery; Operating Conditions: Suitable for typical office environment; Warranty: Minimum 1 year.	प्रति थान
२३७	5 Kva online UPS	Type: online UPS; Capacity: 5kVA / 96V minimum; Input Voltage: 220–240V AC, single-phase; Output Voltage: Pure sine wave, 220–240V AC; Battery: Compatible with external battery bank; Protections: Overvoltage, undervoltage, short circuit, overload; Communication: Basic monitoring interface (RS232/USB); Display: Basic status indicators for power and battery; Operating Conditions: Suitable for typical office environment; Warranty: Minimum 1 year.	प्रति थान
२३८	10 Kva online UPS	Type: online UPS; Capacity: 10kVA / 192 or 240 VDC minimum; 8KW, Input Voltage: 220–240V AC, 1:1-phase; Output Voltage: Pure sine wave, 220–240V AC; Battery: Compatible with external battery bank; Protections: Overvoltage, undervoltage, short circuit, overload; Communication: Basic monitoring interface (RS232/USB); Display: Basic status indicators for power and battery; Operating Conditions: Suitable for typical office environment; Warranty: Minimum 1 year.	प्रति थान
२३९	Battery 100 ah Tubular	Capacity: 100Ah; Type: Tubular Flooded Lead Acid, 12V nominal; Design Life: Minimum 5 years; Operating Temp: -5°C to +40°C; Maintenance: Low maintenance; Terminals: Bolt or Faston type; Standards: Compliant with IEC/IS or equivalent; Minimum 2 year replacement Warranty.	प्रति थान
२४०	Battery 150 ah Tubular	Capacity: 150Ah; Type: Tubular Flooded Lead Acid, 12V nominal; Design Life: Minimum 5 years; Operating Temp: -5°C to +40°C; Maintenance: Low maintenance; Terminals: Bolt or Faston type; Standards: Compliant with IEC/IS or equivalent; Minimum 2 year replacement Warranty.	प्रति थान
२४१	Battery 35 ah	Type: Sealed Maintenance-Free (SMF), Lead-Acid Battery; Capacity: 35Ah; Nominal Voltage: 12V; Technology: VRLA/AGM or better; Operating Temp: -5°C to +40°C; Terminals: Corrosion-resistant, top or front type; Usage: Compatible with UPS, Solar, and Telecom systems; Minimum 1 year replacement Warranty.	प्रति थान
२४२	Battery 65 ah	Type: Sealed Maintenance-Free (SMF), Lead-Acid Battery; Capacity: 65Ah; Nominal Voltage: 12V; Technology: VRLA/AGM or better; Operating Temp: -5°C to +40°C; Terminals: Corrosion-resistant, top or front type; Usage: Compatible with UPS, Solar, and Telecom systems; Minimum 1 year replacement Warranty.	प्रति थान
२४३	Battery 75 ah	Type: Sealed Maintenance-Free (SMF), Lead-Acid Battery; Capacity: 75Ah; Nominal Voltage: 12V; Technology: VRLA/AGM or better; Operating Temp: -5°C to +40°C; Terminals: Corrosion-resistant, top or front type; Usage: Compatible with UPS, Solar, and Telecom systems; Minimum 1 year replacement Warranty.	प्रति थान
२४४	Battery 100 Ah	Type: Sealed Maintenance-Free (SMF), Lead-Acid Battery; Capacity: 100Ah; Nominal Voltage: 12V; Technology: VRLA/AGM or better; Operating Temp: -5°C to +40°C; Terminals: Corrosion-resistant, top or front type; Usage: Compatible with UPS, Solar, and Telecom systems; Minimum 1 year replacement Warranty.	प्रति थान
२४५	Battery 150 Ah	Type: Sealed Maintenance-Free (SMF), Lead-Acid Battery; Capacity: 150Ah; Nominal Voltage: 12V; Technology: VRLA/AGM or better; Operating Temp: -5°C to +40°C; Terminals: Corrosion-resistant, top or front type; Usage: Compatible with UPS, Solar, and Telecom systems; Warranty: Minimum 1 year replacement.	प्रति थान
२४६	Battery 200 Ah	Type: Sealed Maintenance-Free (SMF), Lead-Acid Battery; Capacity: 200Ah; Nominal Voltage: 12V; Technology: VRLA/AGM or better; Operating Temp: -5°C to +40°C; Terminals: Corrosion-resistant, top or front type; Usage: Compatible with UPS, Solar, and Telecom systems; Warranty: Minimum 2 years.	प्रति थान

२४७	Battery 100 AH	Capacity: 100Ah; Type: Lead Acid, 12V nominal; Design Life: Minimum 5 years; Operating Temp: -5°C to +40°C; Maintenance: Low maintenance; Terminals: Bolt or Faston type; Standards: Compliant with IEC/IS or equivalent; Warranty: Minimum 2 years.	प्रति थान
२४८	Battery 150 AH	Capacity: 100Ah; Type: Lead Acid, 12V nominal; Design Life: Minimum 5 years; Operating Temp: -5°C to +40°C; Maintenance: Low maintenance; Terminals: Bolt or Faston type; Standards: Compliant with IEC/IS or equivalent; Warranty: Minimum 2 years.	प्रति थान
२४९	IP Telephone	Device type: IP phone; supports minimum 2 SIP accounts; LCD display 2.4 inch backlit screen; audio codec support for G.711, G.722 or similar; PoE supported; HD voice enabled; dual 10/100 Mbps Ethernet ports; 13 programmable key, security features include SRTP and TLS; basic features: call transfer, mute, call waiting, call log, and minimum 3-way conference; desktop and wall mountable, Warranty: Minimum 1 year	प्रति थान
२५०	SIP Server	Minimum 200 SIP users should works in default and expandable upto 800 in future; handles at least 40 concurrent calls; includes minimum 4 FXS analog out ports and and 4 FXO analog input port for telephone line in; dual 10/100/1000 Mbps Ethernet or better; audio codecs: G.711, G.722, G.729 or similar; video codec: H.264 or similar; SIP trunk supported; Dual Core CPU, call features include IVR/auto attendant, call recording, forwarding, transfer, voicemail, call queues, and minimum 3-way conference; video conferencing (3-5 way or better); built-in call recording with internal or external storage; security with TLS, SRTP, IP filtering or equivalent; supports auto-provisioning, multisite/remote access, and web GUI, Warranty: Minimum 1 year.	प्रति थान
२५१	IRIS Scanner Device	Scanner Type-Dual IRIS Scanner, Image Resolution-640 × 480 pixels per iris image or better, Image Format - JPEG/TIFF/PNG, Compression -1:10, Image Representation - Base 64 string, Standard-ISO/IEC 19794-6:2011 or above, Capture Time-less than 1 second, Interface- USB 2.0 High Speed or better, Protection Rating-IP64/IP65, certifications - CE /FCC/ROHS, Applications-National ID enrollment, Civil Registration, SDK Support-SDK for integration with biometric applications, Warranty: Minimum 1 year.	प्रति थान
२५२	Biometric Thumb Scanner Device		
२५३	Card Holder Horizontal	Horizontal Card Holder for Staff ID Card.	प्रति थान
२५४	Color Ribbon	Color Ribbon Should be Compatible with Existing Matica MC660 Card Printer at IT Department.	प्रति थान
२५५	Retransfer Film	Retransfer Film Should be Compatible with Existing Matica MC660 Card Printer at IT Department.	प्रति थान
२५६	Card Holder Vertical	Vertical Card Holder for Metro Police IT Card.	प्रति थान
२५७	Card Holder Clip	Card Holder Clip for Vertical Card Holder.	प्रति थान
२५८	Lanyard (Blue, Red, Green)	Lanyard (Blue, Red, Green) Card Holder for Staff ID Card (as per sample provided)	प्रति थान
२५९	RF card	Standard ID card size (CR80), operating frequencies like 125 kHz, 13.56 MHz etc	प्रति थान
२६०	Plain PVC card	Standard ID card size (CR80)	प्रति थान
२६१	Cleaning Kit	Cleaning Kit Should be Compatible with Existing Matica MC660 Card Printer at IT Department.	प्रति थान
२६२	Attendance Device with battery backup	CPU-Min. Dual-core processor, RAM/ROM -Min. 256 MB / 4GB , Auto Push Data Technology- Real time cloud-based auto push technology, Face/Fingerprint/Card Capacity-Min 3000, Logs-Min 100000, Display- At least 4.3-inch Touch Display, Language - English (Default), Communication - At least TCP/IP, WIFI, USB, Battery- At least in-built or External (2000 mAh battery) , Recognition Speed- Less than or equal to 0.5 Sec., SDK- Should Support/ Provide Realtime Data to Attendance Software of KMC, Certifications -CE or FCC or Rohs , Warranty - Minimum 1 Years Product Warranty .	प्रति थान
२६३	Multi-Biometric Access Control with battery backup	CPU-Min. Dual-core processor, RAM/ROM -Min. 256 MB / 4GB , Auto Push Data Technology- Real time cloud-based auto push technology, Face/Fingerprint/Card Capacity-Min 1200, Logs-Min 100000, Display- At least 2.4-inch Display, Physical Keypad with alphanumeric, Language - English (Default), Communication - At least TCP/IP, USB, Electric Lock*1, Door Sensor*1, Exit Button*1, Battery- At least in-built or External (2000 mAh battery) , Recognition Speed- Less than or equal to 0.5 Sec., Certifications -CE or FCC or Rohs , Accessories - Warranty - Minimum 1 Years Product Warranty .	प्रति थान

२६४	Access Control Door Lock Device	Type- Fingerprint + Card Access Control , Display- 2.4" or higher, Fingerprint Capacity- 1500 or more, Card Capacity-1500 or more, Log Capacity-100000 or more, Communication Interfaces-RS485, TCP/IP, USB-Host or more, Access Control Interface-3rd-party Electric Lock/ Lock Relay, Door Sensor, Exit Button, Alarm or more, Exit Device, Magnetic Lock, Power Supply- Power Supply-12V DC,3A ; Min. 1-year warranty .	प्रति थान
२६५	Branded Laptop 15.6"	Processor: At least 10 cores, 12 threads, 12 MB cache, up to 4.4 GHz or better, RAM: Minimum 8 GB DDR4, 2600 MHz or higher, Storage: Minimum 512 GB SSD, PCIe Gen 4.0 or higher interface (NVMe preferred), Display: Maximum 15.6-inch FHD (1920 × 1080) IPS, non-touch or better, Graphics: Integrated graphics, Keyboard/Mouse: English keyboard (backlit optional) or multi-gesture touchpad, Multimedia: Built-in speakers with HD webcam, Battery: Minimum 40 Wh integrated battery or better, Connectivity: Wi-Fi 5 and Bluetooth 5.0 or better, Ports: 1 × Universal Audio Port, 2 × USB 3.2, 1 × Type-C, 1 × DisplayPort/HDMI, 1 × Power Connector Port, Operating System: Genuine Windows 11 License, Warranty: Minimum 1-year manufacturer warranty covering parts, battery, and service, Accessories: Laptop charger and laptop bag.	प्रति थान
२६६	Branded Laptop 14"	Processor Speed: Minimum 10 cores, 12 threads, 12 MB cache, 4.8 GHz or better, RAM: Minimum 16 GB LPDDR5, 5200 MHz or higher, Storage: Minimum 512 GB PCIe Gen 4 NVMe M.2 SSD, Display: 14-inch, 1920 × 1200 (2K/WUXGA) resolution or better, Graphics: Integrated graphics, Multimedia: Built-in dual speakers, HD webcam, backlit keyboard and touchpad, Communication: Wi-Fi 6 and Bluetooth 5.2 or better, Battery: Minimum 57 Wh, Ports: Minimum HDMI, USB-C, USB-A, Ethernet (optional), and audio port, Operating System: Genuine Windows 11 Home/Pro License, Accessories: Laptop charger and same-brand laptop bag, Certifications: Energy Star Certified, Warranty: Minimum 1-year full product warranty.	प्रति थान
२६७	All In One Desktop (Branded)	Processor Speed: Minimum 8 cores, 12 threads, 12 MB cache, 4.6 GHz or better, RAM: Minimum 16 GB DDR4 or above, Storage: Minimum 512 GB SSD or above, Display: Minimum 23.8-inch or higher, anti-glare FHD (1920 × 1080) display, Graphics: Integrated graphics, Multimedia: Built-in speaker and HD webcam, Communication: Wi-Fi 6 and Bluetooth 5.0 or better, Ports: Minimum HDMI, USB 2.0, USB 3.2 Gen 2, Ethernet (RJ-45), power connector, and audio jack, Operating System: Genuine Windows 11 Home/Pro License, Accessories: Keyboard, mouse, AIO stand, power cable, and adapter of the same brand, Certifications: Energy Star Certified Warranty: Minimum 1-year full product warranty.	प्रति थान
२६८	Handheld SLAM LiDAR Scanner	Weight: ≤ 1.5 kg Scanning Rate: ≥ 200,000 points per second Positioning: SLAM / IMU-based /GNSS MODULE LiDAR Accuracy (Absolute): ≤ 3 cm Relative Accuracy: ≤ 2 cm Maximum Range: ≥ 70 meters (at 80% reflectivity) Field of View (LiDAR): 360° horizontal Camera System: Integrated RGB camera, ≥ 24 MP Battery Life: ≥ 1.5 hours continuous scanning Environmental Protection: ≥ IP54 LiDAR Processing Software: Perpetual Gaussian Splat Processing Software: Annual	प्रति थान
२६९	RTK Survey / Mapping Drone (integrated survey camera)	Type: RTK-enabled mapping / photogrammetry UAV (multirotor) Weight Class: Compact (< 2 kg) Mapping Camera: ≥ 20 MP, mechanical / global shutter, factory-calibrated Positioning: Integrated RTK; ≤ 2 cm + 1 ppm (H) with RTK / PPK Correction Support: NTRIP / base station / PPK Image Capture: Nadir + oblique (single-pass multi-angle) Flight Endurance: ≥ 30 min per battery Obstacle Avoidance: Multi-directional Environmental: Weather-resistant (IP-rated) Output: Georeferenced imagery- orthophoto / DSM / DTM / point cloud / 3D model	प्रति थान
२७०	RTK GNSS Receiver	Type: Multi-band, multi-constellation RTK GNSS receiver (base or rover) Constellations: GPS, GLONASS, Galileo, BeiDou (multi-frequency, incl. L5) RTK Accuracy: ≤ 15 mm + 1 ppm (H); ≤ 20 mm + 1 ppm (V) Operating Modes: RTK / NTRIP / PPK / Static Tilt Compensation: IMU-based (calibration-free) Corrections I/O: NTRIP (RTCM3), UHF radio Enclosure / Battery: IP67 or better; ≥ 12 h field operation Coordinate Systems: WGS84 / UTM / MUTM / Everest 1830	प्रति थान
		Type: Reflectorless robotic-grade manual total station Angular Accuracy: ≤ 5"	

२७१	Total Station	Distance Accuracy: $\leq 2 \text{ mm} + 2 \text{ ppm}$	प्रति थान
		Reflectorless Range: Up to 500 m	
		Prism Range: Up to 2,000 m (single prism)	
		Compensation: Dual/quadruple-axis automatic compensator	
		Display / Interface: Colour touchscreen, onboard field software	
		Connectivity: Bluetooth, USB, RS232	
		Ingress Protection: $\geq \text{IP54}$	
		Battery: ≥ 16 hours field operation	
		System Includes: Instrument, tribrach, battery (x2), charger, carry case, onboard field software licence	
		Warranty: Minimum 1-year manufacturer warranty	

Mapping सम्बन्धि कार्यका लागि भाडा दर

S.N.	Items	Minimum Specification	Unit
1	Total Station	Angle Accuracy : 5" (arc-seconds)	Per Unit
		Telescope Magnification : 30×	
		Reflectorless Range : Up to 500 m	
		Prism Range : Up to 4,000 m (ideal up to 5,000–6,000 m)	
		Distance Accuracy (Prism) : $\pm(2 \text{ mm} + 2 \text{ ppm} \times D)$	
		Distance Accuracy (No Prism) : $\pm(3 \text{ mm} + 2 \text{ ppm} \times D)$	
		Measurement Time : Fine: 0.9 s, Rapid: 0.7 s, Tracking: 0.3 s	
		Data Storage : 10,000 points internal + USB (up to 8 GB)	
		Battery Life : Up to 36 hours (with standard battery)	
		Environmental Rating : IP66 (dust and water resistant)	
2	Mapping Drone below 2 Kg	Weight (with propellers) : 1 kg	Per Unit
		Maximum Flight Time : Up to 40 minutes	
		Maximum Horizontal Speed : Up to 12 m/s	
		Wind Resistance : Up to 10 m/s	
		Maximum Operating Altitude : Up to 5,000 m above sea level	
		Wide-Angle Camera : 20 MP, 4/3" CMOS sensor, mechanical shutter	
		Transmission Range : Up to 10 km	
		Positioning Accuracy (with RTK) : $\pm 0.1 \text{ m}$ horizontal and vertical	
3	Mapping Drone above 2 Kg	Obstacle Avoidance : Omnidirectional sensors	Per Unit
		Weight (with batteries) : 5 kg	
		Max Takeoff Weight : 8 kg	
		Max Flight Time : Up to 50 minutes	
		Max Horizontal Speed : 15 m/s (Sport mode)	
		Max Wind Resistance : 12 m/s	
		Operating Temperature : -20°C to 50°C	
		Operating Altitude : Up to 7,000 m	
		RTK Positioning Accuracy : Horizontal: $\pm 0.1 \text{ m}$; Vertical: $\pm 0.1 \text{ m}$	
		Obstacle Avoidance : Omnidirectional sensors	
4	Handheld SLAM LiDAR Scanner (Standard)	Ingress Protection Rating : IP45	Per Unit
		Weight : 1 kg	
		Scanning Rate : Up to 200,000 points per second	
		LiDAR Accuracy (Absolute) : 3 cm	
		Relative Accuracy : 2 cm	
		Maximum Range : Up to 70 m (at 80% reflectivity)	
		Field of View (LiDAR) : $360^\circ \times -7^\circ \sim +52^\circ$	
		Field of View (Camera) : $360^\circ \times 360^\circ$	
		Camera System : Dual 48 MP panoramic	
		Battery Life : Up to 1.5 hours	
5	Handheld SLAM LiDAR Scanner (Advanced)	Environmental Protection : IP54	Per Unit
		Weight : 2 kg	
		Scanning Rate : Up to 600,000 points per second	
		LiDAR Accuracy (Absolute) : 3 cm	
		Relative Accuracy : 2 cm	
		Maximum Range : Up to 120 m (at 80% reflectivity)	
		Field of View (LiDAR) : $360^\circ \times 270^\circ$	
		Field of View (Camera) : $190^\circ \times 190^\circ$	
		Camera System : Dual 48 MP panoramic	
		Battery Life : Up to 1.5 hours	
6	Handheld Reality Capture Camera (3DGS Optimized)	Environmental Protection : IP54	Per Unit
		Weight : $\leq 1 \text{ kg}$	
		Imaging : ≥ 4 camera modules / high-resolution panoramic	
		Camera System : 2 × fisheye, 2 × front	
		LiDAR : Integrated, for geometry and scale	
		Field of View (LiDAR) : $180^\circ \times 180^\circ$	
		Scanning Range : Up to 30 m	
		Operation : Indoor and outdoor	
		Battery Life : Up to 1.5 hours	
		Output : High-resolution 3D Gaussian Splat	
7	Drone Mounted LiDAR	Weight : 900 g	Per Unit
		LiDAR Channels : 32 channels	
		Scanning Rate : Up to 240,000 points per second	
		Maximum Range : Up to 100 m	
		Accuracy (Absolute) : $\pm 5 \text{ cm}$	
		Relative Accuracy : $\pm 3 \text{ cm}$	
		Field of View (Vertical) : 50°	
		Operating Temperature : -20°C to 50°C	
		Positioning : Integrated GNSS and IMU	
		Compatible Platforms : Drone above 2 kg weight	
8	Data Processing (Photogrammetry)	GCP Integration : Included	Per Sq KM
		Orthophoto : Included	
		Classification Method : Automated	
		Classified Point Cloud Generation : Automated classification output	

		DTM, DEM and Contour Generation : Included	
		3D Mesh : Included	
9	Data Processing (Photogrammetry)	GCP Integration : Included	Per Sq KM
		Orthophoto : Included	
		Classification Method : Manual + Automated	
		Classified Point Cloud Generation : Manually verified classification	
		DTM, DEM and Contour Generation : Included	
		3D Mesh : Included	
10	Data Processing (LiDAR + Photogrammetry)	GCP Integration : Included	Per Sq KM
		Orthophoto : Included	
		Classification Method : Automated	
		Classified Point Cloud Generation : Automated classification output	
		DTM, DEM and Contour Generation : Included	
		3D Mesh : Included	
11	Data Processing (LiDAR + Photogrammetry)	GCP Integration : Included	Per Sq KM
		Orthophoto : Included	
		Classification Method : Manual + Automated	
		Classified Point Cloud Generation : Manually verified classification	
		DTM, DEM and Contour Generation : Included	
		3D Mesh : Included	
12	Videography (Site Recce & Structure Position Guidance) – Raw / Non-Edited	Purpose : Site reconnaissance and structure position guidance (non-cinematographic)	Per Sq KM
		Footage Type : Raw / non-edited	
		Editing : Not included	
		Location Tagging : Not included	
		Delivery Format : Unprocessed raw video files	
13	Videography (Site Recce & Structure Position Guidance) – Edited, Location-Pinned	Purpose : Site reconnaissance and structure position guidance (non-cinematographic)	Per Sq KM
		Footage Type : Edited	
		Editing : Included (cuts, annotations)	
		Location Tagging : Specific locations pinned / geotagged	
		Delivery Format : Edited video with pinned location markers	
14	3D Gaussian Splat (3DGS) & Point Cloud Delivery	Level of Detail : Coarse (outdoor – large area) / Standard / Fine / High	Per Sq m
		Method : 3D Gaussian Splatting (radiance-field reconstruction)	
		Colorization : Photorealistic true-colour	
		Georeferencing : Aligned to point-cloud coordinate system (optional)	
		Web Delivery : 3D Tiles, web-viewer compatible (optional)	
		Delivery Formats : .ply, .splat, .lcc, .usd, .las, .laz, .e57	
		Point Cloud Processing Level : Raw / Cleaned / Classified	Additional Per Sq m
15	DGPS	Operating Temperature : -20 °C to +65 °C	Per Unit
		Ingress Protection : IP65 (dust-tight and waterproof)	
		Battery Type : Li-ion 6400 mAh	
		Battery Life : 8 hours as RTK rover; 12 hours logging	
		External Power Input : 6–40 V via external power input	
		Supported GNSS Systems : GPS, GLONASS	
		RTK Accuracy : Horizontal: 8 mm + 1 ppm; Vertical: 14 mm + 1 ppm	
		PPK Accuracy : Horizontal: 6 mm + 0.5 ppm; Vertical: 10 mm + 1 ppm	
		Static Accuracy : Horizontal: 5 mm + 0.5 ppm; Vertical: 8 mm + 1 ppm	
		Update Rate : Up to 10 Hz for GPS; 5 Hz for GNSS	
		Connectivity : 3.5G modem, Wi-Fi 802.11 b/g/n, Bluetooth 4.0 / 2.1 EDR	
		NTRIP Support : Supported	
		External Radio : Built-in UHF radio (868 / 915 MHz), range up to 8 km line-of-sight	
		SIM Card Slot : Nano SIM slot for mobile data connectivity	
16	Drone Pilot (Mapping and Inspection)	Certification / License : Valid drone pilot license / minimum Diploma in Surveying or Geomatics Engineering	Per Day
		Flight Hours : Minimum 10–50 logged flight hours certified by licence provider, or three-plus years with a drone service provider institution	
		Knowledge of Aviation Rules : Understanding of local aviation laws and regulations	
		Operational Skills : Proficiency in operating different drone types and models	
		Safety Training : Training on emergency procedures and safe flight practices	
		Visual Line of Sight (VLOS) Operation : Able to maintain VLOS, or operate BVLOS if certified	
		Weather Awareness : Able to assess weather conditions safe for drone operation	
		Equipment Maintenance : Basic drone maintenance and troubleshooting	
		Mapping / Surveying Knowledge : Understanding of photogrammetry, LiDAR or aerial mapping principles	
		Communication Skills : Able to coordinate with team and air traffic control if necessary	
		Educational Background : Diploma in Surveying / Geomatics	
		DGPS Equipment Knowledge : Proficient in operating DGPS receivers and base stations	
		Surveying Skills : Understanding of surveying principles and techniques	
		Coordinate Systems & Projections : Knowledge of local and global coordinate systems (e.g. WGS84, UTM, MUTM)	

17	DGPS Operator	Data Collection & Processing : Able to collect accurate GPS data and process corrections	Per Day
		Field Experience : Experience working on surveying sites with DGPS equipment	
		Maintenance Skills : Basic troubleshooting and maintenance of DGPS equipment	
		Software Proficiency : Familiar with GIS, CAD and GNSS data processing software	
		Communication Skills : Effective communication for coordination with survey teams	
		Safety Awareness : Knowledge of field safety procedures and regulations	
18	DGPS Static Post Processing	Responsible : DGPS Operator	Per Point

बोटबिरुवा र उद्धान सामग्री

क्र.स.	मालसामानको विवरण	स्पेशिफिकेसन	एकाई
१	Blade घाँस काट्ने मेसिनको	घाँस काट्ने	थान
२	औषधी छत्रे पम्प	प्लाष्टिकको ५ लिटरको	प्रति थान
३	औषधी छत्रे पम्प	प्लाष्टिकको ८ लिटरको	प्रति थान
४	औषधी छत्रे पम्प	प्लाष्टिकको १० लिटरको	प्रति थान
५	औषधी छत्रे पम्प	प्लाष्टिकको १६ लिटरको	प्रति थान
६	हजारी	प्लाष्टिकको १० लिटरको	प्रति थान
७	हजारी	प्लाष्टिकको ५ लिटरको	प्रति थान
८	मौरी गोला घर सहित	काठको	प्रति घर
९	COPPER OXYCHLORIDE		के जी
१०	सिक्रेचर	FOLCON or equivalent, 8 inch	प्रति थान
११	निमको पिना		के जी
१२	निमको तेल	100ML	प्रति थान
१३	कोकोपिट		के जी
१४	किंग पाम	२ फिट भन्दा माथि	प्रति बोट
१५	न्याविज पाम	२ फिट भन्दा माथि	प्रति बोट
१६	स्नेक पाम	२ फिट भन्दा माथि	प्रति बोट
१७	धुपी	४ फिटको	प्रति बोट
१८	समी	५ फिटको	प्रति बोट
१९	कपुर	५ फिटको	प्रति बोट
२०	असारे	५ फिटको	प्रति बोट
२१	असोका	५ फिटको	प्रति बोट
२२	गुलाफ	२-३ फिटको	प्रति बोट
२३	बेगमवेली बन्साई	२-३ फिटको	प्रति बोट
२४	बेगमवेली	२-३ फिटको	प्रति बोट
२५	डाइफन भेसिया	२-३ फिटको	प्रति बोट
२६	फिलोडेन्डण	२-३ फिटको	प्रति बोट
२७	चाइनिज मचेरा	२-३ फिटको	प्रति बोट
२८	ड्रेसिना	२ -३फिटको	प्रति बोट
२९	लक्की बेम्बो	२-३ फिटको	प्रति बोट
३०	भेरिकेटोर ड्रेसिना	२ -३फिटको	प्रति बोट
३१	फिडल लिफ	२-३ फिटको	प्रति बोट
३२	एरलोनिमा	२ -३फिटको	प्रति बोट
३३	जिजि प्लार	२-३ फिटको	प्रति बोट
३४	सेप्लोरिया	२ -३फिटको	प्रति बोट
३५	पिस लिली	२ -३फिटको	प्रति बोट
३६	स्पाथि फेलम	१ फिटको	प्रति बोट
३७	आँप	३ फिटको	प्रति बोट
३८	कागती	३ फिटको	प्रति बोट
३९	सुन्तला	३ फिटको	प्रति बोट
४०	मुन्तला	३ फिटको	प्रति बोट
४१	आरु बखडा	३ फिटको	प्रति बोट

४२	जापानीज हलुवावेद	३ फिटको	प्रति बोट
४३	स्थाउको बोट	३ फिटको	प्रति बोट
४४	ओखरको बोट	३ फिटको	प्रति बोट
४५	कागजी बदाम बोट	३ फिटको	प्रति बोट
४६	आरुखडाको बोट	३ फिटको	प्रति बोट
४७	लिचिको बोट	३ फिटको	प्रति बोट
४८	खुर्पानीको बोट	३ फिटको	प्रति बोट
४९	आरुको बोट	३ फिटको	प्रति बोट
५०	नास्पातीको बोट	३ फिटको	प्रति बोट
५१	अंगुरको बोट	३ फिटको	प्रति बोट
५२	जैतुनको बोट	३ फिटको	प्रति बोट
५३	पिकानटको बोट	३ फिटको	प्रति बोट
५४	निमको बोट	३ फिटको	प्रति बोट
५५	सिमेन्टको गमला	३० इन्चको ठुलो	थान
५६	सिमेन्टको गमला	२४ इन्चको ठुलो	थान
५७	सिमेन्टको गमला	२० इन्चको ठुलो	थान
५८	माटोको गमला	१० इन्चको	थान
५९	माटोको गमला	१२ इन्चको	थान
६०	माटोको गमला	१४ इन्चको	थान
६१	माटोको गमला	१६ इन्चको	थान
६२	सेरामिकको गमला प्लेट सहित	१० इन्चको	थान
६३	सेरामिकको गमला प्लेट सहित	१२ इन्चको	थान
६४	सेरामिकको गमला प्लेट सहित	१४ इन्चको	थान
६५	सेरामिकको गमला प्लेट सहित	१६ इन्चको	थान
६६	फाइबरको गमला प्लेट सहित	३० इन्चको ठुलो	थान
६७	फाइबरको गमला प्लेट सहित	२४ इन्चको ठुलो	थान
६८	फाइबरको गमला प्लेट सहित	१० इन्चको	थान
६९	फाइबरको गमला प्लेट सहित	१२ इन्चको	थान
७०	फाइबरको गमला प्लेट सहित	१४ इन्चको	थान
७१	फाइबरको गमला प्लेट सहित	१६ इन्चको	थान
७२	फाइबरको गमला प्लेट सहित	२४ इन्चको	थान
७३	फाइबरको गमला प्लेट सहित	३० इन्चको	थान
७४	सयपत्री	६ इन्चको पोलिव्याग	प्रति बोट
७५	गोदावरी	६ इन्चको पोलिव्याग	प्रति बोट
७६	भ्यागुते फुल	६ इन्चको पोलिव्याग	प्रति बोट
७७	जिनिया	६ इन्चको पोलिव्याग	प्रति बोट
७८	भिन्का	६ इन्चको पोलिव्याग	प्रति बोट
७९	डालिया	६ इन्चको पोलिव्याग	प्रति बोट
८०	कोलियस	६ इन्चको पोलिव्याग	प्रति बोट
८१	कार्नेशन	६ इन्चको पोलिव्याग	प्रति बोट
८२	सयपत्री बोनान्जा	६ इन्चको पोलिव्याग	प्रति बोट
८३	जरवेरा	६ इन्चको पोलिव्याग	प्रति बोट
८४	पितुनिया डबल सिंगल	६ इन्चको पोलिव्याग	प्रति बोट
८५	असर्फी	६ इन्चको पोलिव्याग	प्रति बोट
८६	दियाँनथस	६ इन्चको पोलिव्याग	प्रति बोट
८७	पेन्जी	६ इन्चको पोलिव्याग	प्रति बोट
८८	बागमुखी	६ इन्चको पोलिव्याग	प्रति बोट
८९	सिनेरिया	६ इन्चको पोलिव्याग	प्रति बोट
९०	प्राईमरोज	६ इन्चको पोलिव्याग	प्रति बोट
९१	दालिया	६ इन्चको पोलिव्याग	प्रति बोट
९२	सिजनल फुल	६ इन्चको पोलिव्याग	प्रति बोट
९३	डी ए पि मल		के जी

९४	युरिया मल		के जी
९५	पोटास मल		के जी
९६	चिनी मल		के जी
९७	हड्डी मल		के जी
९८	खरानीको धुलो		के जी
९९	पिटमस		के जी
१००	बलौटे माटो		घन मि
१०१	हर्न मिल		के जी
१०२	फिसमिल		के जी
१०३	पाइप	प्लास्टिकको १ इन्चको, बगैँचामा पानी हाल्ने	रोल
१०४	तार ब्रुश		गोटा
१०५	बासको भाटा	६ फिट अग्लो १.५ इन्च मोटाई को	गोटा
१०६	कृषि चुन		के जी
१०७	कम्पोस्ट मल	प्याकेट	प्रति केजी
१०८	भर्मी कम्पोस्ट मल		के जी
१०९	माछाको दाना		के जी
११०	एल डी पोली		के जी
१११	नीलकाडा हेज	६ इन्चको पोलिब्याग	प्रति बोट
११२	३ फिट सम्मको धूपीको बोट trimming गरि साईट सफा गर्ने		गोटा
११३	३ -५ फिट सम्मको धूपीको बोट trimming गरि साईट सफा गर्ने		गोटा
११४	५ फिट भन्दा ठुलो धूपीको बोट trimming गरि साईट सफा गर्ने		गोटा
११५	हेज trimming गरि साईट सफा गर्ने		रनिङ मिटर
११६	५ फिट सम्मको रुख साईज मिलायर trimming गरि साईट सफा गर्ने कार्य		गोटा
११७	५ -१०फिट सम्मको रुख साईज मिलायर trimming गरि साईट सफा गर्ने कार्य		गोटा
११८	१० फिट भन्दा ठुलो रुख साईज मिलायर trimming गरि साईट सफा गर्ने कार्य		गोटा
११९	टिगार्ड निकाल्ने र टेकु सम्म पुर्याउनेकार्य		प्रति गोटा

बाघ वादनका समायोत्रीको विवरण

क्र.स.	मालसामानको विवरण	स्पेशिफिकेसन	एकाई
१	धिमे	काठको ठुलो (Minimum १५ inches Bass)	थान
२	धिमे	काठको मझौला (Minimum १२ inches Bass)	थान
३	धिमे	काठको सानो (Minimum ९ inches Bass)	थान
४	धिमे	पित्तलको ठुलो (Minimum १५ inches Bass)	थान
५	धिमे	पित्तलको मझौला (Minimum १२ inches Bass)	थान
६	धा:	ठुलो	थान
७	धा:	मझौला	थान
८	नायोखि		थान
९	भुस्या:	ठुलो	थान
१०	भुस्या:	मझौला	थान
११	छुस्या:		थान
१२	खि	ठुलो	थान
१३	खि	मझौला	थान
१४	खि	सानो	थान
१५	कोँचाखि		थान
१६	पछिमा	ठुलो	थान
१७	पछिमा	मझौला	थान

१८	मादल	ढुलो	थान
१९	मादल	मझौला	थान
२०	मादल	सानो	थान
२१	ता:	ढुलो	थान
२२	ता:	सानो	थान
२३	बबूचा जोडी		थान
२४	घौ	घण्टी	थान
२५	जोर नगरा	माटोको ढुलो	थान
२६	जोर नगरा	तामाको ढुलो	थान
२७	जोर नगरा	तामाको मझौला	थान
२८	कान्ता डबडब	धातुको	थान
२९	कान्ता डबडब	काठको	थान
३०	बाँसुरी	काठको (घोर)	थान
३१	बाँसुरी	काठको (माझवाल)	थान
३२	बाँसुरी	काठको (तीप)	थान
३३	बाँसुरी	प्लाष्टिकको D Scale	थान
३४	बाँसुरी	बाँसको ढुलो G Scale	थान
३५	बाँसुरी	बाँसको मध्यम D Scale	थान
३६	बाँसुरी	बाँसको सानो G Scale	थान
३७	बय्	काठको	थान
३८	चिम्टा झ्याली	नेवारी	जोर
३९	चक्रा झ्याली	नेवारी	जोर
४०	पोगा सेट	तामाको	थान
४१	पञ्चैबाजा सेट		थान
४२	सारङ्गी परम्परागत		थान
४३	सारङ्गी शास्त्रिय		थान
४४	सारङ्गी कलात्मक		थान
४५	ढ्यांग्रो ढुलो		थान
४६	ढ्यांग्रो सानो		थान
४७	खैजडी		थान
४८	दः (६ कुने)		थान
४९	धोलक स्टाण्डर्ड		थान
५०	धोलक नेवारी		थान
५१	मुर्चुङ्गा ढुलो		थान
५२	मुर्चुङ्गा मझौला		थान
५३	हार्मोनियम स्केल चेन्चर		थान
५४	हार्मोनियम बिणा १७		थान
५५	हार्मोनियम बिणा ५		थान
५६	तबला	माटोको	सेट
५७	तबला	तामाको	सेट
५८	तबला	स्टिलको	सेट
५९	मंजिरा		थान
६०	मुहालि		थान
६१	कर्ताल		थान
६२	पँथ्ता:	तामाको	थान
६३	डम्फु		थान
६४	तुङ्गना		थान
६५	बिगुल		थान
६६	घंघला ढुलो		थान
६७	घंघला ढुलो		थान

व्यायम सम्बन्धी सामग्रीहरु

S.N.	Items	Specification	Unit
୧	Machine cutting surface dressed Stone	4 " thick	Sq. Ft
୨	Machine cutting surface dressed Stone	3 " thick	Sq. Ft
୩	Single rower	1. Materials: Galvanized Mild steel pipes 2. Dimension:1320mmx990mmx1140mm 3. Main frame pipe 114mm with thickness 3.5mm 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. 5. Bearing holder 60mm pipe with thickness 4.5mm. 6. Step shaft EN8.8 shaft of diameter 32mm used with step of 25mm. 7. Mild steel seat, back seat and foot cover with 2mm thickness. 8. Permanent lubricated sealed 9. All open ends of pipe either sealed or closed by MS/LLDPE cap for user safety. 10. Rubber handle cover with best grip. 11. Paint: Electrostatic oven cooked Powder Coated Paint. 12. Thickness of Base plate for fixing 8 mm with 4 ribs. 13. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod	No.
୪	Air Walker	1. Materials: Galvanized Mild steel pipes 2. Dimension:1320mmx440mmx1200mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. Step EN8.8 shaft of 32mm used with step of 25mm. 6. Mild steel foot cover with thickness 2mm on frame. 7. Permanent lubricated sealed bearing 8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 9. Paint: Electrostatic oven cooked Powder Coated Paint.. 10. Thickness of Base plate for fixing 8 mm with 4 ribs. 11. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod	No.
୫	Push and pull chair/Double Shoulder press	1. Materials: Galvanized Mild steel pipes 2. Dimension:2100mmx710mmx1870mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. Step EN8.8 shaft of 32mm used with step of 25mm. 6. Mild steel seat and back seat with thickness 2mm on frame. 7. Permanent lubricated sealed bearing 8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 9. Rubber handle cover with best grip. 10. Paint: Electrostatic oven cooked Powder Coated Paint.. 11. Thickness of Base plate for fixing 8 mm with 4 ribs. 12. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod	No.
୬	Double Elliptical trainer	1. Materials: Galvanized Mild steel pipes 2. Dimension:1265mmx550mmx1780mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. Step EN8.8 shaft of 32mm used with step of 25mm. 6. Mild steel foot cover with thickness 2mm on frame. 7. Permanent lubricated sealed 8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 9. Rubber handle cover with best grip.	No.

		10. Paint: Electrostatic oven cooked Powder Coated Paint..	
		11. Thickness of Base plate for fixing 8 mm with 4 ribs.	
		12. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	
9	Air Swing/Double surf board	1. Materials: Galvanized Mild steel pipes	
		2. Dimension:1465mmx932mmx1348mm	
		3. Main frame pipe 114mm with thickness 3.5mm.	
		4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm.	
		5. Step EN8.8 shaft of 32mm used with step of 25mm.	
		6. Mild steel foot cover with thickness 2mm on frame.	
		7. Permanent lubricated sealed	
		8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety.	
		9. Rubber handle cover with best grip.	
		10. Paint: Electrostatic oven cooked Powder Coated Paint..	No.
		11. Thickness of Base plate for fixing 8 mm with 4 ribs.	
		12. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	
10	Double Splits machine	1. Materials: Galvanized Mild steel pipes	
		2. Dimension:1000mmx850mmx1248mm	
		3. Main frame pipe 114mm with thickness 3.5mm.	
		4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm.	
		5. Step EN8.8 shaft of 32mm used with step of 25mm.	
		6. Mild steel foot cover with thickness 2mm on frame.	
		7. Permanent lubricated sealed	
		8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety.	
		9. Rubber handle cover with best grip.	
		10. Paint: Electrostatic oven cooked Powder Coated Paint..	No.
		11. Thickness of Base plate for fixing 8 mm with 4 ribs.	
		12. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	
11	Sit-Up-board single/abdominal fitness combo	1. Materials: Galvanized Mild steel pipes	
		2. Dimension:1700mmx1350mmx800mm	
		3. Main frame pipe 114mm with thickness 3.5mm.	
		4. Handle frame 32mm and other frame 48mm pipe with thickness 3mm.	
		5. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety.	
		6. Paint: Paint: Electrostatic oven cooked Powder Coated Paint..	No.
		7. Thickness of Base plate for fixing 8 mm with 4 ribs.	
		8. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	
12	Push Up bar, Leg lifter and Dip station	1. Materials: Galvanized Mild steel pipes	
		2. Dimension:1480mmx1680mmx2100mm	
		3. Main frame pipe 114mm with thickness 3.5mm.	
		4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm.	
		5. Step EN8.8 shaft of 32mm used with step of 25mm.	
		6. Mild steel seat and back seat with thickness 2mm on frame.	
		7. Permanent lubricated sealed	
		8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety.	
		9. Rubber handle cover with best grip.	
		10. Paint: Paint: Electrostatic oven cooked Powder Coated Paint..	No.
		11. Thickness of Base plate for fixing 8 mm with 4 ribs.	

		12. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	
११	Treadmill	1. Materials: Galvanized Mild steel pipes 2. Dimension:1200mmx750mmx1400mm 3. Main frame rectangle pipe 80x40mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. EN8.8 shaft of 16mm used with step of 15mm. 6. Permanent lubricated sealed 7. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 8. Paint: Electrostatic oven cooked Powder Coated Paint.. 9. Thickness of Base plate for fixing 8 mm with 4 ribs. 10. 73Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod	No.
			
१२	Shoulder wheel	1. Materials: Galvanized Mild steel pipes 2. Dimension:1370mmx890mmx1480mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. Step EN8.8 shaft of 32mm used with step of 25mm. 6. Permanent lubricated sealed 7. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 8. Rubber handle cover with best grip. 9. Paint: Electrostatic oven cooked Powder Coated Paint. 10. Thickness of Base plate for 8 mm. 11. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
	 		
१३	Leg extension (Stepper) and fitness rider cycle	1. Materials: Galvanized Mild steel pipes 2. Dimension:1700mmx550mmx1548mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. Step EN8.8 shaft of 32mm used with step of 25mm. 6. Mild steel seat, foot cover and foot peddle with thickness 2mm on frame. 7. Permanent lubricated sealed 8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 9. Paint: Electrostatic oven cooked Powder Coated Paint.. 10. Thickness of Base plate for fixing 8 mm with 4 ribs. 11. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
			
१४	Horse Rider	1. Materials: Galvanized Mild steel 2. Dimension:1000mmx700mmx1000mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Mild steel Flat of 50x10mm used. Bearing holder 60mm pipe with thickness 4.5mm. 5. Step EN8.8 shaft of 32mm used with step of 25mm. 6. Mild steel seat with thickness 2mm on frame. 7. Permanent lubricated sealed 8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 9. Nylon stopper 1inch diameter 10. Rubber handle cover with best grip. 11. Paint: Paint: Electrostatic oven cooked Powder Coated Paint.. 12. Thickness of Base plate for fixing 8 mm with 4 ribs. 13. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
			

၄၃	Double cross walker, Skier		1. Materials: Galvanized Mild steel 2. Dimension:1380mm x570mm x1620mm 3. Main frame rectangle pipe 80X40mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. Step EN8.8 shaft of 32mm used with step of 25mm. 6. Mild steel foot cover with thickness 2mm on frame. 7. Permanent lubricated sealed 8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 9. Rubber handle cover with best grip. 10. Paint: Electrostatic oven cooked Powder Coated Paint. 11. Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
၄၄	Triple Twister sitting and standing		1. Materials: Galvanized Mild steel pipes 2.Dimension:1680mmx1680mmx1348mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. Twister plate of mild steel thickness 10mm. 6. Step EN8.8 shaft of 32mm used with step of 25mm. 7. Mild steel seat with thickness 2mm on frame. 8. Permanent lubricated sealed 9. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 10. Paint: Paint: Electrostatic oven cooked Powder Coated Paint.. 11. Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
၄၅	Back Extension		1. Materials: Galvanized Mild steel pipes 2. Dimension:1000mmx550mmx500mm 3. Main frame rectangle pipe 80x40mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. 5. Mild steel seat and foot cover with thickness 2mm on frame. 6. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 7. Rubber handle cover with best grip. 8. Paint: Electrostatic oven cooked Powder Coated Paint. 9. Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
၄၆	Outdoor cycle		1. Materials: Galvanized Mild steel pipes 2. Dimension:1050mmx548mmx1470mm 3. Safe Play Area: 1.5 Meter × 1 Meter 4. Main frame pipe 114mm with thickness 3.5mm. 5. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 6. Step EN8.8 shaft of 32mm used with step of 25mm. 7. Mild steel seat and foot peddle with thickness 2mm on frame. 8. Permanent lubricated sealed 9. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 10. Rubber handle cover with best grip. 11. Paint: Electrostatic oven cooked Powder Coated Paint. 12. Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.

୧୯	Double Leg press	1. Materials: Galvanized Mild steel pipe 2. Dimension:1700mmx380mmx1550mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. Bearing holder 60mm pipe with thickness 4.5mm. 5. Step EN8.8 shaft of 32mm used with step of 25mm. 6. Mild steel seat and back seat with thickness 2mm on frame. 7. Permanent lubricated sealed 8. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 9. Paint: Electrostatic oven cooked Powder Coated Paint. 10. Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
			
୨୦	Weight lifter	1. Materials: Galvanized Mild steel pipes 2. Dimension:1625mmx448mmx2515mm 3.Main frame pipe 114mm with thickness 3.5mm 4.Handle frame 32mm and other frame 48mm pipe with thickness 3.5mm. 5. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 6.Paint: Electrostatic oven cooked Powder Coated Paint. 7. Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod	No.
			
୨୧	Pull up, Dip station and leg lifter	1. Materials: Galvanized Mild steel pipe 2. Dimension:1.2mmx1mmx2100mm 3 Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm pipe with thickness 3mm. 5. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 6. Rubber handle cover with best grip. 7. Paint: Electrostatic oven cooked Powder Coated Paint. 8.Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
			
୨୨	Parallel bar workout	1. Materials: Galvanized Mild steel pipe 2. Dimension:2580mmx800mmx1600mm Main frame pipe 114mm with thickness 3.5mm. 3. Handle frame 32mm pipe with thickness 3mm. 4. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 5. Paint: Electrostatic oven cooked Powder Coated Paint.. 6. Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.
			
୨୩	Jungle gym workout	1. Materials: Galvanized Mild steel pipe 2. Dimension:8500mmx1800mmx1800mm 3. Main frame pipe 114mm with thickness 3.5mm. 4. Handle frame 32mm pipe with thickness 3mm. 5. All open ends of pipe either sealed in or closed by MS/LLDPE cap for user safety. 6. Paint: Electrostatic oven cooked Powder Coated Paint. 7. Thickness of Base plate for fixing 8 mm with 4 ribs. Foundation reinforcement: Four M16 X 480mm J bolt interconnected with each other with 6mm rod.	No.

बारुण यन्त्र जन्य सामग्रीको दररेट

सि.नं.	मालसामानको विवरण	स्पेसिफिकेशन (For S.N. 1-18: chemical change in 4 years/ cylinder change in 10 years)	एकाई
१	Fire Extinguisher Refilling (DCP Type)	2 kg capacity, monoammonium Phosphate chemical	प्रति थान
२	Fire Extinguisher Refilling (DCP Type)	4 kg capacity, monoammonium Phosphate chemical	प्रति थान
३	Fire Extinguisher Refilling (DCP Type)	5 kg capacity, monoammonium Phosphate chemical	प्रति थान
४	Fire Extinguisher Refilling (DCP Type)	6 kg capacity, monoammonium Phosphate chemical	प्रति थान
५	Fire Extinguisher Refilling (DCP Type)	9 kg capacity, monoammonium Phosphate chemical	प्रति थान
६	Fire Extinguisher Refilling (DCP Type)	25 kg capacity, monoammonium Phosphate chemical	प्रति थान
७	Fire Extinguisher Refilling (DCP Type)	50 kg capacity, monoammonium Phosphate chemical	प्रति थान
८	Fire Extinguisher Refilling (Foam Type)	9 ltr Capacity, Aluminium Sulphate and Sodium bicarbonate chemical	प्रति थान
९	Fire Extinguisher Refilling (CO2 Type)	2 kg capacity, carbondioxide chemical	प्रति थान
१०	Fire Extinguisher Refilling (CO2 Type)	4.5kg capacity, carbondioxide chemical	प्रति थान
११	Fire Extinguisher Refilling (CO2 Type)	9 kg capacity, carbondioxide chemical	प्रति थान
१२	Fire Extinguisher New Tank (DCPType)	2 kg capacity, carbondioxide chemical	प्रति थान
१३	Fire Extinguisher New Tank (DCPType)	4 kg capacity, carbondioxide chemical	प्रति थान
१४	Fire Extinguisher New Tank (DCPType)	6 kg capacity, carbondioxide chemical	प्रति थान
१५	Fire Extinguisher New Tank (DCPType)	9 kg capacity, carbondioxide chemical	प्रति थान
१६	Fire Extinguisher New Tank (DCPType)	25 kg capacity, carbondioxide chemical	प्रति थान
१७	Fire Extinguisher New Tank (DCPType)	50 kg capacity, carbondioxide chemical	प्रति थान
१८	Fire Extinguisher New Tank (Foam Type)	9 ltr	प्रति थान
१९	Fire Extinguisher New Tank (CO2 Type)	2 kg capacity, carbondioxide chemical	प्रति थान
२०	Fire Extinguisher New Tank (CO2 Type)	4 kg capacity, carbondioxide chemical	प्रति थान
२१	Fire Extinguisher New Tank (CO2 Type)	9 kg capacity, carbondioxide chemical	प्रति थान
२२	Fire Blanket	2 by 2 meter, Glass Fiber Fabric and Fire retardent film	प्रति थान
२३	Smoke Detector Sensor		प्रति थान
२४	Digital Fire Alarm control pannel		प्रति थान
२५	Fire Helmet		प्रति थान
२६	Head torch		प्रति थान
२७	Fireman Boot		प्रति थान
२८	Fireman Shuit		प्रति थान
२९	Fireman Gloves		प्रति थान
३०	Hydraulic Bolt Cutter		प्रति थान

सम्पदा सम्बन्धी सामग्रीहरु

सि.नं.	Description	Specifications	Unit
१	Stone sprout (Hiti Manga) : Constructions and fitting off carved hiti manga in black/grey stone (5' length, 9" breadth and 9" height) all complete		no.
२	Constructions and fitting of carved Hiti Manga of 4' length and section size less than 9" as per instruction of site engineer.		no.
३	ढुंगाको मूर्ति (९",१६")		no.
४	Supplying and fixing precast brick butta carved butta works in fence column (10"*2'-6") in perfect plumb lines and level including raking the joints and cleaning the surface all complete as per design and drawings.		no.
५	Supplying and fixing brick butta carved butta works in gate column (1'-7"*4'-5") in perfect plumb lines and level including raking the joints and cleaning the surface all complete as per design and drawings.		no.
६	पोखरीमा प्रयोग गर्ने गठचा माटो		प्रती ब्यू.मि.

Medical General Equipment

SN	Items	Specification	Unit
----	-------	---------------	------

1	Pulse Oximeter	SpO2 detection includes the range: 70 - 100% Data display update rate: every 1s Operated by rechargeable battery power supply.	Pcs
2	Sphygmamometer (BP apparatus)	Composed of a cuff containing an inflatable bag.Length tube between: 50 to 70 cm.Gauge graduated 0 - 300mmHg (min) in 2 (max) mmHg increments, with pressure release valve. Accuracy as per ISO 81060-1: +/- 3mm Hg.Latex and mercury free design.	Pcs
3	Stethoscope	Tube diameter: outer diameter 10mm, inner diameter 4.8mm. Tube length 560mm.Sensitivity from 3.2dB to 26dB in a range from 50 to 1000Hz for cardiology.Sensitivity 8.1dB in a range from 600 Hz to 1,500Hz for pneumology .Arms: brass-steel with a flexible spring. Removable plastic eartieces. Latex-free.	Pcs
4	Examination Table(Fixed Height)	Examination label, two sections extended, including upholstery: (185-190) x 55 x 80cm (lxwx h). Frame: 3 cm (outside, across), 1.35-1.5 mm thickness. Upholstery: 4.5-5 cm (h). Carrying capacity: minimum 160 kg. Knockdown construction: yes.	Pcs
5	Otoscope Set	Handle with a built-in LED light source in a mounted head. Including rotatable viewing lens with a magnification between 3 times. Colour temperature: Cool white in the range 3,200-4,000K. Including reusable, autoclavable specula. Specula are cleanable with alcohol wipes Handle contains on/off switch. Includes a port to connect an insufflation bulb. Uses 2 x type AA Alkaline batteries as a power source.	Pcs
6	Dressing Trolley	Overall: (81-90) x (50-55) x (90 -100) cm (l*w*h) Frame: 2.7-3.3 cm (outside, across), 1.5 mm thickness Thickness shelves: 1.35-1.5mm Swivel castor wheel: 3 x 10 cm (w*diameter) Carrying capacity: 100 kg	Pcs
7	Scale with Height Measuring (Digital)	high 300 kg capacity. built in height rod 61 cm-250 cm with 1cm increments. large easy to read LCD display. AC/DC adaptor and battery operation. battery life up to 100hrs continuous use. BMI function. step-on activation. large and ultra-low profile platform.	Pcs
8	Nebulizer	For compressor model: air flow at least 5 L/min. Minimum drug nebulisation flow greater than: 0.2 ml/min. Integrated drug reservoir with a minimum capacity: 6 ml.	Pcs
9	Artery Forcep	• Straight Artery forceps • Made up of stainless steel • Approx. 160 cm	Pcs
10	Cheatele forcep with Jar	• Cheatele forceps 10 Inch With Cheatele Jar • Made up of stainless steel.	Pcs
11	Digital Thermometer	• Power Source: Battery • With LCD Display • Temperature in °C and °F • Should come with Safety Case, • Automatic shut-off, • Auto Shut OFF	Pcs
12	Disposable wooden tongue depressor	• Made up of wood with smooth texture • Tasteless and order less • Should come in pack of 100 pcs	Pcs
13	Duck Speculum	• Made up of stainless steel • Size: 80*32mm, 90*37mm and 115*37mm	Pcs

14	Examination Lamp	• Height approx.: 100cm with approx.. 75cm articulating arm. • Operating voltage: 220V-240V • Light Source: LED or incandescent bulb	Pcs
15	Fetoscope	• Made up of stainless steel or aluminium • Diameter 2 cm and length 30 cm	Pcs
16	Flash light/Torch Light	• LED light • AA battery operated • Approx. 10 cm length	Pcs
17	Footstep	• Double step • Made up of mild steel/ SS	Pcs
18	Gauze Drum	• Stainless steel drum • Approx size: 5"*12"	Pcs
19	Kidney Tray	• Set of 4 stainless steel kidney tray • Size 6", 8", 10" and 12"	Pcs
20	Knee Jerk hammer	• Should come with triangular rubber head and flat stainless-steel handle • Size: approx. 12"	Pcs
21	Mackintosh Sheet	• Made of High Quality Natural Rubber • Soft & High quality Breaking & Tearing Strength • Size: Approx. 36"*84"	Pcs
22	Pillow With Cover	• Waterproof pillow with cover • Approx. size: 16"*22"	Pcs
23	Protoscope	• Made up of stainless steel • Size: Medium	Pcs
24	Scissors	• Made up of Stainless steel • Size: 8" and 12"	Pcs
25	Screen	• Movable 3 fold folding screen • Size: approx. 8'*5' • Frame made of Stainless steel or high strength mild steel	Pcs
26	Snellen's chart	• SNELLEN eye chart for visual acuity and vision test. • Size: Approx. 23 x 35.5 cm	Pcs
27	Speculam	• Made up of stainless steel material • Size: Medium	Pcs
28	Tooth forcep	Stainless Still 8"	Pcs
29	Artery forcep	Stainless Still 8"	Pcs
30	Sponge holding forceps	Stainless Still 8"	Pcs
31	Artery forceps, curved.	Stainless Still 6"	Pcs
32	Needle holder-	Stainless Still 6"	Pcs
33	Suture cutting scissor	Stainless Still 6"	Pcs
34	Stop watch /Timer	• Timer with LCD display	Pcs
35	Surgical drum	• Stainless steel drum • Approx size: 15"*12"	Pcs
36	Tape to measure fundal height	• 100 cm long	Pcs
37	Tray with cover	• Stainless steel tray of approx. 20*25*2 CM	Pcs
38	Tuning fork	• 256 Hz for for medical and hearing testing	Pcs
39	Eye Towel	36"x36" with opening at center about 3" diameter	Pcs
40	Wrapper	36*36	Pcs

41	Yoga Mat Deluxe	2*6 fit(Non-slip on both sides to enhance user safety. Comfortable cushioning without excessive compression. Resistant to cracking, peeling, and deformation during normal use. Uniform thickness and smooth finish throughout the mat. Manufactured from durable, skin-friendly, and eco-friendly materials)	Pcs
42	Yoga Mat Simple	2*6 fit(Non-slip on both sides to enhance user safety. Comfortable cushioning without excessive compression. Resistant to cracking, peeling, and deformation during normal use. Uniform thickness and smooth finish throughout the mat. Manufactured from durable, skin-friendly, and eco-friendly materials.)	Pcs
43	USG Jel	5 ltr	Jar
44	Medical Masking Tape	2*5 meter	Roll
45	Colour Coded Dust Bin with Cover	50 Ltr(Tight-fitting lid Color-coded waste bag (matching bin color) Waste identification label Biohazard symbol (for infectious waste bins) User instruction label (optional)	Pcs
46	Colour Coded Dust Bin with Cover	30 Ltr(Tight-fitting lid Color-coded waste bag (matching bin color) Waste identification label Biohazard symbol (for infectious waste bins) User instruction label (optional)	Pcs
47	Colour Coded Dust Bin with Cover	20 Ltr(Tight-fitting lid Color-coded waste bag (matching bin color) Waste identification label Biohazard symbol (for infectious waste bins) User instruction label (optional)	Pcs
48	Transparency Sheet	A4 Size Plastic Paper	Pcs
49	Medical Bed Sheet	1 Mtr* 2 Mtr	Pcs
50	Baltn with Cover	20 Ltr	Pcs
51	Baltn with Cover	10Ltr	Pcs
52	Mattress	Mtr	Pcs
53	Aprone	Pcs	Pcs
54	Autoclave Rod	Compatible with Autoclave(20Ltr)	Pcs
55	Autoclave Rod	Compatible with Autoclave(30Ltr)	Pcs
56	Autoclave Rod	Compatible with Autoclave(50Ltr)	Pcs
57	Autoclave Rod	Compatible with Autoclave(80Ltr)	Pcs
58	Surgical Mask	Three layer latex free medical surgical mask BFE 98.0% PFE 99.3%	Pcs
59	Improved Neubauer Counting Chamber	Thick glass plate with size of a glass slide(30*70*4mm), grid design: 9mm2, chamber depth: 0.1mm	Pcs
60	Cover slip for microscopy	Microscope cover glass, square, size 22mm*22mm 20/pack One box	Box
61	Glass slides	Plain, flat, corrosion-resistant, untreated surface glass slide (borosilicate or soda-lime), Ground edges, 75X25 mm, 1mm thickness with shatter-proof (cardboard with paper or foam ing),1*50/Pcs pack	pkt
62	Pipette Tips (5-200 ul)	Plastic,1000Pcs/Pkt	pkt
63	Pipette Tips (100-1000 ul)	Plastic, 500 Pcs/Pkt	pkt
64	Tourniquet	Rubber tube	Pcs
65	Urine and stool containers	Sturdy polypropylene container with spill-proof screw cap and label, individually ed, capacity 30-50 ml (preferably transparent and with graduations)	Pcs
66	Bamboo stick	Length 6 cm 100/Pkt (ISO/ CE/USFDA approved)	Pkt
67	Sodium hypochloride	4 or 10%, W/V, liquid	Ltr
68	SGOT Reagent	400ML/KIT (ISO, CE/USFDA approved)	Kit
69	SGPT Reagent	400ML/KIT (ISO, CE/USFDA approved)	Kit
70	Alkaline Phosphate Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
71	Glucose Test Reagent	1000ML/KIT (ISO, CE/USFDA approved)	Kit
72	Uristic	Three parameters (Glucose, protein, pH) on a strip with color chart for reference to visual reading, 100 Strips/Package	Bottle
73	RA Factor Test Kit	Qualitative, latex, 100 Tests (ISO, CE/USFDA approved)	Kit
74	cholesterol Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
75	Triglyceride Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
76	HDL Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
77	ESR Tube	Wintrobe's Tube, graduated	Pcs
78	Dropper	5 ml capacity (ISO, CE/USFDA approved)	Pcs

79	EDTA Vacutainer	1.Intended use of haematological test. 2.Anti coagulant: EDTA K2 3.Capacity 3ml, certified 4. size: 100 tubes/ et 5.Should be ISO, FDA or CE certified 6.Should be color coded on top and sterile 7.Tube should not release any kind of materials while sample is on process 8.Leak proof 9.Should be compatible with vacuum blood collection	Pcs
80	Tube Brush	Plastic Brush with Metal Handle (squirrel brush)	Pcs
81	Uric Acid Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
82	Urea Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
83	Creatinine Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
84	CRP Reagent	Qualitative, latex, 100 Tests/Box (ISO, CE/USFDA approved)	Kit
85	ESR Needle	(ISO, CE/USFDA approved)	Pic
86	1 MI Syringe	(ISO, CE/USFDA approved)	Pcs
87	Mantoux Reagent	Tuberculin PPD/ 5 ml	Bottle
88	Platelet Reagent	platelet diluting fluid (1% ammonium oxalate), 100 ml, ready to use	Bottle
89	Antimicrobial Soap Liquid	"Suitable for sensitive and all skin type.provide protection from a range of germs, free standing with pump dispenser, Volume: /Ltr	Ltr
90	Handiplast	Round Tape/100 Pcs Pkt	Box
91	Scrub Gown	M/L Size	Set
92	Lab Apron	M/L Size	pcs
93	Sample Tray	sturdy, non leaky, stainless steel surace	Pcs
94	Dengue Combi Rapid test	Cartridge, immunochromatographic based kit with qualitative detection of NS1 antigen, and IgG and IgM antibodies separately with inbuilt control. Individually packed, long expiry. Sufficient amount of buffer and sample dropper to be included for each kit. CE IVD/USFDA/ (10tests/kit)	Box
95	Glass test tube	Borosilicate glass, Round bottomed, flat top, 8-10mm diameter, 75 mm.100 tube box	Box
96	Lens Paper	Lintless & Non-Abrasive Material. 100 sheet pad	Pad
97	Sharps safety container	1.Made of heavy puncture-proof rigid cardboard material with one piece aperture handle and marked level for maximum fill. 2.Volume: 5 litres 3.Intended use: safely and efficiently contain, transport and store used sharps injection devices until final destruction, safe disposal or recycling. 4.Clear label indicating it's a safety used for syringes, needles and sharps with yellow in color. 5.Bio-hazard sign clearly and cons uously displayed on all the faces. 6.Step by step numerical directions for assembling.10/pic Box	Box
98	Test tubes	Glass, Autoclavable Test Tube, Rimless, Clear, transparent, Size: 100mm x 12mm diameter.	
99	Measuring Cylinder	Polypropylene, 50ml	Pic
100	Wright stain	Should contain wright stain powder and solvent separately in pack.(250 ml/bottle)	Bottle
101	Immersion Oil	Liquid state, cedar wood immersion oil.100ml/bottle	Bottle
102	Occult Blood Kit	Gum-Guaiac based kit with applicator, developer solution and test card. (50 test/pkt)	Pkt
103	Helicobacter pylori Antigen	Cartridge, immunochromatographic based with qualitative detection of antigen to Helicobacter pylori and inbuilt control. Individually packed, long expiry. Sufficient amount of bufferand sample dropper to be included for each kit. CE IVD/ USFDA/ (25 tests/kit)	Test
104	Plastic Garbage Bag	50 KG Capacity	Pcs
105	Detergent	1000 Gm	Pocket
106	Loose Gloves	Par Box 100 Pcs	Box
107	Surgical Gloves	Sterile in different size	Pair
108	Enzymetic Cleaner	Pack (1Ltr)	Pak
109	Enzymetic Cleaner Concentrate	Pack (50ML)	Pak
110	Lyse Reagent	Pack (1Ltr)	Pak
111	Diluent Solution	Pack (20 Ltr)	Pak
112	USG Paper	Thermal Paper 110mm*20M	Roll
113	ECG Paper	80mm*20m	Roll
114	Macintosh	Rubber	Meter
115	Test Tube Rack	24/holes Steels	Pcs
116	Test Tube Rack	24/Holes Plastic	Pcs
117	Vacutainer (Clot Activator)	3ml	Pcs
118	EDTA Vail	3ml	Pcs
119	Gel Clot Vial	3ml	
120	Sodium Fluoride Vial	3ml	Pcs
121	Tips Stand Rack	(10-100UL)	Pcs
122	Tips Stand Rack	(100-1000UL)	Pcs
123	Micropipette	10-100UL Variable	Pcs
124	Micropipette	100-1000UL Variable	Pcs
125	Micropipette	1000 IU Fixed	Pcs
126	Test tube Brush	Medium	Pcs
127	Micropore Tape	5 Meter	Pcs
128	Glucometer Strips	Strips	Pcs
129	Hemoglobin Strips	Strips	Pcs
130	Rotator	vide gentle and continuous mixing of blood samples, reagents, and test s	Pcs
131	VDRL shekor	or performing VDRL (Venereal Disease Research Laboratory) tests by en	Pcs

132	Blood grouping tile	tile with multiple wells used for ABO and Rh blood grouping by observation	Pcs
133	Ependorf tube 0.5 ml	(500pcs /pack)	Pcs
134	Ependorf tube 1.5 ml	(500pcs /pack)	Pcs
135	Ependorf tube 2 ml	(500pcs /pack)	Pcs
136	Graduated Nuclease Tube free with cap	1.5ML 1000 pcs/box	Pcs
137	lamp of semi-automatic biochemistry analyzer	Lamp Type-Tungsten Halogen Lamp / Quartz Halogen Lamp, Rated Voltage-6 V or 12 V (as required by analyzer model)	Pcs
138	Table lamp	Adjustable LED laboratory lamp providing bright, shadow-free illumination for sample examination and bench work.	Pcs
139	Timer	Digital laboratory timer with accurate countdown and alarm functions for monitoring test and incubation times.	Pcs
140	Sample aspiration probe	Precision sampling probe designed for accurate aspiration and transfer of liquid specimens in automated laboratory analyzers.	Pcs
141	Roller	Laboratory tube roller providing gentle, continuous rolling motion for uniform mixing of blood samples, reagents, and other liquid specimens.	Pcs
142	Quality control for hematology test	5 ML (Ready-to-use three-level hematology control (Low, Normal, High). Compatible with the existing hematology analyzer model. Covers all routine hematology parameters reported by the analyzer. Supplied with lot-specific target values, SD, and acceptable ranges).	Pcs
143	Quality Control Sera Pathogenic	5ml (Human serum-based pathological (abnormal) quality control serum. Assigned abnormal target values for routine chemistry analytes. Compatible with the laboratory's biochemistry analyzer and reagent system).	Pcs
144	Quality Control Sera Normal	Human serum-based quality control material, Normal (Level 1) control with assigned values for all listed analytes. Compatible with the laboratory's biochemistry analyzer and reagent system.	pcs
145	Distil Water	Laboratory Grade, Clear, Colorless, Free from Suspended Matter ,Shelf Life Typically 12–24, Ph-5.0-7.0	Ltr
146	X-Ray Film	High-quality radiographic film designed to produce clear, high-resolution diagnostic images with excellent contrast for use in medical X-ray imaging systems. Dry Films size , 10 *12 (100pcs/pkt)	PKT
147	X-Ray Film	High-quality radiographic film designed to produce clear, high-resolution diagnostic images with excellent contrast for use in medical X-ray imaging systems. Dry Films size , 8 *10 (100pcs/pkt)	Kit
148	Daily Rines Kit	for routine daily laboratory testing and quality analysis, ensuring accurate results	Set
149	Fluid Pack	pack used for automated laboratory analyzers to support routine testing	Set
150	Mission Control	used to verify analyzer performance, monitor accuracy, and ensure reliable results	Kit
151	Troubleshooting Kit	igned to identify, resolve, and verify analyzer or reagent-related issues during operation	Pkt
152	Acupuncture needle	Sterile, single-use stainless steel needle for acupuncture treatment, available in various lengths and gauges.	Pkt
153	acupuncture tapping needles	um blossom/dermal hammer) used for superficial skin stimulation and treatment	Than
154	Acupuncture stimulator machine	Adjustable electrical pulses through acupuncture needles for enhanced pain relief	Than
155	BCM blood circulatory machine	blood circulation, reduce muscle stiffness, and promote recovery through electrical stimulation	Set
156	Cupping set	with manual or vacuum pump for cupping therapy to relieve muscle tension	Set
157	Acupuncture wall charts & dolls	ts and meridian dolls illustrating acupuncture points and channels for teaching	Than
158	Acp vibrator machine	ration device used to stimulate acupuncture points, relieve muscle pain, and improve circulation	Set
159	Infra red lamp for heating purpose	eat lamp providing deep tissue warmth to reduce pain, improve circulation, and promote healing	Than
160	Round acupuncture tray	ey with round trays for organizing and transporting acupuncture instruments	Pkt
161	Pure moxa , impure moxa , stick moxa	from mugwort, available in loose, processed, and stick forms for heat therapy	piece
162	Perilight	on light providing bright, focused illumination for medical examinations	piece
163	condom box	le male condoms for contraception and prevention of sexually transmitted infections	piece
164	Fetal Doppler	Portable handheld ultrasound device used to detect and monitor fetal heart rate during pregnancy.	piece
165	Duck's speculum	Reusable or disposable vaginal speculum used for gynecological examinations and cervical procedures.	tab
166	xylocain 1%	tic solution used to provide temporary pain relief during minor surgical procedures	piece
167	surgical blade 11 no.	pointed surgical blade designed for precise incisions, punctures, and drainage	piece
168	Disposable syringe 20 ml	ase 20 mL syringe for accurate administration or withdrawal of fluids and medications	PCS
169	Dumbell	Ergonomic grip, durable cast iron construction with protective coating for resistance exercises. 1 kg	PCS
170	Dumbell	Ergonomic grip, durable cast iron construction with protective coating for resistance exercises. 2 kg	PCS
171	Dumbell	Ergonomic grip, durable cast iron construction with protective coating for resistance exercises. 3 kg	PCS
172	Weight Cuff	Soft padded design for comfort during resistance training and mobility exercises. 1 kg	PCS
173	Weight Cuff	Soft padded design for comfort during resistance training and mobility exercises. 2 kg	PCS
174	Weight Cuff	Soft padded design for comfort during resistance training and mobility exercises. 3 kg	PCS
175	Foot Roller	Textured roller designed to massage the plantar fascia, reduce foot pain, and improve circulation.	PCS
176	Flex Bar	Flexible resistance bar for grip strengthening, forearm rehabilitation, and shoulder exercises. Available in different resistance levels.	PCS
177	Physio Wand	Lightweight exercise stick for shoulder mobility, stretching, posture correction, and range-of-motion exercises.	PCS
178	Gel Fist Ball	Soft gel-filled hand exercise ball for grip strengthening, stress relief, and finger rehabilitation.	PCS

179	Vibration Gun	Handheld percussion massager with multiple speed settings and interchangeable massage heads for muscle recovery and pain relief.	PCS
180	Foam Roller	High-density EVA foam roller for self-myofascial release, muscle relaxation, flexibility, and balance training.	PCS
181	Stress Ball	Soft, squeezable therapeutic ball designed to improve hand strength, finger dexterity, grip function, and stress relief during rehabilitation exercises.	PCS
182	Crayon Set	Non-toxic, assorted color crayons used for drawing, coloring, and developing fine motor skills and hand-eye coordination in therapy and educational activities.	pcs
183	Surgical Blade	Sterile, Disposable, Carbon Steel, Sizes No. 10, 11, 15, 20–24	pcs
184	Scalpel Handle	Stainless Steel, No. 3 & No. 4	pcs
185	Mayo Scissors	Straight/Curved, Stainless Steel, 14–17 cm	pcs
186	Metzenbaum Scissors	Curved, Stainless Steel, 18 cm	pcs
187	Dressing Scissors	Stainless Steel, 14–16 cm	pcs
188	Artery Forceps	Straight & Curved, Stainless Steel, 12.5–16 cm	pcs
189	Mosquito Forceps	Straight/Curved, Stainless Steel, 12.5 cm	pcs
190	Tissue Forceps	Toothed (1x2 Teeth), Stainless Steel, 15 cm	pcs
191	Dressing Forceps	Plain, Stainless Steel, 15–18 cm	pcs
192	Needle Holder	Mayo-Hegar, Stainless Steel, 16–18 cm	pcs
193	Sponge Holding Forceps	Stainless Steel, 24 cm	pcs
194	Backhaus Towel Clip	Stainless Steel, 9–13 cm	pcs
195	Allis Tissue Forceps	Stainless Steel, 15 cm	pcs
196	Babcock Forceps	Stainless Steel, 16–20 cm	pcs
197	Kocher Forceps	Straight/Curved, Stainless Steel, 16 cm	pcs
198	Retractor	Langenbeck, Stainless Steel, Double-ended	pcs
199	Skin Stapler	Sterile, Disposable, 35 Staples	pcs
200	Staple Remover	Sterile, Disposable	pcs
201	Suture Materials	Absorbable & Non-absorbable, USP 2-0 to 5-0	pcs
202	Hypodermic Needle	Sterile, Disposable, 18G–26G	pcs
203	Sterile Gloves	Latex/Nitrile, Sizes 6.5–8.5	pcs
204	Surgical Gown	Sterile, Disposable, SMS Fabric	pcs
205	Surgical Drapes	Sterile, Disposable, Fenestrated/Plain	pcs
206	Gauze Swab	Sterile, 8-Ply, 10 × 10 cm	pcs
207	Cotton Roll	Absorbent, Medical Grade	pcs
208	Crepe Bandage	Cotton, 5 cm, 10 cm, 15 cm	pcs
209	Adhesive Tape	Microporous, 1–3 Inch Width	pcs
210	Kidney Tray	Stainless Steel, 8–10 Inch	pcs
211	Instrument Tray	Stainless Steel, Various Sizes	pcs
212	Gallipot	Stainless Steel, 150–250 mL	pcs
213	Dressing Drum	Stainless Steel, 9–12 Inch	pcs
214	Sterilization Indicator Tape	Steam Autoclave Compatible	pcs
215	Autoclave Pouch	Self-Sealing, Various Sizes	pcs
216	Suction Catheter	Sterile, FG 8–16	pcs
217	Disposable Suction Tubing	Medical Grade PVC	pcs
218	Roller Bandage (Cotton)	5 cm × 4 m(100% Cotton, Non-sterile, Soft, Highly Absorbent)	pcs
219	Roller Bandage (Cotton)	7.5 cm × 4 m(100% Cotton, Non-sterile, Soft, Highly Absorbent)	pcs
220	Roller Bandage (Cotton)	10 cm × 4 m(100% Cotton, Non-sterile, Soft, Highly Absorbent)	pcs
221	Roller Bandage (Cotton)	15 cm × 4 m(100% Cotton, Non-sterile, Soft, Highly Absorbent)	pcs
222	Crepe Bandage	5 cm × 4 m (Stretched)(Cotton/Spandex Blend, Elastic, Washable, Reusable)	pcs
223	Crepe Bandage	7.5 cm × 4 m (High Elasticity, Skin Friendly)	pcs
224	Crepe Bandage	10 cm × 4 m (Stretched)(Compression Support, Breathable)	pcs
225	Crepe Bandage	15 cm × 4 m (Stretched)(Heavy Compression, Reusable)	pcs
226	Elastic Adhesive Bandage (EAB)	5 cm × 4.5 m(Cotton Fabric with Zinc Oxide Adhesive)	pcs
227	Elastic Adhesive Bandage (EAB)	7.5 cm × 4.5 m(Strong Adhesion, Flexible)	pcs
228	Triangular Bandage	90 × 90 × 127 cm(100% Cotton, Non-sterile, Reusable)	pcs
229	Dental Probe	Double-ended Explorer/Probe, Stainless Steel (AISI 420), Autoclavable, Corrosion Resistant.	pcs
230	Pedo Extraction Forcep	Pediatric Extraction Forceps, Stainless Steel (AISI 420), Autoclavable, Ergonomic Handle.	pcs
231	Suitcase with Wheel	Hard ABS/Polycarbonate Case, Four Wheels, Telescopic Handle, Lockable, Suitable for Carrying Dental Instruments.	pcs
232	Tweezer	College Tweezers, Stainless Steel, Serrated Tips, 15–16 cm, Autoclavable.	pcs
233	Straight Elevator	Medium Size, Stainless Steel (AISI 420), Ergonomic Handle, Autoclavable.	pcs
234	Dental Airtor	High-Speed Handpiece, Push Button Chuck, Standard 4-Hole Connection, Ceramic Bearings, Autoclavable up to 135°C.	pcs
235	Torch Light	Rechargeable LED Torch, Minimum 300 Lumens, Aluminum Body, Battery & Charger Included.	pcs
236	Ball Burnisher	Double-Ended Dental Ball Burnisher, Stainless Steel, Autoclavable.	pcs

237	Periosteal Elevator	Stainless Steel, Double-Ended, Ergonomic Handle, Autoclavable.	pcs
238	Dental Mirror	Front Surface Mirror No. 4 or No. 5, Stainless Steel Handle, Autoclavable.	pcs
239	Head Cap	Disposable Bouffant Cap, Non-Woven Polypropylene, Free Size, Latex-Free.	pcs
240	Articulating Paper	Horseshoe/Strip Type, 40–100 Microns, Double-Sided (Red/Blue), Waterproof.	pcs
241	Cotton Roll (Dental)	100% Medical Grade Cotton, Highly Absorbent, Size No. 2, Non-Sterile, Pack of 500 Rolls.	pcs
242	Suction Tips	Disposable Saliva Ejector Tips, Medical Grade PVC, Non-Toxic, Individually Packed or Bulk Pack.	pcs
243	Plastic Tray	Dental Instrument Tray, Medical Grade Plastic, Approx. 28 × 18 × 2 cm, Autoclavable/Chemical Resistant.	pcs
244	Round Bur (Medium)	Tungsten Carbide or Diamond Round Bur, Medium Size, FG Shank (1.6 mm), Sterile/Autoclavable.	pcs
245	Round Bur (Small)	Tungsten Carbide or Diamond Round Bur, Small Size, FG Shank (1.6 mm), Sterile/Autoclavable.	pcs
246	Plastic Strips	Polyester Finishing & Polishing Strips, Medium/Fine Grit, Assorted Sizes.	pcs
247	Xylocaine Spray	Lidocaine 10% Topical Spray, 50 mL Pump Spray, Medical Grade.	pcs
248	Disposable Glass Roll	Disposable Mixing Pad/Glass Roll, Medical Grade, Single Use.	pcs
249	Glass Ionomer Cement	Restorative Type II, Radiopaque, Tooth-Coloured, Powder & Liquid Kit, High Compressive Strength, ISO 9917 Compliant.	pcs
250	Cidex (Glutaraldehyde)	2% Activated Glutaraldehyde Solution, 5 L Container, High-Level Instrument Disinfectant, Effective for 14 Days After Activation.	pcs
251	Lignocaine 2% with Adrenaline Jelly	Lidocaine Hydrochloride 2% with Adrenaline 1:200,000, 30 mL Tube/Vial, Sterile, For Dental Use.	pcs
252	IV Cannula	Sterile, Disposable, PTFE/FEP Catheter, Sizes 14G, 16G, 18G, 20G, 22G, 24G, Injection Port, Color Coded.	pcs
253	IV Infusion Set	Sterile, Disposable, DEHP-Free PVC, 20 Drops/mL, 150 cm Tubing, Roller Clamp, Latex-Free Injection Port, Luer Lock, EO Sterilized.	pcs
254	Urine Collection Bag (Urobag)	Sterile, Disposable, Capacity 2000 mL, Medical Grade PVC, Non-Return Valve, 90–120 cm Kink-Resistant Tubing, Universal Connector, Bottom Drain Valve (T-Valve/Cross Valve), Graduated Scale, Bed Hanger, EO Sterilized.	pcs
255	Foley Urinary Catheter (2-Way)	Sterile, Disposable, Latex Silicone-Coated or 100% Silicone, 2-Way, Balloon Capacity 5–10 mL (6–10 Fr) & 30 mL (12–24 Fr), Sizes: 8, 10, 12, 14, 16, 18, 20, 22, 24 Fr, Color Coded, EO Sterilized.	pcs
256	Garbage Bag (Black)	HDPE/LDPE, 30–50 Microns, Leak-Proof, Size: 19" × 21" (Small), Capacity: 15–20 L.	pcs
257	Garbage Bag (Black)	HDPE/LDPE, 40–60 Microns, Leak-Proof, Size: 24" × 32" (Medium), Capacity: 35–50 L.	pcs
258	Garbage Bag (Black)	HDPE/LDPE, 50–80 Microns, Heavy Duty, Size: 30" × 40" (Large), Capacity: 70–80 L.	pcs
259	Garbage Bag (Black)	HDPE/LDPE, 60–100 Microns, Heavy Duty, Size: 36" × 48", Capacity: 100–120 L.	pcs
260	Garbage Bag (Yellow)	HDPE/LDPE, 50 Microns or as per Biomedical Waste Rules, Leak-Proof, Autoclavable/Incinerable, Various Sizes.	pcs
261	Garbage Bag (Red)	HDPE/LDPE, 50 Microns or as per Biomedical Waste Rules, For Contaminated Plastic Waste, Leak-Proof.	pcs
262	Garbage Bag (Blue)	HDPE/LDPE, 50 Microns, For Glassware and Metallic Implants, Leak-Proof.	pcs
263	Garbage Bag (White/Translucent)	High-Strength Plastic, Puncture Resistant, For Sharps Container Lining (where applicable).	pcs
264	Garbage Bag (Green)	HDPE/LDPE, 40–50 Microns, For Biodegradable/General Organic Waste, Leak-Proof.	pcs
265	MUAC Tape	WHO/UNICEF-compatible MUAC tape for children 6–59 months, Non-stretch, waterproof, durable plastic construction, Measurement scale in millimetres with 1 mm graduations.	pcs
266	Zip Lock	Transparent Low-Density Polyethylene (LDPE) or Polyethylene (PE), food/laboratory grade, Leak-resistant, airtight zip-lock seal, Minimum 50-micron thickness.	pcs

Lab Equipment And Reagent

सि.नं.	Description of Goods	Specification	Unit
१	Improved Neubauer Counting Chamber	Thick glass plate with size of a glass slide (30*70*4mm), grid design: 9mm ² , chamber depth: 0.1mm	Pcs
२	Cover slip for microscopy	Microscope cover glass, square, size 22mm*22mm 20/pack One box	Box
३	Glass slides	Plain, flat, corrosion-resistant, untreated surface glass slide (borosilicate or soda-lime), Ground edges, 75X25 mm, 1mm thickness with shatter-proof (cardboard with paper or foam ing), 1*50/Pcs pack	pkt
४	Pipette Tips (5-200 ul)	Plastic, 1000Pcs/Pkt	pkt
५	Pipette Tips (100-1000 ul)	Plastic, 500 Pcs/Pkt	pkt
६	Tourniquet	Rubber tube	Pcs
७	Urine and stool containers	Sturdy polypropylene container with spill-proof screw cap and label, individually ed, capacity 30-50 ml (preferably transparent and with graduations)	Pcs

୯	Bamboo stick	Length 6 cm 100/Pkt (ISO/ CE/USFDA approved)	Pkt
୧୦	Sodium hypochloride	4 or 10%, W/V, liquid	Ltr
୧୧	SGOT Reagent	400ML/KIT (ISO, CE/USFDA approved)	Kit
୧୨	SGPT Reagent	400ML/KIT (ISO, CE/USFDA approved)	Kit
୧୩	Alkaline Phosphate Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
୧୪	Glucose Test Reagent	1000ML/KIT (ISO, CE/USFDA approved)	Kit
୧୫	Uristix	Three parameters (Glucose, protein, pH) on a strip with color chart for reference to visual reading, 100 Strips/Package	Bottle
୧୬	RA Factor Test Kit	Qualitative, latex, 100 Tests (ISO, CE/USFDA approved)	Kit
୧୭	cholesterol Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
୧୮	Triglyceride Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
୧୯	HDL Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
୨୦	ESR Tube	Wintrobe's Tube, graduated	Pcs
୨୧	Dropper	5 ml capacity (ISO, CE/USFDA approved)	Pcs
୨୨	EDTA Vaccutainer	1.Intended use of haematological test. 2.Anti coagulant: EDTA K2 3.Capacity 3ml, certified 4. size: 100 tubes/ et 5.Should be ISO, FDA or CE certified 6.Should be color coded on top and sterile 7.Tube should not release any kind of materials while sample is on process 8.Leak proof 9.Should be compatible with vaccum blood collection	Pcs
୨୩	Tube Brush	Plastic Brush with Metal Handle (squirrel brush)	Pcs
୨୪	Uric Acid Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
୨୫	Urea Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
୨୬	Creatinine Reagent	100ML/KIT (ISO, CE/USFDA approved)	Kit
୨୭	CRP Reagent	Qualitative, latex, 100 Tests/Box (ISO, CE/USFDA approved)	Kit
୨୮	ESR Needle	(ISO, CE/USFDA approved)	Pic
୨୯	1 Ml Syringe	(ISO, CE/USFDA approved)	Pcs
୩୦	Mantoux Reagent	Tuberculin PPD/ 5 ml	Bottle
୩୧	Platelet Reagent	platelet diluting fluid (1% ammonium oxalate), 100 ml, ready to use	Bottle
୩୨	Antimicrobial Soap Liquid	"Suitable for sensitive and all skin type,provide protection from a range of germs, free standing with pump dispenser, Volume: /Ltr	Ltr
୩୩	Handiplast	Round Tape/100 Pcs Pkt	Box
୩୪	Scrub Gown	M/L Size	Set
୩୫	Lab Apron	M/L Size	pcs
୩୬	Sample Tray	sturdy, non leaky, stainless steel surace	Pcs
୩୭	Dengue Combi Rapid test	Cartridge, immunochromatographic based kit with qualitative detection of NS1 antigen, and IgG and IgM antibodies separately with inbuilt control. Individually packed, long expiry. Sufficient amount of buffer and sample dropper to be included for each kit. CE IVD/USFDA/ (10tests/kit)	Box
୩୮	Glass test tube	Borosilicate glass, Round bottomed, flat top, 8-10mm diameter, 75 mm.100 tube box	Box
୩୯	Lens Paper	Lintless & Non-Abrasive Material. 100 sheet pad	Pad
୪୦	Sharps safety container	1.Made of heavy puncture-proof rigid cardboard material with one piece aperture handle and marked level for maximum fill. 2.Volume: 5 litres 3.Intended use: safely and efficiently contain, transport and store used sharps injection devices until final destruction, safe disposal or recycling. 4.Clear label indicating it's a safety used for syringes, needles and sharps with yellow in color. 5.Bio-hazard sign clearly and cons uously displayed on all the faces. 6.Step by step numerical directions for assembling.10/pic Box	Box
୪୧	Test tubes	Glass, Autoclavable Test Tube, Rimless, Clear, transparent, Size: 100mm x 12mm diameter.	
୪୨	Measuring Cylinder	Polypropylene, 50ml	Pic
୪୩	Wright stain	Should contain wright stain powder and solvent separately in pack.(250 ml/bottle)	Bottle
୪୪	Immersion Oil	Liquid state, cedar wood immersion oil.100ml/bottle	Bottle
୪୫	Occult Blood Kit	Gum-Guaiac based kit with applicator, developer solution and test card. (50 test/pkt)	Pkt

૪૪	Helicobacter pylori Antigen	Cartridge, immunochromatographic based with qualitative detection of antigen to Helicobacter pylori and inbuilt control. Individually packed, long expiry. Sufficient amount of buffer and sample dropper to be included for each kit. CE IVD/ USFDA/ (25 tests/kit)	Test
૪૬	Plastic Garbage Bag	50 KG Capacity	Pcs
૪૭	Detergent	1000 Gm	Pocket
૪૮	Loose Gloves	Par Box 100 Pcs	Pocket
૪૯	Surgical Gloves	Per Packet 50 Pair	Pocket
૫૦	Enzymetic Cleaner	Pack (1Ltr)	Pak
૫૧	Enzymetic Cleaner Concentrate	Pack (50ML)	Pak
૫૨	Lyse Reagent	Pack (1Ltr)	Pak
૫૩	Diluent Solution	Pack (20 Ltr)	Pak
૫૪	USG Paper	Thermal Paper 110mm*20M	Roll
૫૫	ECG Paper	80mm*20m	Roll
૫૬	Macintosh	Rubber	Meter
૫૭	Test Tube Rack	24/holes Steels	Pcs
૫૮	Test Tube Rack	24/Holes Plastic	Pcs
૫૯	Vacutainer (Clot Activator)	3ml	Pcs
૬૦	EDTA Vail	3ml	Pcs
૬૧	Sodium Fluoride Vial	3ml	Pcs
૬૨	Tips Stand Rack	(10-100UL)	Pcs
૬૩	Tips Stand Rack	(100-1000UL)	Pcs
૬૪	Micropipette	10-100UL Variable	Pcs
૬૫	Micropipette	100-1000UL Variable	Pcs
૬૬	Micropipette	1000 IU Fixed	Pcs
૬૭	Test tube Brush	Medium	Pcs
૬૮	Micropore Tape	5 Meter	Pcs
૬૯	Glucometer Strips	Strips	Pcs
૭૦	Hemoglobin Strips	Strips	Pcs
૭૧	X-Ray Film	Medical X-ray Dry Films size , 10 *12 (100pcs/pkt)	PKT
૭૨	X-Ray Film	Medical X-ray Dry Films Size, 8 *10 (100pcs/pkt)	PKT

Ayurveda Medicine

s.n.	Medicine Name	Specification	Unit
1	Avipattikar churna	100gm	ph
2	Hingwastak churna	100gm	ph
3	Mahanarayan oil	60 ml	ph
4	Sitopaladi churna	100gm	ph
5	Pushyanug Churna	100gm	ph
6	Mrigamadasav	15 ml.	ph
7	Nimbadi churna	100gm	ph
8	Gandhak rasayan	10gm	ph
9	Khadiradi vati	10gm	ph
10	Yograj guggulu	25gm	ph
11	Jatyadi Tail	60 ml	ph
12	Kaishoor guggulu	25gm	ph
13	Chandraprabha vati	25gm	ph
14	Triphala churna	100gm	ph
15	Ashwagandha churna	100gm	ph
16	Bilwadi Churna	100gm	ph
17	Mahayograj Guggul	10 gm	ph
18	Jwano Churna	100gm	ph
19	Dashmool Tail	50ml	ph
20	Amalki Churna	100gm	ph
21	Shatavari Churna	100gm	ph
22	Lawan Bhaskar Churna	60gm	ph
23	Balamrit	100ml	ph
24	Shadvindu Tail	15ml	ph
25	Mahashankha Vati	10gm	ph
26	Laxmibilash Ras	10gm	ph

27	Arshakuthar Ras	10gm	ph
28	Ishabgol Powder	100gm	ph
29	Ichchhavedi Ras	10gm	ph
30	Arshoghni Vati	10gm	ph
31	Arogyabardhini Vati	10gm	ph
32	Shilajit Gold	10cap	ph
33	Shilajit Paste	25gm	ph
34	Bolbaddha Ras	10gm	ph
35	Bramhi Vati	10gm	ph
36	Lohasava	450ml	ph
37	Kumaryasav	450ml	ph
38	Rohitakyadi Churna	50gm	ph
39	Panchasakar Churna	50gm	ph
40	Ashokarista	450ml	ph
41	Dashmularista	450ml	ph
42	Khadirarista	450ml	ph
43	Abhayarista	450ml	ph
44	Kutajarista	450ml	ph
45	Chyawanprash Abaleha	500gm	ph
46	Sarpagandhaghan Vati	25gm	ph
47	Mahasudarshan Churna	100gm	ph
48	Tankan Bhasma	10gm	ph

Essential Medicine

S.N.	Particulars	Specifications	Streth
1	Acetylsalicylic acid (aspirin)	Tablet	75mg
2	Adrenaline (epinephrine)	Injection	1mg in 1ml
3	Albendazole	Chewable Tablet	400mg
4	Albendazole	Suspension	200mg/5ml
5	Aluminium hydroxide + Magnesium Hydroxide (antacid)	Tablet	250mg + 250mg
6	Amitriptyline	Tablet	10mg
7	Amitriptyline	Tablet	25mg
8	Amlodipine	Tablet	5mg
9	Amoxicillin	Oral Capsule	500mg
10	Amoxicillin	Powder for oral suspension	125mg/5ml,100 ml
11	Amoxicillin	Dispersible Tablets	125mg
12	Amoxicillin	Dispersible Tablets	250mg
13	Ampicillin	Powder for IV/IM injection	250mg vial
14	Ampicillin	Powder for IV/IM injection	500mg vial
15	Atropine	Injection	0.6mg in 1ml ampoule
16	Azithromycin	Tablets	250mg
17	Azithromycin	Tablets	500mg
18	Calamine	Lotion	15% w/v,30ml
19	Calcium gluconate	Injection	1gm per 10ml (100mg/ml of 10 ml)
20	Carbamazepine	Tablets	100mg
21	Carbamazepine	Tablets	200mg
22	Cefixime	Tablet	400 mg
23	Cefixime	Tablet	200mg
24	Cefixime	Oral suspension	100mg/5ml (30ml)
25	Ceftriaxone	Powder for Injection	250mg/ vial
26	Ceftriaxone	Powder for Injection	500mg/vial
27	Ceftriaxone	Powder for Injection	1gm w/vial
28	Cetirizine HCL	Tablet	10mg
29	Cetirizine HCL	syrup	5mg/5ml (30ml)
30	Charcoal, activated	Powder in sachet	10gm
31	Chlorhexidine (CHX)	Solution	Solution, 0.2% oral 50ml
32	Chlorhexidine (CHX)	Ointment	4%,5gm
33	Chloroquine (CQ)	Tablet	150mg
34	Ciprofloxacin	Tablets	250mg
35	Ciprofloxacin	Tablets	500mg
36	Ciprofloxacin	Eye/Ear Drops	0.3%w/v, 5ml ,
37	Ciprofloxacin	Eye ointment	0.3%, 5g
38	Ciprofloxacin	Injection	200mg/100ml
39	Clotrimazole	skin cream	1%, 25g
40	Clotrimazole	Vaginal Tablets	100mg
41	Clotrimazole	Mouth Paint	1%w/v ,15 ml
42	Clove Oil	Liquid	5ml
43	Cloxacillin	Capsules	250mg
44	Cloxacillin	Capsules	500mg
45	Cloxacillin	Powder for oral liquid	125mg/5ml in100ml

46	Cotrimoxazole (Sulphamethoxazole and Trimethoprim 4:1)	Tablets	400 mg + 80mg
47	Cotrimoxazole (Sulphamethoxazole and Trimethoprim 4:1)	Tablets	800mg + 160mg
48	Cotrimoxazole (Sulphamethoxazole and Trimethoprim 4:1)	syrup	200mg + 40mg/5ml, 50ml
49	Dexamethasone	Injection	4mg in 1ml ampoule
50	Dextrose (glucose)	Injection/soln	5%,500ml
51	Dextrose (glucose)	Injection/soln	25% of 50ml Amp
52	Diazepam	Injection	2ml amp (5mg/ml)
53	Diazepam	Tablet	5mg
54	Diclofenac sodium	Tablet	50mg,
55	Diclofenac sodium	Injection	3ml ampoule (25mg/ml)
56	Doxycycline	capsule	100mg
57	Ferrous sulphate and folic acid	Tablet	60mg elemental iron plus 400mcg folic acid
58	Fluconazole	Capsule	150mg
59	Fluoxetine	Capsule	20mg
60	Folic acid	Tablet	5mg
61	Furosemide	Tablet	40mg
62	Gentamicin	Injection	40mg/ml in 2ml
63	Gentian Violet	Aqueous solution	1% , 10 ml
64	Glimepiride	Tablets	1mg
65	Glimepiride	Tablets	2mg
66	Hydrocortisone	Powder for injection	100mg in vial
67	Hyoscine butylbromide	Injection	Inj 20mg/ml
68	Hyoscine butylbromide	Tablet	10mg
69	Ibuprofen	Tablets	200mg
70	Ibuprofen		400mg
71	Ibuprofen	Syrup	100mg/5ml
72	Lignocaine hydrochloride	Injection	2 % in vial,30 ml
73	Lignocaine with adrenaline 1:10,000	Injection	2% plus Adrenalin 1:10,000,30 ml
74	Losartan	Tablets	25mg
75	Losartan	Tablets	50mg
76	Magnesium sulphate	Injection	500mg/ml in 2ml ampoule
77	Metformin	Tablets	500mg,
78	Metformin	Tablets	850 mg
79	Metformin	Tablets	1000mg
80	metoclopramide	Tablet	10mg
81	metoclopramide	Solution	5mg/5ml (15ml)
82	metoclopramide	Injection	5mg/ml in 2ml ampoule
83	Metronidazole	Tablets	200mg
84	Metronidazole	Tablets	400mg
85	Metronidazole	Oral liquid	200mg/5ml ,90 ml
86	Metronidazole	Injection	500mg/100ml
87	Mifepristone + Misoprostol	Tablet	combi pack includes 200mg + 4(200) mcg
88	Misoprostol	Tablet	200mcg
89	Neomycin skin	Ointment	2% w/w 10gm
90	Nifedipine	Tablet	10mg
91	Nitrofurantion	Tablet	100mg
92	Normal Saline (NS)	Solution	0.9% Infusion solution, 500ml
93	Oral Rehydration Salts (ORS)	Powder	WHO formula sachet
94	Oxygen	Inhalation	Medicinal Gas
95	Oxymetazoline	Nasal drop	0.025%: 10ml,
96	Oxymetazoline	Nasal drop	0.05% 10ml
97	Paracetamol	Injection	150mg/ml in 2ml ampoule
98	Paracetamol	Tablet	500mg
99	Paracetamol	Syrup	125mg/5ml,50ml
100	Permethrin	Lotion	1% 100 ml
101	Permethrin	Cream	5% w/v 30g
102	Pheniramine	Injection	22.75mg/ml 2ml
103	Phenobarbital	Tablet	30mg
104	Povidone iodine	Solution	5%w/v 500ml
105	Potassium Chloride	Injection	150mg/ml
106	Prednisolone	Tablets	5mg
107	Prednisolone	Tablets	10mg
108	Prednisolone	Tablets	20mg
109	Primaquine	Tablet	7.5mg
110	Pyridoxine	Tablet	10mg
111	Ranitidine	Tablet	150mg
112	Ranitidine	Injection	25mg/ml in 2ml ampoule

113	Ringer's Lactate (RL)	Solution	500ml
114	Risperidone	Tablets	1mg
115	Risperidone	Tablets	2mg
116	Salbutamol	Solution for nebulisation	1mg/ml of 15 ml
117	Salbutamol	Oral Liquid	2mg/5ml (60ml)
118	Salbutamol	MDI	100mcg
119	Silver sulfadiazine	Cream	0.2% w/v 15g
120	Tetanus Toxoid (TT)	Injection	0.5ml /dose
121	Tetracycline	Eye ointment	1%, 5g
122	Tinidazole	Tablet	500mg
123	Vitamin B complex	Tablet	Thiamine 10mg, riboflavin 10mg, pyridoxie 3mg, cyanocobalamin 15 mcg. (Therapeutic dose)
124	Zinc sulphate	Dispersible Tablets	10mg
125	Zinc sulphate	Dispersible Tablets	20mg
126	Calcium	Tab	an oral supplement containing 500 mg of elemental calcium and 250 IU of Vitamin D3
127	Mifepristone + misoprostol	Strip (Dose)	mifepristone (200 mg) and four tablets of misoprostol (200 µg each)
128	Levonorgestrel	Tab	1.5 mg (Pharmacological Class Emergency hormonal contraceptive)

निर्माण सम्बन्धी सामग्रीहरू

क्र.स.	मालसामानको विवरण	स्पेसिफिकेसन	एकई
१	Telia brick	(thickness 2"), size: 8"x8"	थान
२	Urinal Sensor	Mini Concealed Type (SNR-STL-51083 or equivalent)	set
३	Urinal (Back inlet)	fixing Accessories, Size 385*325*635 mm (URS-WHT-13253N)	सेट
४	४ इन्च बाक्लो इटा साइजको मेशिन कटिङ्ग ढुङ्गा	(९ इन्च * ४ इन्च)	piece
५	३ इन्च बाक्लो इटा साइजको मेशिन कटिङ्ग ढुङ्गा	(९ इन्च * ४ इन्च)	piece

Sanitary Works - HDPE Pipe

क्र.स.	Description of Works	Unit	Quantity
१	110mm dia. HDP Pipe (4 Kg/cm2)	RM	1
२	125mm dia. HDP Pipe (4 Kg/cm2)	RM	1
३	140mm dia. HDP Pipe (4 Kg/cm2)	RM	1
४	160mm dia. HDP Pipe (4 Kg/cm2)	RM	1
५	180mm dia. HDP Pipe (4 Kg/cm2)	RM	1
६	200mm dia. HDP Pipe (4 Kg/cm2)	RM	1
७	50mm dia. HDP Pipe (6 Kg/cm2)	RM	1
८	110mm dia. HDP Pipe (6 Kg/cm2)	RM	1
९	125mm dia. HDP Pipe (6 Kg/cm2)	RM	1
१०	140mm dia. HDP Pipe (6 Kg/cm2)	RM	1
११	160mm dia. HDP Pipe (6 Kg/cm2)	RM	1
१२	180mm dia. HDP Pipe (6 Kg/cm2)	RM	1
१३	200mm dia. HDP Pipe (6 Kg/cm2)	RM	1
१४	50mm dia. HDP Pipe (10 Kg/cm2)	RM	1
१५	110mm dia. HDP Pipe (10 Kg/cm2)	RM	1
१६	125mm dia. HDP Pipe (10 Kg/cm2)	RM	1
१७	140mm dia. HDP Pipe (10 Kg/cm2)	RM	1
१८	160mm dia. HDP Pipe (10 Kg/cm2)	RM	1
१९	180mm dia. HDP Pipe (10 Kg/cm2)	RM	1
२०	200mm dia. HDP Pipe (10 Kg/cm2)	RM	1

Road Works - Stone Paving Works

क्र.स.	Description of Works	Unit	Quantity
१	४" बाक्लो कालो मेसिन कटीड ढुंगा	Sq.Ft	1
२	४" बाक्लो सेतो मेसिन कटीड ढुंगा	Sq.Ft	1
३	३" बाक्लो कालो मेसिन कटीड ढुंगा	Sq.Ft	1
४	३" बाक्लो सेतो मेसिन कटीड ढुंगा	Sq.Ft	1

Road Works - Interlocking Block Paving Works

क्र.स.	Description of Works	Unit	Quantity
१	Rectangular Interlocking Pavers Multi Color Blended with compressive strength M35 or above , Thickness 60 mm , Dimension 200*100*60 (NS Standard)	Sq.m	1
२	Matrix Slab/Tile/Tack Tile Single Color with compressive strength M35 or above , Thickness 60 mm , Dimension 400*400*60 (NS Standard)	Sq.Ft	1
३	Matrix Slab/Tile/Tack Tile Single Color with compressive strength M35 or above , Thickness 40 mm , Dimension 400*400*40 (NS Standard)	Sq.Ft	1

Electrical Works

क्र.स.	Description of Works	Unit	Quantity
१	Bed Switch	Nos	1
२	Bulb Cover Umbrella	Nos	1
३	Safety Gloves	Pair	1
४	Pendent holder screw type	Nos	1
५	Pendent Holder Pin Type	Nos	1
६	Metal Body street light bulb cover	Nos	1
७	Plastic Body street light bulb cover	Nos	1
८	Light Number plate (8*5) inches	Nos	1
९	Day night sensor for auto on-off for street light	Nos	1
१०	20-30 watt printed circuit board (PCB) Osram, Philips or equivalent	Nos	1
११	40-50 watt printed circuit board (PCB) Osram, Philips or equivalent	Nos	1
१२	100-120 watt printed circuit board (PCB) Osram, Philips or equivalent	Nos	1
१३	20-30 watt high quality LED Power Driver	Nos	1
१४	40-50 watt high quality LED Power Driver	Nos	1
१५	100-120 watt high quality LED Power Driver	Nos	1
१६	street light Arms/stand, 0.5 to 0.7 mtr long	Nos	1
१७	Installation of Street light	Set	1
१८	Installation of street light (बिग्रेको लाईट फिल्ड बाट झिक्री ओर्कशोपमा लगी सामान्य मर्मत सुधार गरी पून फिल्डमा जडान)	Set	1

Electrical Works

क्र.स.	Description of Works	Unit	Quantity
१	Dimming Street Light		
	Supply of LED AC street light with auto on-off switch and auto dimming (Three Step Dimming or as per specific requirements.) operation including all accessories. (Connecting Cable 2.5 sq mm copper cable or 6 sq mm aluminium cable, Identity mark of street light etc.) 110V -270 volt, Aluminim die-cast with good heat sink fins, P.F≥0.95 (at full load), IP≥66, IK 09 or above, Filker free, THD<10%, CRI>70, luminous efficiency ≥140 lm/watt, SPD:4 (Internal)/10KV(External), CCT 3500K to 4500K, Class-II, The Light should have provision for smart control (i.e. Centrally Control and Monitoring System, CCMS) having manufacture's warranted from authorized dealer/manufacture for minium of 5 years:		
	50 Watt	Set	1

	80 Watt	Set	1
	100 Watt	Set	1
	120 Watt	Set	1
	150 Watt	Set	1
२	Feeder Panel		
	Supply, installation, Testing and commissioning of an outdoor feeder panel/control cabinet, The panel shall include Copper Bus Bar and a copper rod earthing system as per IS standards, with separate earthing for the body and the Surge Protection Device (SPD, appropriate size of SPD should be Installed and should be earthing properly at coated price), ensuring proper grounding and corrosion protection for outdoor conditions. The cabinet shall be constructed from galvanized steel or powder-coated 2 mm thick CRCA sheet, with a minimum IP65 rating to ensure full protection against dust and water ingress. The design must include surge protection to safeguard electrical components, a tamper-resistant locking mechanism for security, and weatherproof cable glands at entry/exit points to prevent moisture ingress. Provisions for easy installation and visibility of an energy meter shall be incorporated, ensuring accessibility for readings and maintenance. Adequate ventilation or cooling will be provided to prevent overheating in direct sunlight, and the overall design will be suitable for the local climate, ensuring durability and reliability in harsh outdoor conditions.	Set	1
३	Panel Accessories		
	10/16 Amp DP Contractor	Nos	1
	10/16 TP Contractor	Nos	1
	10/16 FP Contractor	Nos	1
	25 Amp DP Contractor	Nos	1
	32 Amp DP Contractor	Nos	1
	32 Amp TP Contractor	Nos	1
	32 Amp FP Contractor	Nos	1
	40 Amp TP Contractor	Nos	1
	40 Amp FP Contractor	Nos	1
	63 Amp TP Contractor	Nos	1
	63 Amp FP Contractor	Nos	1
	Astronomical Timer	Nos	1

सम्पदा तथा पर्यटन सँग सम्बन्धित

क्र.सं.	Description	Unit	
१	ढुङ्गाको गजुर (३'४" डायमिटर, ४÷४" उचाई)	No.	
२	ढुङ्गाको गजुर (१' बेस डायमिटर, १'८" उचाई)	No.	
३	ढुङ्गाको गजुर (३'५" डायमिटर, ४÷५" उचाई)	No.	
४	ढुङ्गाको पिलर (८"×८"×७'८")	No.	
५	ढुङ्गाको पिलरको बेस (१'४"×१'४"×८")	No.	
६	ढुङ्गाको विम(८"×८"×६'१०")	No.	
७	ढुङ्गाको विम(८"×८"×४'८")	No.	
८	५" बाक्लो ढुङ्गा बाट स्लोप छाना बनाउने कार्य (ढुङ्गा को नाप १२"×१०"×५")	R.ft.	
९	५+++ बाक्लो ढुङ्गा बाट (टुवा ज्य) स्लोप छानाको किनारा बनाउने कार्य	R.ft.	
१०	५" बाक्लो ढुङ्गा खल नागोल काँनेश बनाउने कार्य	R.ft.	
११	ढुङ्गा बाट ३" मोटाईको गोल नागोल बनाउने कार्य	R.ft.	
१२	ढुङ्गा बाट विभिन्न वुट्टेदार काँनेश बनाउने कार्य(२"×३"×४")	R.ft.	

१३	ढुङ्गाको तोरण, फ्रेम बेस आदी सहित को ढोका (लम्बाई ४'२" * उचाई ६'४")	No.	
१४	ढुङ्गेधारा सानो (३' भन्दा सानो), बुझा कुदेको	No.	
१५	ढुङ्गेधारा सानो ३' भन्दा ठुलो (४' भन्दा सानो), बुझा कुदेको	No.	
१६	ढुङ्गेधारा ४' भन्दा ठुलो (५' भन्दा सानो), बुझा कुदेको	No.	
१७	ढुङ्गा मूर्ति (९" * १६")	No.	
१८	ढुङ्गा मूर्ति (१२" * १८")	No.	
१९	बारको स्तम्भको साइज (१८"x१२" x४') मा प्रिक्कास्ट ईटाको बुझा कुँदिएको र बुझाको काम, फिक्सिड गर्ने, सतह सफा गर्ने लगायत लेभल मिलाउने काम, डिजाइन रेखाचित्र अनुसार गर्ने काम	No.	
२०	बारको स्तम्भको साइज (१५"x११" x३.५') मा प्रिक्कास्ट ईटाको बुझा कुँदिएको र बुझाको काम, फिक्सिड गर्ने, सतह सफा गर्ने लगायत लेभल मिलाउने काम, डिजाइन रेखाचित्र अनुसार गर्ने काम	No.	
२१	ढुङ्गाको मुर्ति ५"x८"	थान	
२२	ढुङ्गाको मुर्ति ७"x१०"	थान	
२३	ढुङ्गाको मुर्ति ८"x१२"	थान	
२४	ढुङ्गाको मुर्ति १०"x१५"	थान	
२५	ढुङ्गाको मुर्ति १२"x१८"	थान	
२६	ढुङ्गाको सिंहको मुर्ति ४' फिट अग्लो	थान	
२७	ढुङ्गाको सिंहको मुर्ति ३' फिट अग्लो	थान	
२८	ढुङ्गाको सिंहको मुर्ति २' फिट अग्लो	थान	
२९	ढुङ्गाको सिंहको मुर्ति १८ इन्च अग्लो	थान	
३०	Type-1 stone hiti 1 feet length (medium)	piece	
३१	Type-1 stone hiti 1.5 feet length (medium)	piece	
३२	Type-1 stone hiti 2 feet length (medium)	piece	
३३	Type-1 stone hiti 2.5 feet length (medium)	piece	
३४	Type-1 stone hiti 3 feet length (medium)	piece	
३५	Type-1 stone hiti 3 feet length (heavy)	piece	
३६	Type-1 stone hiti 4 feet length (medium)	piece	
३७	Type-1 stone hiti 4 feet length (heavy)	piece	
३८	Type-1 stone hiti 5 feet length (medium)	piece	
३९	Type-1 stone hiti 5 feet length (heavy)	piece	
४०	Type-2 stone hiti 1 feet length (medium)	piece	
४१	Type-2 stone hiti 1.5 feet length (medium)	piece	
४२	Type-2 stone hiti 2 feet length (medium)	piece	
४३	Type-2 stone hiti 2.5 feet length (medium)	piece	
४४	Type-2 stone hiti 3 feet length (medium)	piece	
४५	Type-2 stone hiti 3 feet length (heavy)	piece	
४६	Type-2 stone hiti 4 feet length (medium)	piece	
४७	Type-2 stone hiti 4 feet length (heavy)	piece	
४८	Type-2 stone hiti 5 feet length (medium)	piece	
४९	Type-2 stone hiti 5 feet length (heavy)	piece	